

Package ‘dvir’

June 30, 2026

Type Package

Title Disaster Victim Identification

Version 3.4.2

Description Joint DNA-based disaster victim identification (DVI), as described in Vigeland and Egeland (2021) [doi:10.21203/rs.3.rs-296414/v1](https://doi.org/10.21203/rs.3.rs-296414/v1). Identification is performed by optimising the joint likelihood of all victim samples and reference individuals. Individual identification probabilities, conditional on all available information, are derived from the joint solution in the form of posterior pairing probabilities. 'dvir' is part of the 'pedsuite' collection of packages for pedigree analysis.

License GPL-3

URL <https://github.com/magnusdv/dvir>

BugReports <https://github.com/magnusdv/dvir/issues>

Depends pedtools (>= 2.11.0), R (>= 4.2.0)

Imports forrel (>= 1.9.0), mirai, pedFamilias, pedprobr (>= 1.1.0), ribd, verbalisr

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Encoding UTF-8

Language en-GB

LazyData true

Config/roxygen2/version 8.0.0

Config/testthat/edition 3

NeedsCompilation no

Author Magnus Dehli Vigeland [aut, cre] (ORCID: <https://orcid.org/0000-0002-9134-4962>),
Thore Egeland [aut] (ORCID: <https://orcid.org/0000-0002-3465-8885>)

Maintainer Magnus Dehli Vigeland <m.d.vigeland@medisin.uio.no>

Repository CRAN

Date/Publication 2026-06-30 14:50:02 UTC

Contents

addVictims	3
amDrivenDVI	3
Bmarginal	4
directMatch	5
dviCompare	6
dviData	8
dviGLR	9
dviGridSize	10
dviJoint	11
dviSim	12
dviSolve	13
example1	15
example2	15
excludePairing	16
exclusionExample	17
expand.grid.nodup	17
familias2dvir	18
findExcluded	20
findNonidentifiable	21
findUndisputed	22
fire	24
formatSummary	25
generatePairings	26
getDatabase	27
getFamily	27
getSimpleFams	28
grave	29
icmp	29
jointDVI	30
KETPchap481	32
KETPchap484	33
KETPexer497	33
KETPexer498	34
mergePM	35
ncomb	36
pairwiseLR	37
planecrash	38
plotDVI	39
plotSolution	40
plotUndisputed	41
relabelDVI	42
sequentialDVI	43
setPairing	45
subsetDVI	46
swapOrientation	47
symmetricSibs	48

addVictims	<i>Add victim samples to a DVI dataset</i>
------------	--

Description

This is a convenience function for adding new victim samples to an existing `dviData()` object. Users are recommended to use this instead of manipulating the pm data directly, as it ensures consistency of the output and also recomputes the internal pairings object.

Usage

```
addVictims(dvi, newvics)
```

Arguments

dvi	A <code>dviData()</code> object.
newvics	A singleton object or a list of such.

Value

A new `dviData()` object with the new victims added to the pm data.

Examples

```
addVictims(example1, singleton("V4"))
```

amDrivenDVI	<i>AM-driven DVI</i>
-------------	----------------------

Description

AM-driven identification, i.e., considering one AM family at a time. Simple families (exactly 1 missing) are handled directly from the LR matrix, while nonsimple families are analysed with `dviJoint()`.

Usage

```
amDrivenDVI(
  dvi,
  fams = NULL,
  threshold = 10000,
  threshold2 = max(1, threshold/10),
  verbose = TRUE
)
```

Arguments

dvi	A dviData object.
fams	A character; the names of families to consider. By default, all families. Special keywords: "simple" (all families with exactly 1 missing) and "nonsimple" (all families with > 1 missing).
threshold	LR threshold for 'certain' match.
threshold2	LR threshold for 'probable' match (in <i>simple</i> families).
verbose	A logical.

Details

Note: This function assumes that undisputed identifications have been removed. Strange outputs may occur otherwise.

Value

A list of dviReduced and summary.

Examples

```
w = amDrivenDVI(example2)
w$summary
w$dviReduced

# Bigger example: Undisputed first
u = findUndisputed(planecrash)
u$summary

# AM-driven analysis of the remaining
amDrivenDVI(u$dviReduced, threshold2 = 500)
```

Bmarginal

Posterior pairing probabilities

Description

Compute posterior pairing and non-pairing probabilities, based on a prior and the output from [jointDVI\(\)](#).

Usage

```
Bmarginal(jointRes, missing, prior = NULL)
```

Arguments

jointRes	Output from <code>jointDVI()</code> .
missing	Character vector with names of missing persons.
prior	A numeric vector of length equal the number of rows in jointRes. Default is a flat prior.

Details

The prior assigns a probability to each assignment, each row of jointRes. If the prior is not specified, a flat prior is used. The prior needs not sum to 1 since the user may rather choose a flat prior on the *a priori* possible assignments.

Value

A matrix. Row *i* gives the posterior probability that victim *i* is one of the missing persons or someone else, denoted '**'.

See Also

`jointDVI()`

Examples

```
jointRes = jointDVI(example1)

Bmarginal(jointRes, example1$missing)

# Artificial example: all but optimal solution excluded by prior
Bmarginal(jointRes, example1$missing, prior = c(1, rep(0,26)))
```

directMatch

Direct match LR

Description

Computes the likelihood ratio comparing if two samples are from the same individual or from unrelated individuals.

Usage

```
directMatch(x, y, g1 = NULL, g2 = NULL, .skipChecks = FALSE)
```

Arguments

`x, y` Typed singletons.
`g1, g2` (Optional) Named character vectors with genotypes for `x` and `y` respectively.
`.skipChecks` A logical indicating that various input checks can be skipped, e.g. when called by `mergePM()`.

Value

A nonnegative likelihood ratio.

See Also

[mergePM\(\)](#).

Examples

```
pm = singletons(c("V1", "V2", "V3")) |>
  addMarker(V1 = "1/1", V2 = "2/2", V3 = "1/1",
            afreq = c("1" = 0.01, "2" = 0.99), name = "L1")

directMatch(pm[[1]], pm[[2]])
directMatch(pm[[1]], pm[[3]])
```

dviCompare

Compare DVI approaches

Description

Legacy helper for comparing different computational approaches to DVI.

Usage

```
dviCompare(
  dvi,
  true,
  refs = NULL,
  methods = 1:6,
  markers = NULL,
  threshold = 1,
  simulate = TRUE,
  db = NULL,
  Nsim = 1,
  returnSims = FALSE,
  seed = NULL,
  numCores = 1,
  verbose = TRUE
)
```

Arguments

dvi	A dviData object, typically created with <code>dviData()</code> . If <code>simulate = FALSE</code> , a list of such objects.
true	A character of the same length as <code>dvi\$pm</code> , with the true solution, e.g. <code>true = c("M2", "M3", "*")</code> if the truth is $V1 = M2$, $V2 = M3$ and $V3$ unmatched.
refs	Character vector with names of the reference individuals. By default the typed members of <code>dvi\$am</code> .
methods	A subset of the numbers 1,2,3,4,5,6.
markers	If <code>simulate = FALSE</code> : A vector indicating which markers should be used.
threshold	An LR threshold passed on to the sequential methods.
simulate	A logical, indicating if simulations should be performed.
db	A frequency database used for simulation, e.g. <code>forrel::NorwegianFrequencies</code> . By default the frequencies attached to <code>dvi\$am</code> are used.
Nsim	A positive integer; the number of simulations.
returnSims	A logical: If TRUE, the simulated data are returned without any DVI comparison.
seed	A seed for the random number generator, or NULL.
numCores	Deprecated and ignored.
verbose	A logical.

Details

NOTE: This is a legacy function, mainly kept for reproducibility of older analyses. It is not part of the recommended `dvir` workflow. Use with caution.

The following methods are available through the `methods` parameter:

1. Sequential, without LR updates.
2. Sequential, with LR updates.
3. Sequential (undisputed) + joint (remaining). Always returns the most likely solution(s).
4. Joint - brute force. Always returns the most likely solution(s).
5. Like 3, but returns the winner(s) only if $LR > \text{threshold}$; otherwise the empty assignment.
6. Like 4, but returns the winner(s) only if $LR > \text{threshold}$; otherwise the empty assignment.

Value

A list of solution frequencies for each method, and a vector of true positive rates for each method.

Examples

```
db = forrel::NorwegianFrequencies[1:6]

# True solution: V1 = M1, while V2/V3 are the siblings M2/M3
true = c("M1", "M2", "M3")
```

```
# Increase Nsim for accurate estimates
dviCompare(fire, true = true, db = db, Nsim = 2, seed = 1)

# Simulations can also be generated first
sims = dviCompare(fire, true = true, db = db, Nsim = 2, seed = 1,
                  returnSims = TRUE)
dviCompare(sims, true = true, simulate = FALSE)
```

dviData

DVI data

Description

DVI data

Usage

```
dviData(pm, am, missing, generatePairings = TRUE)

checkDVI(
  dvi,
  pairings = NULL,
  errorIfEmpty = FALSE,
  ignoreSex = FALSE,
  verbose = TRUE
)
```

Arguments

pm	A list of singletons: The victim samples.
am	A list of pedigrees: The reference families.
missing	A character vector with names of missing persons.
generatePairings	A logical. If TRUE (default) a list of sex-compatible pairings is included as part of the output.
dvi	A dviData object.
pairings	A list of pairings.
errorIfEmpty	A logical.
ignoreSex	A logical.
verbose	A logical.

Value

An object of class dviData, which is basically a list of pm, am, missing and pairings.

Examples

```
dvi = dviData(pm = singleton("V1"), am = nuclearPed(1), missing = "3")
dvi

checkDVI(dvi)
```

dviGLR

*Finds Generalised Likelihood Ratios (GLRs)***Description**

Based on a dviData object, or output from dviJoint() or jointDVI(), the GLR, the ratio of the maximum likelihood under H0 to the maximum under H1, is calculated for specified hypotheses.

Usage

```
dviGLR(dvi, pairings = generatePairings(dvi), dviRes = NULL)
```

Arguments

dvi	A dviData object.
pairings	List. See details.
dviRes	data frame. Output from jointDVI().

Details

The Generalised Likelihood Ratio (GLR) statistic is defined as the ratio of the maximum likelihood for the alternatives in the numerator to the maximum in the denominator. The default pairings = dvi::generatePairings(dvi) tests all hypotheses. Specific tests can be specified as shown in an example: pairings = list(V1 = "M1") gives a test for H0: V1 = M1 against H1: V1 != M1. dviRes will be calculated using jointDVI() if not provided.

Value

A data frame with GLRs and SGLR (strict GLR, max replaced by min in the numerator).

Examples

```
# dviGLR(example2, pairings = list(V1 = "M1"))

# All tests with output from jointDVI
# dviGLR(example2)
```

dviGridSize	<i>Size of joint assignment grid</i>
-------------	--------------------------------------

Description

Calculates how many rows would be produced by `expand.grid.nodup()`, either exactly or as a guaranteed lower bound. This is used to detect DVI problems where a joint search would be prohibitive.

Usage

```
dviGridSize(dvi = NULL, pairings = NULL, ignoreSex = FALSE, max = Inf)
```

Arguments

dvi	A dviData object. If pairings is not supplied, candidate pairings are taken from dvi\$pairings, or generated with <code>generatePairings()</code> .
pairings	A list of character vectors, typically produced by <code>generatePairings()</code> . If supplied, dvi is ignored.
ignoreSex	A logical, passed on to <code>generatePairings()</code> if pairings are generated from dvi.
max	A positive number. Exact counting may stop once the count is known to exceed this value. Default: Inf.

Details

Exact counting is done without constructing the full table. The algorithm counts matchings in the bipartite graph between victims and missing persons, treating the non-assignment value "*" as a repeatable choice. For large problems, the function returns a lower bound instead of the exact count. (See Value.)

Value

A list with elements size (a number) and type (either "exact" or "lower bound").

See Also

`expand.grid.nodup()`, `dviJoint()`, `generatePairings()`, `ncomb()`

Examples

```
dviGridSize(example1)

pairings = generatePairings(example1)
dviGridSize(pairings = pairings)
```

dviJoint

*Joint DVI search***Description**

dviJoint() performs a joint likelihood search over candidate assignments in a DVI problem, ranking all assignments and returning both PM-oriented and AM-oriented assignment columns. It is used internally by [dviSolve\(\)](#) for unresolved complex families. Compared with the legacy [jointDVI\(\)](#), it does not perform preprocessing steps such as exclusions or undisputed matches.

Usage

```
dviJoint(
  dvi,
  assignments = NULL,
  ignoreSex = FALSE,
  disableMutations = FALSE,
  maxAssign = 1e+05,
  numCores = 1,
  cutoff = 0,
  verbose = TRUE,
  progress = interactive()
)
```

Arguments

dvi	A dviData object, typically created with dviData() .
assignments	A data frame containing the assignments to be considered in the joint analysis. By default, this is automatically generated by taking all combinations from dvi\$pairings.
ignoreSex	A logical, only relevant if dvi\$pairings is NULL, so that candidate pairings have to be generated.
disableMutations	Either TRUE, FALSE (default) or NA. If NA, mutation modelling is applied only in families where the reference data are incompatible with the pedigree unless at least one mutation has occurred.
maxAssign	A positive integer. If the number of assignments going into the joint calculation exceeds this, the function will abort with an informative error message. Default: 1e5.
numCores	Deprecated and ignored.
cutoff	Currently ignored.
verbose	A logical.
progress	A logical, indicating if a progress bar should be shown.

Value

A data frame.

Examples

```
dviJoint(example2)
```

dviSim

Simulate genotypes in a DVI dataset

Description

Simulates genotypes for the references and missing persons in each AM family, transfers to the PM singletons according to the indicated matching. Remaining victims are simulated as unrelated.

Usage

```
dviSim(
  dvi,
  N = 1,
  refs = typedMembers(dvi$am),
  truth = NULL,
  seed = NULL,
  conditional = FALSE,
  simplify1 = TRUE,
  verbose = FALSE
)
```

Arguments

dvi	A dviData object.
N	The number of complete simulations to be performed.
refs	A character indicating reference individuals. By default, the typed members of the input. If conditional = TRUE, the refs should be a subset of the typed members, and the simulations are conditional on these.
truth	A named vector of the format c(vic1 = mis1, vic2 = mis2, ...).
seed	An integer seed for the random number generator.
conditional	A logical, by default FALSE. If TRUE, references are kept unchanged, while the missing persons are simulated conditional on these.
simplify1	A logical, by default TRUE, removing the outer list layer when N = 1. See Value.
verbose	A logical.

Value

If $N = 1$, a dviData object similar to the input, but with new genotypes for the pm samples. If $N > 1$, a list of dviData objects.

See Also

`forrel::profileSim()`.

Examples

```
# Simulate refs and missing once and plot:
ex = dviSim(example2, N = 1, truth = c(V1 = "M1", V2 = "M2", V3 = "M3"))
plotDVI(ex, marker = 1)

# Two simulations and plot for the first
ex = dviSim(example2, N = 2, truth = c(V1 = "M1", V2 = "M2", V3 = "M3"),
          seed = 1729)
plotDVI(ex[[1]], marker = 1)
```

Description

Wraps the main dviR workflow for DVI analysis and identification of likely AM–PM matches.

Usage

```
dviSolve(
  dvi,
  threshold = 10000,
  threshold2 = max(1, threshold/10),
  maxIncomp = 2,
  ignoreSex = FALSE,
  limit = 0,
  maxAssign = 1e+05,
  detailedOutput = FALSE,
  verbose = TRUE,
  debug = FALSE
)
```

Arguments

<code>dvi</code>	A <code>dviData</code> object.
<code>threshold</code>	LR threshold for 'significant' match.
<code>threshold2</code>	LR threshold for 'probable' match. By default set to <code>threshold/10</code> .
<code>maxIncomp</code>	An integer passed onto <code>findExcluded()</code> . A pairing is excluded if the number of incompatible markers exceeds this.
<code>ignoreSex</code>	A logical, by default <code>FALSE</code> .
<code>limit</code>	A number passed onto <code>findUndisputed()</code> ; only pairwise LR values above this are considered.
<code>maxAssign</code>	A positive integer, or <code>Inf</code> ; the maximum number of assignments allowed in a joint analysis. Default: <code>1e5</code> .
<code>detailedOutput</code>	A logical, by default <code>FALSE</code> . See Details.
<code>verbose, debug</code>	Logicals.

Details

The function roughly implements the following workflow:

- **Preparation and QC**
 - Consolidate data and validate input: `checkDVI()`
 - Generate pairings: `generatePairings()`
- **Initial reduction**
 - Detect and remove nonidentifiable missing persons: `findNonidentifiable()`
- **Iterative reduction** (repeat until stable)
 - Excluded individuals and pairings: `findExcluded()`
 - Undisputed matches from pairwise LRs: `findUndisputed()`
- **AM-driven analysis**: `amDrivenDVI()`
 - Simple families (1 missing): Summarise conflicting results
 - Complex families (>1 missing): Joint analysis + GLR
- **PM-driven analysis**
 - Summarise remaining victim samples.
- **Output**
 - Format AM and PM summaries: `formatSummary()`

Value

A list of data frames AM and PM summarising the results.

If `detailedOutput = TRUE`, the output also includes:

- `LRmatrix`: the LR matrix from the first call to `findUndisputed()`
- `exclusionMatrix` the exclusion matrix from the first call to `findExcluded()`
- `jointTables`: a list of joint tables for each complex family

Examples

```
dviSolve(example2)
dviSolve(example2, threshold = 5, detailedOutput = TRUE, verbose = FALSE)
```

example1

DVI dataset: Generational trio

Description

A proof-of-concept dataset involving three missing members (child, father, grandfather) of a single family. With the given data, stepwise victim identification fails to find the correct solution, while joint identification succeeds.

Usage

```
example1
```

Format

A dviData object with the following content:

- pm: A list of 3 singletons (victims).
- am: A pedigree with three missing persons and one typed reference individual.
- missing: A vector containing the names of the missing persons.

Examples

```
example1
plotDVI(example1, marker = 1)

jointDVI(example1)
```

example2

DVI dataset: Two reference families

Description

A small DVI example with three victims, and three missing persons from two reference families

Usage

```
example2
```

Format

A dviData object with the following content:

- pm: A list of 3 singletons (victims).
- am: A list of 2 pedigrees with three missing persons and one typed reference individual.
- missing: A vector containing the names of the missing persons.

Examples

```
example2
plotDVI(example2, marker = 1)

jointDVI(example2)
```

excludePairing	<i>Exclude pairings</i>
----------------	-------------------------

Description

Disallow certain pairings by removing them from the list dvi\$pairings of candidate pairings for a given victim sample.

Usage

```
excludePairing(dvi, victim, missing)
```

Arguments

dvi	A dviData object.
victim	The name of a single victim sample.
missing	The name(s) of one or several missing individuals.

Value

A dviData object.

Examples

```
# Disallow V1 = M1 in the `example2` dataset:
ex = excludePairing(example2, victim = "V1", missing = "M1")
jointDVI(ex, verbose = FALSE)

# Compare with original
jointDVI(example2, verbose = FALSE)

# The only difference is in the `pairings` slot:
ex$pairings
example2$pairings
```

exclusionExample	<i>Dataset: Exclusion example</i>
------------------	-----------------------------------

Description

This data is based on a real case, but pedigrees have been changed and marker data simulated to preserve anonymity.

Usage

```
exclusionExample
```

Format

A dviData object with the following content:

- pm: A list of 16 singletons (male victims).
- am: A list of 15 pedigrees, each with one missing person
- missing: A vector containing the names of the 15 missing persons.

Examples

```
exclusionExample
```

expand.grid.nodup	<i>Assignment grid for joint analysis</i>
-------------------	---

Description

Given a list of candidate pairings for each victim, `expand.grid.nodup()` constructs the corresponding assignment table. This is similar to `expand.grid()`, but excludes assignments where the same missing person is used more than once. The special value "*" is treated as non-assignment and may be repeated. This is used by `dviJoint()` to enumerate joint assignments.

Usage

```
expand.grid.nodup(  
  pairings = NULL,  
  max = 1e+05,  
  df = TRUE,  
  verbose = FALSE,  
  lst = NULL  
)
```

Arguments

pairings	A list of character vectors, typically produced by <code>generatePairings()</code> . Each list entry gives the possible assignments for one victim.
max	A positive number. If the grid size exceeds this, the function aborts with an informative error message. Default: 1e5.
df	A logical, indicating if the function should return a data frame (default) or a matrix.
verbose	A logical.
lst	Deprecated alias for pairings.

Value

A data frame or matrix with one row for each valid assignment.

See Also

`dviGridSize()`, `dviJoint()`, `generatePairings()`, `expand.grid()`

Examples

```
pairings = list(V1 = c("M1", "M2", "*"), V2 = c("M1", "M2", "*"))
expand.grid.nodup(pairings)

# Compare with expand.grid()
expand.grid(pairings)

# Dataset `example1`
pairings = generatePairings(example1)
g = expand.grid.nodup(pairings)
n = dviGridSize(pairings = pairings)
stopifnot(nrow(g) == n$size)
```

families2dvir

Convert a Familias file to DVI data

Description

This is a wrapper for `pedFamilias::readFam()` that reads Familias files with DVI information.

Usage

```
families2dvir(
  famfile,
  victimPrefix = NULL,
  familyPrefix = NULL,
  refPrefix = NULL,
```

```

    missingPrefix = NULL,
    missingFormat = NULL,
    othersPrefix = NULL,
    verbose = TRUE,
    missingIdentifier = "^Missing"
  )

```

Arguments

<code>famfile</code>	Path to Familias file.
<code>victimPrefix</code>	Prefix used to label PM individuals.
<code>familyPrefix</code>	Prefix used to label the AM families.
<code>refPrefix</code>	Prefix used to label the reference individuals, i.e., the typed members of the AM families.
<code>missingPrefix</code>	Prefix used to label the missing persons. At most one of <code>missingPrefix</code> and <code>missingFormat</code> can be given.
<code>missingFormat</code>	A string indicating family-wise labelling of missing persons, using [FAM], [IDX], [MIS] as place holders with the following meanings (see Examples): • [FAM]: family index • [IDX]: index of missing person within the family • [MIS]: index within all missing persons
<code>othersPrefix</code>	Prefix used to label other untyped individuals. Use "" for numeric labels (1, 2, ...).
<code>verbose</code>	A logical, passed on to <code>readFam()</code> .
<code>missingIdentifier</code>	A character of length 1 used to identify missing persons in the Familias file. The default chooses everyone whose label begins with "Missing".

Details

The sex of the missing persons need to be checked as this information may not be correctly recorded in the fam file.

Value

A `dviData` object.

See Also

[dviData\(\)](#), [relabelDVI\(\)](#)

Examples

```

# Family with three missing
file = system.file("extdata", "dvi-example.fam", package="dvir")

# Read file without relabelling

```

```

y = familias2dvir(file)
plotDVI(y)

# With relabelling
z = familias2dvir(file, missingFormat = "M[FAM]-[IDX]",
                  refPrefix = "ref", othersPrefix = "E")
plotDVI(z)

```

findExcluded	<i>Excluded individuals and pairings in a DVI dataset</i>
--------------	---

Description

Analysing exclusions is often an efficient way to reduce large DVI datasets. A pairing $V = M$ is *excluded* if it implies (too many) genetic inconsistencies. The function `findExcluded()` identifies and removes (i) victim samples with too many inconsistencies against all missing persons, (ii) missing persons with too many inconsistencies against all victim samples, and (iii) inconsistent pairings among the remaining.

Usage

```

findExcluded(
  dvi,
  maxIncomp = 2,
  pairings = NULL,
  ignoreSex = FALSE,
  verbose = TRUE
)

exclusionMatrix(dvi, pairings = NULL, ignoreSex = FALSE)

```

Arguments

<code>dvi</code>	A <code>dviData()</code> object.
<code>maxIncomp</code>	An integer. A pairing is excluded if the number of incompatible markers exceeds this.
<code>pairings</code>	A list of possible pairings for each victim. By default, <code>dvi\$pairings</code> is used, or, if this is <code>NULL</code> , <code>generatePairings(dvi, ignoreSex)</code> .
<code>ignoreSex</code>	A logical, by default: <code>FALSE</code> .
<code>verbose</code>	A logical, by default <code>TRUE</code> .

Details

The main calculation in `findExcluded()` is done by `exclusionMatrix()`, which records number of incompatible markers of each pairwise comparison.

Value

A list with the following entries:

- `exclusionMatrix`: A matrix showing the number of inconsistencies for each pair (or NA if the pairing was not considered)
- `excluded`: A list of three character vectors:
 - `sample`: victim samples excluded against all missing persons
 - `missing`: missing persons excluded against all victims
 - `fam`: families in which all missing members are excluded against all victim samples
- `dviReduced`: A reduced version of `dvi`, where the excluded elements are removed, and the pairings are updated.
- `summary`: A list of data frames PM and AM, summarising the excluded individuals.

See Also

`findUndisputed()`. See also `forrel::findExclusions()` for analysis of a specific pairwise comparison.

Examples

```
e = findExcluded(icmp)
e$summary
e$exclusionMatrix

# The exclusion matrix can also be computed directly:
exclusionMatrix(icmp)

# Inspect a particular pair: M4 vs V4
forrel::findExclusions(icmp$am, id = "M4", candidate = icmp$pm$V4)

# Plot one of the incompatible markers
plotDVI(icmp, pm = 4, marker = "D7S820")
```

findNonidentifiable	<i>Nonidentifiable missing persons</i>
---------------------	--

Description

A missing person in a DVI case is nonidentifiable if they are not related to any (genotyped) reference individuals, neither directly nor through other missing persons in the family. This function identifies such individuals, and reduces the DVI dataset accordingly.

Usage

```
findNonidentifiable(dvi)
```

Arguments

dvi A dviData object, typically created with `dviData()`.

Details

Two individuals are unrelated if their kinship coefficient is zero. The implementation uses `ribd::kinship()` to calculate all pairwise kinship coefficients.

Value

A list with the following entries:

- `nonidentifiable`: A character vector (possibly empty) with the names of the nonidentifiable missing persons.
- `dviReduced`: A reduced dviData object, where the nonidentifiable individuals are removed from the list of missing persons. If there are no nonidentifiable, this is just a copy of dvi.
- `summary`: A data frame summarising the findings.

Examples

```
# Example 1: No nonidentifiables in dataset `example1`
findNonidentifiable(example1)

# Example 2: Add nonidentifiable person "A"
amNew = example1$am[[1]] |>
  addSon(parents = c("NN", "A"))
missNew = c(example1$missing, "A")

dvi = dviData(pm = example1$pm, am = amNew, missing = missNew)
plotDVI(dvi, textAbove = c(A = "nonidentif.))

findNonidentifiable(dvi)
```

findUndisputed

Undisputed identifications in a DVI problem

Description

This function uses the pairwise LR matrix to find *undisputed* matches between victims and missing individuals. An identification $V_i = M_j$ is called undisputed, relative to a threshold T , if the corresponding likelihood ratio $LR_{i,j} \geq T$ AND $LR_{i,j}$ is at least T times greater than all other pairwise LR's involving V_i or M_j .

Usage

```
findUndisputed(
  dvi,
  pairings = NULL,
  ignoreSex = FALSE,
  threshold = 10000,
  strict = FALSE,
  limit = 0,
  nkeep = NULL,
  numCores = 1,
  keepLRmatrs = FALSE,
  verbose = TRUE
)
```

Arguments

dvi	A dviData object, typically created with dviData() .
pairings	A list of possible pairings for each victim. If NULL, all sex-consistent pairings are used.
ignoreSex	A logical.
threshold	A non-negative number. If no pairwise LR exceed this, the iteration stops.
strict	A logical affecting the definition of being undisputed (see Details). Default: FALSE.
limit	A positive number. Only pairwise LR values above this are considered.
nkeep	An integer, or NULL. If given, only the nkeep most likely pairings are kept for each victim.
numCores	An integer; the number of cores used in parallelisation. Default: 1.
keepLRmatrs	A logical; for internal purposes. Default: FALSE.
verbose	A logical. Default: TRUE.

Details

If the parameter `strict` is set to `TRUE`, the last criterion is replaced with the stronger requirement that all other pairwise LR's involving V_i or M_j must be at most 1.

Value

A list with the following entries:

- `dviReduced`: A reduced version of `dvi`, where undisputed victims/missing persons are removed, and data from undisputed victims inserted into the reference data.
- `summary`: A data frame summarising the undisputed matches.
- `LRmatrix`: Output from `pairwiseLR()` applied to the reduced problem.

See Also

[pairwiseLR\(\)](#), [findExcluded\(\)](#)

Examples

```
u1 = findUndisputed(planecrash, verbose = FALSE)
u1$summary

# With `strict = TRUE`, the match M3 = V2 goes away
u2 = findUndisputed(planecrash, strict = TRUE, verbose = FALSE)
u2$summary

# Reason: M3 has LR > 1 also against V7
u2$LRmatrix[, "M3"] |> round(2)
```

fire	<i>DVI dataset: Family of fire victims</i>
------	--

Description

A family with three missing persons after a fire, and one reference individual. This example is featured in the GLR paper (Egeland & Vigeland, 2024).

Usage

```
fire
```

Format

A dviData object with the following content:

- pm: A list of 3 singletons (victims).
- am: A pedigree with three missing persons and one typed reference individual.
- missing: A vector containing the names of the missing persons.

Examples

```
fire
plotDVI(fire, marker = 1)
dviSolve(fire, verbose = FALSE)
```

formatSummary	<i>Format final summary table</i>
---------------	-----------------------------------

Description

Combines and harmonises summary tables from different DVI analyses

Usage

```
formatSummary(dfs, orientation = c("AM", "PM"), columns = NULL, dvi = NULL)
```

Arguments

dfs	A list of data frames.
orientation	Either "AM" or "PM", controlling column order and sorting.
columns	A (optional) character vector with column names in the wanted order.
dvi	A dviData object used for sorting. Note that if given, this must contain all victims and families.

Details

The default column order is controlled by orientation, which the following effect:

- AM:
 - Column order: Family, Missing, Sample, LR, GLR, Conclusion, Comment
 - Sort by: Family and Missing
- PM:
 - Column order: Sample, Missing, Family, LR, GLR, Conclusion, Comment
 - Sort by: Sample

Columns (in any of the data frames) other than these are simply ignored.

Value

A data frame.

Examples

```
u = findUndisputed(planecrash)
a = amDrivenDVI(u$dviReduced, threshold2 = 500)

u$summary
a$summary

formatSummary(list(u$summary, a$summary$AM))
formatSummary(list(u$summary, a$summary$PM), orientation = "PM", dvi = planecrash)
```

generatePairings	<i>Sex-consistent pairings</i>
------------------	--------------------------------

Description

Generate a list of sex-consistent pairings for each victim in a DVI problem. By default, the empty pairing (denoted `*`) is included for each victim.

Usage

```
generatePairings(dvi, includeEmpty = TRUE, ignoreSex = FALSE)
```

Arguments

<code>dvi</code>	A <code>dviData</code> object, typically created with <code>dviData()</code> .
<code>includeEmpty</code>	A logical. If TRUE (default), the do-nothing symbol (<code>*</code>) is included for each victim.
<code>ignoreSex</code>	A logical.

Value

A list of character vectors. Each vector is a subset of `missing`, plus the character `*` denoting no pairing.

See Also

[jointDVI\(\)](#)

Examples

```
pm = singletons(c("V1", "V2"), sex = 1:2)

missing = paste0("M", 1:4)
am = list(nuclearPed(children = missing[1:3]),
          nuclearPed(children = missing[4], sex = 2))

dvi = dviData(pm, am, missing)
generatePairings(dvi)
```

getDatabase	<i>Extract the marker database from a DVI dataset</i>
-------------	---

Description

Extract the marker database from a DVI dataset

Usage

```
getDatabase(dvi, check = TRUE, includeAttrs = FALSE)
```

Arguments

dvi	A <code>dviData()</code> object.
check	A logical. If TRUE (default), the functions checks if the AM and PM databases are identical, and raises an error if not. If FALSE, the AM database is returned without checking PM.
includeAttrs	A logical, indicating if the full list of attributes of each marker (including mutation model and position data) should be returned, or only the allele frequencies. Default: FALSE.

Value

A list of marker information.

Examples

```
getDatabase(example1)
getDatabase(example1, includeAttrs = TRUE)
```

getFamily	<i>Get AM component of selected individuals</i>
-----------	---

Description

Get AM component of selected individuals

Usage

```
getFamily(dvi, ids)
```

Arguments

dvi	A <code>dviData()</code> object.
ids	A vector of ID labels of members of <code>dvi\$am</code> .

Value

A vector of the same length as `ids`, containing the family names of the `ids` individuals.

Examples

```
getFamily(example2, ids = example2$missing)
```

`getSimpleFams`*Find the simple families of a DVI dataset*

Description

Extract the names (if present) or indices of the *simple* reference families, i.e., the families containing exactly 1 missing person.

Usage

```
getSimpleFams(dvi)
```

Arguments

`dvi` A `dviData` object.

Value

A character (if `dvi$am` has names) or integer vector.

See Also

[getFamily\(\)](#)

Examples

```
# No simple families
simple1 = getSimpleFams(example1)
stopifnot(length(simple1) == 0)

# Second family is simple
simple2 = getSimpleFams(example2)
stopifnot(simple2 == "F2")
```

grave

DVI dataset: Family grave

Description

Family grave data in Kling et al. (2021) "Mass Identifications: Statistical Methods in Forensic Genetics". There are 5 female victims and 3 male victims. There is one reference family with 5 missing females and 3 missing males. There are 23 markers, no mutation model.

Usage

grave

Format

A dviData object with the following content:

- pm: A list of 8 singletons (victims).
- am: A pedigree with 8 missing persons.
- missing: A vector containing the names of the missing persons.

Examples

```
grave
plotDVI(grave, marker = 1)

# dviSolve(grave)
```

icmp

DVI dataset: A large reference pedigree

Description

DVI dataset based loosely on the ICMP 2017 workshop material <https://www.few.vu.nl/~ksn560/Block-III-PartI-KS-ISFG2017.pdf> (page 18). There are 3 female victims, 2 male victims and 6 missing persons of both sexes. We have renamed the individuals and simulated data for 13 CODIS markers (see Details).

Usage

icmp

Format

A dviData object with the following content:

- pm: A list of 5 singletons (victims).
- am: A reference pedigree with 6 genotyped members and 12 missing persons.
- missing: A vector containing the names of the missing persons.

Details

The 13 markers are, in order: CSF1P0, D3S1358, D5S818, D7S820, D8S1179, D13S317, D16S539, D18S51, D21S11, FGA, TH01, TPOX, and vWA.

Source code for the simulation, and a file containing the allele frequencies, can be found in the data-raw folder of the GitHub repository: <https://github.com/magnusdv/dvir>.

Examples

```
icmp
plotDVI(icmp)

# Markers and allele frequencies
db = getDatabase(icmp)
db[1:3]
```

jointDVI

Legacy DVI workflow with joint analysis

Description

Joint matching of victims and missing persons in a disaster victim identification (DVI) case, as described by Vigeland & Egeland (2021).

NOTE: This is a legacy function. For new projects we recommend these instead:

- dviSolve() (for a complete DVI pipeline)
- dviJoint() (for fully joint analysis)

The jointDVI() function was the first implementation of a complete DVI analysis in dvir. It both manages the analysis workflow (including exclusion of impossible pairings and detection of undisputed matches) and performs the final joint analysis. As the package evolved, it became beneficial to split these two roles, resulting in the two functions above.

Usage

```
jointDVI(
  dvi,
  pairings = NULL,
  ignoreSex = FALSE,
  assignments = NULL,
  limit = 0,
  nkeep = NULL,
  undisputed = TRUE,
  markers = NULL,
  threshold = 10000,
  strict = FALSE,
  disableMutations = NA,
  maxAssign = 1e+05,
  numCores = 1,
  check = TRUE,
  verbose = TRUE
)

compactJointRes(jointRes, LRthresh = NULL)
```

Arguments

<code>dvi</code>	A <code>dviData</code> object, typically created with <code>dviData()</code> .
<code>pairings</code>	A list of possible pairings for each victim. If <code>NULL</code> , all sex-consistent pairings are used.
<code>ignoreSex</code>	A logical.
<code>assignments</code>	A data frame containing the assignments to be considered in the joint analysis. By default, this is automatically generated by taking all combinations from <code>pairings</code> .
<code>limit</code>	A positive number, by default 0. Only pairwise LR values above this are considered.
<code>nkeep</code>	An integer, or <code>NULL</code> . If given, only the <code>nkeep</code> most likely pairings are considered for each victim.
<code>undisputed</code>	A logical, by default <code>TRUE</code> .
<code>markers</code>	A vector indicating which markers should be included in the analysis. By default all markers are included.
<code>threshold</code>	A positive number, passed onto <code>findUndisputed()</code> . Default: 1e4.
<code>strict</code>	A logical, passed onto <code>findUndisputed()</code> . Default: <code>FALSE</code> .
<code>disableMutations</code>	A logical, or <code>NA</code> (default). The default action is to disable mutations in all reference families without Mendelian errors.
<code>maxAssign</code>	A positive integer. If the number of assignments going into the joint calculation exceeds this, the function will abort with an informative error message. Default: 1e5.

numCores	Deprecated and ignored.
check	A logical, indicating if the input data should be checked for consistency.
verbose	A logical.
jointRes	A data frame produced by <code>jointDVI()</code> .
LRthresh	A positive number, used as upper limit for the LR comparing the top result with all others.

Value

A data frame. Each row describes an assignment of victims to missing persons, accompanied with its log likelihood, the LR compared to the null (i.e., no identifications), and the posterior corresponding to a flat prior.

The function `compactJointRes()` removes columns without assignments, and solutions whose LR compared with the top result is below $1/\text{LRthresh}$.

References

Vigeland, MD., Egeland, T. Joint DNA-based disaster victim identification. Sci Rep 11, 13661 (2021).

See Also

`pairwiseLR()`, `findUndisputed()`

Examples

```
jointDVI(example2)
```

KETPchap481

Data used in the book Kling et al. (2021)

Description

Data used in the example in Chapter 4.8.1 in Kling et al. (2021) "Mass Identifications: Statistical Methods in Forensic Genetics". The victims are V1 and V2, both females. There is one reference family with 2 missing persons, both females. There are 21 markers, no mutation model.

Usage

```
KETPchap481
```

Format

A `dviData` object with the following content:

- `pm`: A list of 2 singletons (victims).
- `am`: A list of 1 pedigree.
- `missing`: A vector containing the names of the missing persons.

Examples

```
plotDVI(KETPchap481, marker = 1)
```

KETPchap484

Data used in the book Kling et al. (2021)

Description

Data used in last example of Chapter 4 in Kling et al. (2021) "Mass Identifications: Statistical Methods in Forensic Genetics". There are 2 female victims, 2 male victims. There are four reference families with 2 missing females and 2 missing males. There are 21 markers. An 'equal mutation mode with rate 0.005 is specified.

Usage

```
KETPchap484
```

Format

A dviData object with the following content:

- pm: A list of 4 singletons (victims).
- am: A list of 3 pedigrees.
- missing: A vector containing the names of the missing persons.

Examples

```
KETPchap484
```

```
plotDVI(KETPchap484, nrowPM = 4)
```

KETPexer497

Data used in the book Kling et al. (2021)

Description

Data used in Exercise 4.9.7 in Kling et al. (2021) "Mass Identifications: Statistical Methods in Forensic Genetics". There are 3 female victims and 3 reference families with 3 missing females. There are 23 markers, equal mutation model, rate 0.001.

Usage

```
KETPexer497
```

Format

A dviData object with the following content:

- pm: A list of 3 singletons (victims).
- am: A list of 3 pedigrees.
- missing: A vector containing the names of the missing persons.

Examples

```
plotDVI(KETPexer497, nrowPM = 3)
```

KETPexer498

Data used in the book Kling et al. (2021)

Description

Data used in Exercise 4.9.8 in Kling et al. (2021) "Mass Identifications: Statistical Methods in Forensic Genetics". There are 2 female victims and 1 male. There is one reference family with 2 missing females and one missing male. There are 16 markers, equal mutation model, rate 0.001.

Usage

```
KETPexer498
```

Format

A dviData object with the following content:

- pm: A list of 3 singletons (victims).
- am: A list of 1 pedigree.
- missing: A vector containing the names of the missing persons.

Examples

```
plotDVI(KETPexer498)
```

mergePM*Identify and merge matching PM samples*

Description

Computes the direct matching LR of each pair of samples, and merges the matching samples.

Usage

```
mergePM(  
  pm,  
  threshold = 10000,  
  method = c("mostcomplete", "first", "combine"),  
  verbose = TRUE  
)
```

Arguments

pm	A list of typed singletons.
threshold	LR threshold for positive identification.
method	A keyword indicating how to merge matching samples. See Details.
verbose	A logical.

Details

The available methods for merging matched samples are:

- "mostcomplete": Use the sample with the highest number of non-missing genotypes
- "first": Use the first in each group, according to the input order
- "combine": Not implemented yet.

Value

A list with the following entries:

- groups: A list containing the groups of matching samples.
- LRmat: A symmetric matrix (with 0s on the diagonal) containing the direct matching LR values.
- nonmissing: A named vector reporting the number of non-missing genotypes for each sample.
- pmReduced: A list of singletons. If use is "best" or "first", this is a subset of the input pm.

See Also

[directMatch\(\)](#).

Examples

```
pm = singletons(c("V1", "V2", "V3")) |>
  addMarker(V1 = "1/1", V2 = "2/2", V3 = "1/1",
            afreq = c("1" = 0.01, "2" = 0.99), name = "L1")

mergePM(pm)
```

ncomb

*The total a priori number of assignments in a DVI problem***Description**

Calculates the total number of assignments, i.e., the different ways the victims can be paired with the missing persons while respecting sex. Note that in practice, the number of assignments considered in a joint DVI analysis is usually much smaller than this, due to reductions in preliminary steps. See [dviGridSize\(\)](#) for a more refined version.

Usage

```
ncomb(nVfemales, nMPfemales, nVmales, nMPmales)
```

Arguments

nVfemales	Integer. The number of female victims.
nMPfemales	Integer. The number of female missing persons.
nVmales	Integer. The number of male victims.
nMPmales	Integer. The number of male missing persons.

Value

The total number of possible assignments.

See Also

[dviGridSize\(\)](#)

Examples

```
# Example
m1 = ncomb(5,5,5,5)

# Example: 3 male victims; 2 male missing persons.
# The number of a priori possible assignments is
m1 = ncomb(0,0,3,2) # 13

# Compare with the complete list of assignments
```

```

m2 = expand.grid.nodup(list(V1 = c("x", "M1", "M2"),
                           V2 = c("x", "M1", "M2"),
                           V3 = c("x", "M1", "M2")))
stopifnot(m1 == nrow(m2))

```

pairwiseLR

*Pairwise LR matrix***Description**

For a given DVI problem, compute the matrix consisting of pairwise likelihood ratios $LR_{i,j}$ comparing $V_i = M_j$ to the null. The output may be reduced by specifying arguments `limit` or `nkeep`.

Usage

```

pairwiseLR(
  dvi,
  pairings = NULL,
  ignoreSex = FALSE,
  limit = 0,
  nkeep = NULL,
  check = FALSE,
  numCores = 1,
  verbose = FALSE
)

```

Arguments

<code>dvi</code>	A <code>dviData</code> object, typically created with <code>dviData()</code> .
<code>pairings</code>	A list of possible pairings for each victim. If <code>NULL</code> , all sex-consistent pairings are used.
<code>ignoreSex</code>	A logical.
<code>limit</code>	A nonnegative number controlling the <code>pairings</code> slot of the output: Only pairings with LR greater or equal to <code>limit</code> are kept. If zero (default), pairings with $LR > 0$ are kept.
<code>nkeep</code>	An integer, or <code>NULL</code> . If given, only the <code>nkeep</code> most likely pairings are kept for each victim.
<code>check</code>	A logical, indicating if the input data should be checked for consistency.
<code>numCores</code>	Deprecated and ignored.
<code>verbose</code>	A logical.

Value

A list with 3 elements:

- **LRmatrix**: A matrix containing the pairwise LR values.
- **LRlist**: A list of numerical vectors, containing the pairwise LRs in list format.
- **pairings**: A reduced version of the input pairings, keeping only entries with corresponding $LR \geq \text{limit}$. For the default case $\text{limit} = 0$ a strict inequality is used, i.e., $LR > 0$.

Examples

```
pairwiseLR(example1, verbose = TRUE)
```

planecrash

DVI dataset: Simulated plane crash

Description

A simulated dataset based on Exercise 3.3 in Egeland et al. "Relationship Inference with Familias and R" (2015).

Usage

```
planecrash
```

Format

A `dviData` object with the following content:

- **pm**: A list of 8 female singletons (victims).
- **am**: A list of 5 pedigrees, each with one missing member and one genotyped member.
- **missing**: A vector containing the names of the missing persons.

Details

The 15 markers are CSF1PO, D13S317, D16S539, D18S51, D21S11, D3S1358, D5S818, D7S820, D8S1179, FGA, PENTA_D, PENTA_E, TH01, TPOX, and VWA.

Source code for the simulation, and a file containing the allele frequencies, can be found in the `data-raw` folder of the GitHub repository: <https://github.com/magnusdv/dvir>.

Examples

```
planecrash
plotDVI(planecrash)

# Markers and allele frequencies
db = getDatabase(planecrash)
db[1:3]
```

plotDVI	<i>Plot a DVI problem</i>
---------	---------------------------

Description

Plot a DVI problem

Usage

```
plotDVI(
  dvi,
  pm = TRUE,
  am = TRUE,
  style = 1,
  famnames = NA,
  hatched = typedMembers,
  frames = TRUE,
  titles = c("PM", "AM"),
  cex = NA,
  cex.titles = NA,
  col = 1,
  lwd = 1,
  fill = NA,
  carrier = NULL,
  widths = NULL,
  heights = NULL,
  nrowPM = NA,
  nrowAM = NA,
  ncolAM = NA,
  dev.height = NULL,
  dev.width = NULL,
  newdev = !is.null(c(dev.height, dev.width)),
  ...
)
```

Arguments

dvi	A dviData object, typically created with dviData() .
pm	Either a logical indicating if the PM data should be plotted (as a set of singletons), or a vector of indices selecting a subset of the PM samples. Default: TRUE.
am	Either a logical indicating if the AM families data should be plotted, or a vector of indices selecting a subset of the families. Default: TRUE.
style	An integer (currently 1 or 2) indicating the style of the plot.
famnames	A logical. If NA (default) family names are included if there are multiple families.

<code>hatched</code>	A character vector of ID labels, or the name of a function. By default, typed individuals are hatched.
<code>frames</code>	A logical, by default TRUE.
<code>titles</code>	A character of length 2.
<code>cex.titles</code>	A numeric controlling the size of the titles.
<code>fill, cex, col, lwd, carrier</code>	Arguments passed on to <code>pedtools::plot.ped()</code> .
<code>widths, heights</code>	Numeric with relative columns widths / row heights, to be passed on to <code>layout()</code> .
<code>nrowPM</code>	The number of rows in the array of PM singletons.
<code>nrowAM, ncolAM</code>	The number of rows/cols in the array of AM families.
<code>dev.height, dev.width</code>	Plot height and widths in inches. These are optional, and only relevant if <code>newdev = TRUE</code> .
<code>newdev</code>	A logical indicating if a new plot window should be opened.
<code>...</code>	Further parameters to be passed on to <code>pedtools::plot.ped()</code> , e.g., <code>marker</code> , <code>cex</code> , <code>cex.main</code> , <code>symbolsize</code> .

Examples

```
plotDVI(example2)

# Override default layout
plotDVI(example2, nrowPM = 1, ncolAM = 1)

# Subset
plotDVI(example2, pm = 1:2, am = 1, titles = c("PM (1-2)", "AM (1)"))

# AM only
plotDVI(example2, pm = FALSE, titles = "AM families")

# Further plot options
plotDVI(example2, frames = FALSE, marker = 1, cex = 1.2, nrowPM = 3, nrowAM = 2,
  textAnnot = list(inside = list(c(M1 = "?", M2 = "?", M3 = "?"), cex = 1.5)))
```

plotSolution

Plot DVI solution

Description

A version of `plotDVI()` tailor-made to visualise identified individuals, for example as reported by `jointDVI()`.

Usage

```
plotSolution(dvi, assignment, k = 1, format = "[S]=[M]", ...)
```

Arguments

dvi	A dviData object.
assignment	A named character of the format <code>c(victim = missing, ...)</code> , or a data frame produced by <code>jointDVI()</code> .
k	An integer; the row number when assignment is a data frame.
format	A string indicating how identified individuals should be labelled, using [M] and [S] as place holders for the missing person and the matching sample, respectively. (See Examples.)
...	Further arguments passed on to <code>plotDVI()</code> .

Value

NULL.

Examples

```
res = jointDVI(example2, verbose = FALSE)

plotSolution(example2, res)

# With line break in labels
plotSolution(example2, res, format = "[M]=\n[S]")

# With genotypes for marker 1
plotSolution(example2, res, marker = 1)

# Non-optimal solutions
plotSolution(example2, res, k = 2, pm = FALSE)
plotSolution(example2, res, k = 2, cex = 1.3)
```

plotUndisputed	<i>Plot undisputed identifications</i>
----------------	--

Description

Plot undisputed identifications

Usage

```
plotUndisputed(dvi, undisputed, ...)
```

Arguments

dvi	A dviData object.
undisputed	A data frame containing the undisputed matches, typically the entry undisputed in output from <code>findUndisputed()</code> (only three first columns used).
...	Further arguments passed on to <code>plotSolution()</code> .

See Also

[findUndisputed\(\)](#), [plotSolution\(\)](#)

Examples

```
# Example
res = findUndisputed(example2, threshold = 2, verbose = FALSE)
u = res$summary
plotUndisputed(example2, u, marker = 1)
```

relabelDVI

Automatic labelling of a DVI dataset

Description

Relabel the individuals and families in a DVI dataset.

Usage

```
relabelDVI(
  dvi,
  victims = NULL,
  victimPrefix = NULL,
  familyPrefix = NULL,
  refs = NULL,
  refPrefix = NULL,
  missingPrefix = NULL,
  missingFormat = NULL,
  othersPrefix = NULL
)
```

Arguments

dvi	A dviData object, typically created with dviData() .
victims	A named vector of the form <code>c(old = new)</code> with names for the PM samples, or a function to be applied to the existing names.
victimPrefix	Prefix used to label PM individuals.
familyPrefix	Prefix used to label the AM families.
refs	A named vector of the form <code>c(old = new)</code> with names for the typed references, or a function to be applied to the existing names.
refPrefix	Prefix used to label the reference individuals, i.e., the typed members of the AM families.
missingPrefix	Prefix used to label the missing persons. At most one of <code>missingPrefix</code> and <code>missingFormat</code> can be given.

missingFormat A string indicating family-wise labelling of missing persons, using [FAM], [IDX], [MIS] as place holders with the following meanings (see Examples):

- [FAM]: family index
- [IDX]: index of missing person within the family
- [MIS]: index within all missing persons

othersPrefix Prefix used to label other untyped individuals. Use "" for numeric labels (1, 2, ...).

Value

A `dviData()` object.

Examples

```
# Builtin dataset `example2`
relabelDVI(example2,
  victimPrefix = "vic",
  familyPrefix = "fam",
  refPrefix    = "ref",
  missingPrefix = "mp")

# Family-wise labelling of missing persons
relabelDVI(example2, missingFormat = "M[FAM]-[IDX]")
relabelDVI(example2, missingFormat = "M[IDX] (F[FAM])")
relabelDVI(example2, missingFormat = "fam[FAM].m[IDX]")
```

sequentialDVI

Sequential DVI search

Description

Performs a sequential matching procedure based on the pairwise LR matrix. In each step the pairing corresponding to the highest LR is selected and included as a match if the LR exceeds the given threshold. By default, (`updateLR = TRUE`) the pairwise LRs are recomputed in each step after including the data from the identified sample.

Usage

```
sequentialDVI(
  dvi,
  updateLR = TRUE,
  threshold = 1,
  check = TRUE,
  verbose = TRUE,
  debug = FALSE
)
```

Arguments

dvi	A dviData object, typically created with <code>dviData()</code> .
updateLR	A logical. If TRUE, the LR matrix is updated in each iteration.
threshold	A non-negative number. If no pairwise LR values exceed this, the iteration stops.
check	A logical, indicating if the input data should be checked for consistency.
verbose	A logical, by default TRUE.
debug	A logical, by default FALSE. If TRUE, the LR matrix is printed in each step.

Details

If, at any point, the highest LR is obtained by more than one pairing, the process branches off and produces multiple solutions. (See Value.)

Value

A list with two elements:

- matches: A single assignment vector, or (if multiple branches) a data frame where each row is an assignment vector.
- details: A data frame (or a list of data frames, if multiple branches) including the LR of each identification in the order they were made.

Examples

```
# Without LR updates
sequentialDVI(example1, updateLR = FALSE)

# With LR updates (default). Note two branches!
r = sequentialDVI(example1)

# Plot the two solutions
plotSolution(example1, r$matches, k = 1)
plotSolution(example1, r$matches, k = 2)

# Add `debug = T` to see the LR matrix in each step
sequentialDVI(example1, debug = TRUE)

# The output of can be fed into `jointDVI()`:
jointDVI(example1, assignments = r$matches)
```

setPairing	<i>Set identifications manually</i>
------------	-------------------------------------

Description

Manually set one or several identifications in a DVI dataset. Typically, these are obtained by external means, e.g., fingerprints, dental records etc.

Usage

```
setPairing(  
  dvi,  
  match = NULL,  
  victim = NULL,  
  missing = NULL,  
  Conclusion = "Provided",  
  Comment = "",  
  verbose = TRUE  
)
```

Arguments

dvi	A DVI dataset.
match	A named vector of the format <code>c(vic1 = miss1, vic2 = miss2, ...)</code> .
victim	A vector of victim sample names. If <code>NULL</code> , defaulting to <code>names(match)</code> .
missing	A vector of missing person names, of the same length as <code>victim</code> . If <code>NULL</code> , defaulting to <code>as.character(match)</code> .
Conclusion	A character passed on to the Conclusion column of the output summary.
Comment	A character passed on to the Comment column of the output summary.
verbose	A logical, by default <code>TRUE</code> .

Details

The command `setPairing(dvi, c("V" = "M"))` does the following:

- Transfer the data of victim "V" to the individual "M" in the appropriate reference family
- Remove "M" from the list of missing persons
- Remove "V" from the list of victim samples
- Update the list of pairings

Value

A list with the following entries:

- `dviReduced`: The new `dviData` object, as described in Details
- `summary`: A data frame summarising the identifications

Examples

```
x = setPairing(example2, match = c("V3" = "M2"))
x$dviReduced
x$summary

# Alternative syntax, using `victim` and `missing`
y = setPairing(planecrash, victim = c("V4", "V5"), missing = c("M4", "M5"),
               Conclusion = "External evidence", Comment = "Dental")
y$dviReduced
y$summary
```

subsetDVI	<i>Extract a subset of a DVI dataset</i>
-----------	--

Description

Extract a subset of a DVI dataset

Usage

```
subsetDVI(
  dvi,
  pm = NULL,
  am = NULL,
  missing = NULL,
  removeUnpairedPM = TRUE,
  verbose = TRUE
)
```

Arguments

dvi	A <code>dviData()</code> object
pm	A vector with names or indices of victim samples. By default, all are included.
am	A vector with names or indices of AM components. By default, components without remaining missing individuals are dropped.
missing	A vector with names or indices of missing persons. By default, all missing persons in the remaining AM families are included.
removeUnpairedPM	A logical, by default TRUE, removing PM samples with no remaining pairings.
verbose	A logical.

Value

A `dviData` object.

Examples

```
subsetDVI(example2, pm = 1:2) |> plotDVI()
subsetDVI(example2, pm = "V1", am = 1) |> plotDVI()
subsetDVI(example2, missing = "M3") |> plotDVI()
```

swapOrientation	<i>Swap orientation of an assignment table</i>
-----------------	--

Description

This function switches the roles of victims and missing persons in a table of assignments, from PM-oriented (victims as column names) to AM-oriented (missing persons as column names), and *vice versa*. In both versions, each row describes the same assignment vector.

Usage

```
swapOrientation(df, from = NULL, to = NULL)
```

Arguments

df	A data frame. Each row is an assignment, with * representing non-pairing.
from	A character vector; either victims or missing persons. By default, the column names of df. The only time this argument is needed, is when df has other columns in addition, as in output tables of dviJoint().
to	The column names of the transformed data frame. If missing, the unique elements of df are used. An error is raised if to does not contain all elements of df (except *).

Value

A data frame with `nrow(df)` rows and `length(to)` columns.

Examples

```
df = example1 |> generatePairings() |> expand.grid.nodup()
df
swapOrientation(df)

# Swap is idempotent
stopifnot(identical(swapOrientation(swapOrientation(df)), df))
```

`symmetricSibs`*Dataset: Symmetry examples*

Description

A toy DVI dataset illustrating various forms of undecidability due to symmetries in the solutions.

Usage

```
symmetricSibs
```

Format

A `dviData` object with the following content:

- `pm`: A list of 5 singletons (male victims).
- `am`: A list of 3 pedigrees
- `missing`: A character vector of length 5, naming the missing persons.

Examples

```
symmetricSibs
```

Index

* datasets

- example1, [15](#)
- example2, [15](#)
- exclusionExample, [17](#)
- fire, [24](#)
- grave, [29](#)
- icmp, [29](#)
- KETPchap481, [32](#)
- KETPchap484, [33](#)
- KETPexer497, [33](#)
- KETPexer498, [34](#)
- planecrash, [38](#)
- symmetricSibs, [48](#)

addVictims, [3](#)

amDrivenDVI, [3](#)

amDrivenDVI(), [14](#)

Bmarginal, [4](#)

checkDVI(dviData), [8](#)

checkDVI(), [14](#)

compactJointRes(jointDVI), [30](#)

directMatch, [5](#)

directMatch(), [35](#)

dviCompare, [6](#)

dviData, [8](#)

dviData(), [3, 7, 11, 19, 20, 22, 23, 26, 27, 31, 37, 39, 42–44, 46](#)

dviGLR, [9](#)

dviGridSize, [10](#)

dviGridSize(), [18, 36](#)

dviJoint, [11](#)

dviJoint(), [3, 10, 17, 18](#)

dviSim, [12](#)

dviSolve, [13](#)

dviSolve(), [11](#)

example1, [15](#)

example2, [15](#)

excludePairing, [16](#)

exclusionExample, [17](#)

exclusionMatrix(findExcluded), [20](#)

expand.grid(), [17, 18](#)

expand.grid.nodup, [17](#)

expand.grid.nodup(), [10](#)

familias2dvir, [18](#)

findExcluded, [20](#)

findExcluded(), [14, 23](#)

findNonidentifiable, [21](#)

findNonidentifiable(), [14](#)

findUndisputed, [22](#)

findUndisputed(), [14, 21, 31, 32, 41, 42](#)

fire, [24](#)

formatSummary, [25](#)

formatSummary(), [14](#)

forrel::findExclusions(), [21](#)

forrel::profileSim(), [13](#)

generatePairings, [26](#)

generatePairings(), [10, 14, 18](#)

getDatabase, [27](#)

getFamily, [27](#)

getFamily(), [28](#)

getSimpleFams, [28](#)

grave, [29](#)

icmp, [29](#)

jointDVI, [30](#)

jointDVI(), [4, 5, 11, 26, 41](#)

KETPchap481, [32](#)

KETPchap484, [33](#)

KETPexer497, [33](#)

KETPexer498, [34](#)

mergePM, [35](#)

mergePM(), [6](#)

ncomb, 36
ncomb(), 10

pairwiseLR, 37
pairwiseLR(), 23, 32
pedFamiliars::readFam(), 18
pedtools::plot.ped(), 40
planecrash, 38
plotDVI, 39
plotDVI(), 40, 41
plotSolution, 40
plotSolution(), 41, 42
plotUndisputed, 41

relabelDVI, 42
relabelDVI(), 19

sequentialDVI, 43
setPairing, 45
subsetDVI, 46
swapOrientation, 47
symmetricSibs, 48