

Package ‘ggsci’

July 30, 2026

Type Package

Title Scientific Journal and Sci-Fi Themed Color Palettes for
'ggplot2'

Version 5.2.0

Maintainer Nan Xiao <me@nanx.me>

Description A collection of 'ggplot2' color palettes inspired by
plots in scientific journals, data visualization libraries,
science fiction movies, and TV shows.

License GPL (>= 3)

URL <https://nanx.me/ggsci/>, <https://github.com/nanxstats/ggsci>

BugReports <https://github.com/nanxstats/ggsci/issues>

Depends R (>= 3.5.0)

Imports ggplot2 (>= 2.0.0), grDevices, rlang, scales

Suggests gridExtra, knitr, ragg, rmarkdown

VignetteBuilder knitr

Encoding UTF-8

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Nan Xiao [aut, cre, cph] (ORCID:
<<https://orcid.org/0000-0002-0250-5673>>),
Joshua Cook [ctb],
Clara Jégousse [ctb],
Hui Chen [ctb],
Miaozhu Li [ctb],
iTerm2-Color-Schemes contributors [ctb, cph] (iTerm2-Color-Schemes
project),
Winston Chang [ctb, cph] (staticimports.R)

Repository CRAN

Date/Publication 2026-07-30 14:00:08 UTC

Contents

example_scatterplot	3
gephi_palettes	4
iterm_palettes	4
pal_aaas	5
pal_atlassian	5
pal_bmj	6
pal_bs5	7
pal_cosmic	8
pal_d3	9
pal_flatui	10
pal_frontiers	10
pal_futurama	11
pal_gephi	12
pal_gsea	12
pal_igv	13
pal_iterm	14
pal_jama	15
pal_jco	15
pal_lancet	16
pal_locuszoom	17
pal_material	17
pal_nejm	19
pal_npg	19
pal_observable	20
pal_primer	21
pal_rickandmorty	21
pal_simpsons	22
pal_startrek	23
pal_tron	23
pal_tw3	24
pal_uchicago	25
pal_ucscgb	26
rgb_bs5	27
rgb_gsea	28
rgb_material	29
rgb_tw3	30
scale_color_aaas	31
scale_color_atlassian	32
scale_color_bmj	33
scale_color_bs5	34
scale_color_cosmic	35
scale_color_d3	36
scale_color_flatui	38
scale_color_frontiers	39
scale_color_futurama	40
scale_color_gephi	41

scale_color_gsea	41
scale_color_igv	42
scale_color_iterm	43
scale_color_jama	44
scale_color_jco	45
scale_color_lancet	46
scale_color_locuszoom	46
scale_color_material	47
scale_color_nejm	49
scale_color_npg	50
scale_color_observable	50
scale_color_primer	51
scale_color_rickandmorty	52
scale_color_simpsons	53
scale_color_startrek	53
scale_color_tron	54
scale_color_tw3	55
scale_color_uchicago	57
scale_color_ucscgb	58
Index	59

example_scatterplot	<i>Example plots for discrete color palettes</i>
---------------------	--

Description

Utility functions that return simple ggplot2 examples to demonstrate discrete color/fill scales.

Usage

```
example_scatterplot()
```

```
example_barplot()
```

Details

- `example_scatterplot()` creates a scatter plot of large diamonds (`carat >= 2.2`), mapping `table` to the x-axis, `price` to the y-axis, and `cut` to color.
- `example_barplot()` creates a side-by-side bar chart of diamond counts by color, grouped by cut via fill.

Value

A ggplot object.

Examples

```
example_scatterplot()
example_barplot()
```

gephi_palettes	<i>Gephi generative palette names</i>
----------------	---------------------------------------

Description

Gephi generative palette names

Usage

```
gephi_palettes()
```

Value

Character vector of Gephi generative palette identifiers.

Examples

```
gephi_palettes()
```

iTerm_palettes	<i>iTerm color palette names</i>
----------------	----------------------------------

Description

iTerm color palette names

Usage

```
iTerm_palettes()
```

Value

Character vector of palette names.

Examples

```
iTerm_palettes()
```

pal_aaas	AAAS journal color palettes
----------	-----------------------------

Description

Color palettes inspired by plots in journals published by American Association for the Advancement of Science (AAAS), such as *Science* and *Science Translational Medicine*.

Usage

```
pal_aaas(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette inspired by <i>Science</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_aaas("default")(10))
show_col(pal_aaas("default", alpha = 0.6)(10))
```

pal_atlassian	Atlassian Design System palette
---------------	---------------------------------

Description

The Atlassian Design System categorical data visualization palette.

Usage

```
pal_atlassian(palette = c("categorical8"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "categorical8" (8-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Atlassian (2025). "Atlassian Design System categorical chart colors." <https://atlassian.design/foundations/color-new/data-visualization-color>

Examples

```
library("scales")
show_col(pal_atlassian("categorical8")(8))
show_col(pal_atlassian("categorical8", alpha = 0.6)(8))
```

pal_bmj

BMJ color palettes

Description

Color palette from the BMJ living style guide.

Usage

```
pal_bmj(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (9-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Hui Chen | <huichen@zju.edu.cn>

References

<https://github.com/BMJ-Ltd/living-style-guide>

Examples

```
library("scales")
show_col(pal_bmj("default")(9))
show_col(pal_bmj("default", alpha = 0.6)(9))
```

`pal_bs5`*Bootstrap 5 color palettes*

Description

Bootstrap 5 color palettes.

Usage

```
pal_bs5(  
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",  
             "teal", "cyan", "gray"),  
  n = 10,  
  alpha = 1,  
  reverse = FALSE  
)
```

Arguments

<code>palette</code>	Palette type. There are 11 available options: • "blue" • "indigo" • "purple" • "pink" • "red" • "orange" • "yellow" • "green" • "teal" • "cyan" • "gray"
<code>n</code>	Number of individual colors to be generated.
<code>alpha</code>	Transparency level, a real number in (0, 1]. See <code>alpha</code> in grDevices::rgb() for details.
<code>reverse</code>	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("scales")  
show_col(pal_bs5("indigo")(10))  
show_col(pal_bs5("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_cosmic	<i>COSMIC color palettes</i>
------------	------------------------------

Description

Color palettes inspired by the colors used in projects from the [Catalogue Of Somatic Mutations in Cancers \(COSMIC\)](#).

Usage

```
pal_cosmic(  
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),  
  alpha = 1  
)
```

Arguments

palette	Palette type. Currently there are three available options: • "signature_substitutions" (6-color palette). • "hallmarks_light" (10-color palette). • "hallmarks_dark" (10-color palette). The "hallmarks_light" option is from Hanahan and Weinberg (2011) .
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Joshua H. Cook | <joshuacook0023@gmail.com> | [@jhrcook](#)

Examples

```
library("scales")  
show_col(pal_cosmic("hallmarks_light")(10))  
show_col(pal_cosmic("hallmarks_light", alpha = 0.6)(10))  
show_col(pal_cosmic("hallmarks_dark")(10))  
show_col(pal_cosmic("hallmarks_dark", alpha = 0.6)(10))  
show_col(pal_cosmic("signature_substitutions")(6))  
show_col(pal_cosmic("signature_substitutions", alpha = 0.6)(6))
```


Description

Color palettes based on the colors used by D3.js.

Usage

```
pal_d3(  
  palette = c("category10", "category20", "category20b", "category20c"),  
  alpha = 1  
)
```

Arguments

palette	Palette type. There are four available options: • "category10" (10-color palette). • "category20" (20-color palette). • "category20b" (20-color palette). • "category20c" (20-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

References

<https://github.com/d3/d3-3.x-api-reference/blob/master/Ordinal-Scales.md>

Examples

```
library("scales")  
show_col(pal_d3("category10")(10))  
show_col(pal_d3("category20")(20))  
show_col(pal_d3("category20b")(20))  
show_col(pal_d3("category20c")(20))
```

pal_flatui	<i>Flat UI color palettes</i>
------------	-------------------------------

Description

Color palettes inspired by the Flat UI colors.

Usage

```
pal_flatui(palette = c("default", "flattastic", "aussie"), alpha = 1)
```

Arguments

palette	Palette type. Currently there are three available options: • "default" (10-color palette). • "flattastic" (12-color palette). • "aussie" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Clara Jégousse | <cat3@hi.is>

Examples

```
library("scales")
show_col(pal_flatui("default")(10))
show_col(pal_flatui("flattastic")(12))
show_col(pal_flatui("aussie")(10))
show_col(pal_flatui("aussie", alpha = 0.6)(10))
```

pal_frontiers	<i>Frontiers journal color palettes</i>
---------------	---

Description

Color palettes inspired by the colors used in *Frontiers* journals.

Usage

```
pal_frontiers(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Clara Jégousse | [<cat3@hi.is>](mailto:cat3@hi.is)

Examples

```
library("scales")
show_col(pal_frontiers("default")(7))
show_col(pal_frontiers("default", alpha = 0.6)(7))
```

pal_futurama	<i>Futurama color palettes</i>
--------------	--------------------------------

Description

Color palettes inspired by the colors used in *Futurama*.

Usage

```
pal_futurama(palette = c("planetexpress"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "planetexpress" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_futurama("planetexpress")(12))
show_col(pal_futurama("planetexpress", alpha = 0.6)(12))
```

pal_gephi	<i>Gephi color palettes</i>
-----------	-----------------------------

Description

Generative discrete color palettes adapted from the palette engine in Gephi. These palettes are designed to generate visually distinct colors for an arbitrary number of categories.

Usage

```
pal_gephi(palette = gephi_palettes(), alpha = 1)
```

Arguments

palette	Palette type. See gephi_palettes() for available options.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Details

The Gephi palette generator uses the current R random number state directly. If you need reproducible results, call [base::set.seed\(\)](#) before creating a palette or evaluating the scale. To isolate RNG side effects, consider using [withr::with_seed\(\)](#).

Examples

```
library("scales")
set.seed(42)
show_col(pal_gephi("default")(10))
show_col(pal_gephi("fancy_light")(20))
```

pal_gsea	<i>The GSEA GenePattern color palettes</i>
----------	--

Description

Color palette inspired by the colors used in the heatmaps plotted by GSEA GenePattern.

Usage

```
pal_gsea(palette = c("default"), n = 12, alpha = 1, reverse = FALSE)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (continuous palette with 12 base colors).
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_gsea("default")(12))
show_col(pal_gsea("default", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_igv

Integrative Genomics Viewer (IGV) color palettes

Description

Color palettes based on the colors used by Integrative Genomics Viewer (IGV).

Usage

```
pal_igv(palette = c("default", "alternating"), alpha = 1)
```

Arguments

palette	Palette type. There are two available options: • "default" (51-color palette). • "alternating" (2-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

James T. Robinson, Helga Thorvaldsdóttir, Wendy Winckler, Mitchell Guttman, Eric S. Lander, Gad Getz, Jill P. Mesirov. Integrative Genomics Viewer. *Nature Biotechnology* 29, 24–26 (2011).

Examples

```
library("scales")
show_col(pal_igv("default")(51))
show_col(pal_igv("alternating")(2))
```

pal_iterm

iTerm color palettes

Description

ANSI terminal color palettes sourced from the `iterm2-color-schemes` project. Each theme provides normal and bright variants.

Usage

```
pal_iterm(
  palette = iterm_palettes(),
  variant = c("normal", "bright"),
  alpha = 1
)
```

Arguments

palette	Palette name. See <code>iterm_palettes()</code> for available options.
variant	Variant of the palette. One of "normal", "bright".
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Details

Preview all available iTerm color palettes in ggsci: <https://nanx.me/ggsci-iterm/>.

References

<https://github.com/mbadolato/iTerm2-Color-Schemes>

Examples

```
library("scales")
show_col(pal_iterm("Rose Pine")(6))
show_col(pal_iterm("Rose Pine", variant = "bright", alpha = 0.7)(6))
```

pal_jama

Journal of the American Medical Association color palettes

Description

Color palette inspired by plots in *The Journal of the American Medical Association*.

Usage

```
pal_jama(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_jama("default")(7))
show_col(pal_jama("default", alpha = 0.6)(7))
```

pal_jco

Journal of Clinical Oncology color palettes

Description

Color palette inspired by plots in *Journal of Clinical Oncology*.

Usage

```
pal_jco(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_jco("default")(10))
show_col(pal_jco("default", alpha = 0.6)(10))
```

pal_lancet

Lancet journal color palettes

Description

Color palettes inspired by plots in Lancet journals, such as *Lancet Oncology*.

Usage

```
pal_lancet(palette = c("lanonc"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "lanonc" (9-color palette inspired by <i>Lancet Oncology</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_lancet("lanonc")(9))
show_col(pal_lancet("lanonc", alpha = 0.6)(9))
```

pal_locuszoom	<i>LocusZoom color palette</i>
---------------	--------------------------------

Description

Color palettes based on the colors used by LocusZoom.

Usage

```
pal_locuszoom(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Pruim, Randall J., et al. (2010). LocusZoom: regional visualization of genome-wide association scan results. *Bioinformatics*, 26(18), 2336–2337.

Examples

```
library("scales")
show_col(pal_locuszoom("default")(7))
show_col(pal_locuszoom("default", alpha = 0.6)(7))
```

pal_material	<i>Material Design color palettes</i>
--------------	---------------------------------------

Description

Material Design 2 color palettes.

Usage

```
pal_material(
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",
    "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",
    "deep-orange", "brown", "grey", "blue-grey"),
  n = 10,
  alpha = 1,
  reverse = FALSE
)
```

Arguments

palette	Palette type. There are 19 available options: • "red" • "pink" • "purple" • "deep-purple" • "indigo" • "blue" • "light-blue" • "cyan" • "teal" • "green" • "light-green" • "lime" • "yellow" • "amber" • "orange" • "deep-orange" • "brown" • "grey" • "blue-grey"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_material("indigo")(10))
show_col(pal_material("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_nejm	NEJM color palettes
----------	---------------------

Description

Color palette inspired by plots in *The New England Journal of Medicine*.

Usage

```
pal_nejm(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (8-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_nejm("default")(8))
show_col(pal_nejm("default", alpha = 0.6)(8))
```

pal_npg	NPG journal color palettes
---------	----------------------------

Description

Color palettes inspired by plots in journals published by Nature Publishing Group, such as *Nature Reviews Cancer*.

Usage

```
pal_npg(palette = c("nrc"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "nrc" (10-color palette inspired by <i>Nature Reviews Cancer</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_npg("nrc")(10))
show_col(pal_npg("nrc", alpha = 0.6)(10))
```

pal_observable	<i>Observable 10 color palette</i>
----------------	------------------------------------

Description

The Observable 10 palette.

Usage

```
pal_observable(palette = c("observable10"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "observable10" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Pettiross J (2023). "Crafting data colors and staying on brand." *Observable blog*. <https://observablehq.com/blog/crafting-data-colors>

Examples

```
library("scales")
show_col(pal_observable("observable10")(10))
show_col(pal_observable("observable10", alpha = 0.6)(10))
```

`pal_primer`*Primer design system palette*

Description

The Primer design system data visualization palette.

Usage

```
pal_primer(palette = c("mark17"), alpha = 1)
```

Arguments

<code>palette</code>	Palette type. Currently there is one available option: "mark17" (17-color palette).
<code>alpha</code>	Transparency level, a real number in (0, 1]. See <code>alpha</code> in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

References

GitHub (2025). "Primer data visualization colors." <https://primer.style/product/ui-patterns/data-visualization/>

Examples

```
library("scales")
show_col(pal_primer("mark17")(17))
show_col(pal_primer("mark17", alpha = 0.6)(17))
```

`pal_rickandmorty`*Rick and Morty color palettes*

Description

Color palettes inspired by the colors used in *Rick and Morty*.

Usage

```
pal_rickandmorty(palette = c("schwifty"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "schwifty" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_rickandmarty("schwifty")(12))
show_col(pal_rickandmarty("schwifty", alpha = 0.6)(12))
```

pal_simpsons	<i>The Simpsons color palettes</i>
--------------	------------------------------------

Description

Color palettes inspired by the colors used in *The Simpsons*.

Usage

```
pal_simpsons(palette = c("springfield"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "springfield" (16-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_simpsons("springfield")(16))
show_col(pal_simpsons("springfield", alpha = 0.6)(16))
```

pal_startrek	<i>Star Trek color palettes</i>
--------------	---------------------------------

Description

Color palettes inspired by the colors used in *Star Trek*.

Usage

```
pal_startrek(palette = c("uniform"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "uniform" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_startrek("uniform")(7))
show_col(pal_startrek("uniform", alpha = 0.6)(7))
```

pal_tron	<i>Tron Legacy color palettes</i>
----------	-----------------------------------

Description

Color palettes inspired by the colors used in *Tron Legacy*.

Usage

```
pal_tron(palette = c("legacy"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "legacy" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_tron("legacy")(7))
show_col(pal_tron("legacy", alpha = 0.6)(7))
```

pal_tw3

Tailwind CSS color palettes

Description

Tailwind CSS color palettes.

Usage

```
pal_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  n = 10,
  alpha = 1,
  reverse = FALSE
)
```

Arguments

palette	Palette type. There are 22 available options: • "slate" • "gray" • "zinc" • "neutral" • "stone" • "red" • "orange" • "amber" • "yellow" • "lime" • "green" • "emerald" • "teal" • "cyan" • "sky"
---------	--

	• "blue" • "indigo" • "violet" • "purple" • "fuchsia" • "pink" • "rose"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_tw3("rose")(10))
show_col(pal_tw3("rose", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

pal_uchicago

The University of Chicago color palettes

Description

Color palettes based on the colors used by the University of Chicago.

Usage

```
pal_uchicago(palette = c("default", "light", "dark"), alpha = 1)
```

Arguments

palette	Palette type. There are three available options: • "default" (9-color palette); • "light" (9-color light palette); • "dark" (9-color dark palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

https://news.uchicago.edu/sites/default/files/UCM_UniversityIdentityGuidelines_2-2020.pdf

Examples

```
library("scales")
show_col(pal_uchicago("default")(9))
show_col(pal_uchicago("light")(9))
show_col(pal_uchicago("dark")(9))
```

pal_ucscgb

UCSC Genome Browser color palette

Description

Color palette from UCSC Genome Browser chromosome colors.

Usage

```
pal_ucscgb(palette = c("default"), alpha = 1)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (26-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_ucscgb("default")(26))
show_col(pal_ucscgb("default", alpha = 0.6)(26))
```

`rgb_bs5`*Bootstrap 5 color palettes*

Description

Bootstrap 5 color palettes.

Usage

```
rgb_bs5(  
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",  
             "teal", "cyan", "gray"),  
  n = 10,  
  alpha = 1,  
  reverse = FALSE  
)
```

Arguments

palette	Palette type. There are 11 available options: • "blue" • "indigo" • "purple" • "pink" • "red" • "orange" • "yellow" • "green" • "teal" • "cyan" • "gray"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

<https://getbootstrap.com/docs/5.3/customize/color/#all-colors>

Examples

```
library("scales")
show_col(pal_bs5("indigo")(10))
show_col(pal_bs5("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

 rgb_gsea

The GSEA GenePattern color palettes

Description

Color palette inspired by the colors used in the heatmaps plotted by GSEA GenePattern.

Usage

```
rgb_gsea(palette = c("default"), n = 12, alpha = 1, reverse = FALSE)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (continuous palette with 12 base colors).
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Note

The 12 base colors used in this palette are derived from the [HeatMapImage documentation](#).

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("scales")
show_col(pal_gsea("default")(12))
show_col(pal_gsea("default", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

rgb_material	<i>Material Design color palettes</i>
--------------	---------------------------------------

Description

Material Design 2 color palettes.

Usage

```
rgb_material(  
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",  
    "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",  
    "deep-orange", "brown", "grey", "blue-grey"),  
  n = 10,  
  alpha = 1,  
  reverse = FALSE  
)
```

Arguments

palette	Palette type. There are 19 available options: • "red" • "pink" • "purple" • "deep-purple" • "indigo" • "blue" • "light-blue" • "cyan" • "teal" • "green" • "light-green" • "lime" • "yellow" • "amber" • "orange" • "deep-orange" • "brown" • "grey" • "blue-grey"
n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

<https://m2.material.io/design/color/the-color-system.html>

Examples

```
library("scales")
show_col(pal_material("indigo")(10))
show_col(pal_material("indigo", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

rgb_tw3

Tailwind CSS color palettes

Description

Tailwind CSS color palettes.

Usage

```
rgb_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  n = 10,
  alpha = 1,
  reverse = FALSE
)
```

Arguments

palette Palette type. There are 22 available options:

- "slate"
- "gray"
- "zinc"
- "neutral"
- "stone"
- "red"
- "orange"
- "amber"
- "yellow"
- "lime"
- "green"

- "emerald"
- "teal"
- "cyan"
- "sky"
- "blue"
- "indigo"
- "violet"
- "purple"
- "fuchsia"
- "pink"
- "rose"

n	Number of individual colors to be generated.
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
reverse	Logical. Should the order of the colors be reversed?

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

<https://tailwindcss.com/docs/customizing-colors>

Examples

```
library("scales")
show_col(pal_tw3("rose")(10))
show_col(pal_tw3("rose", n = 30, alpha = 0.6, reverse = TRUE)(30))
```

scale_color_aaas	<i>AAAS journal color scales</i>
------------------	----------------------------------

Description

See `pal_aaas()` for details.

Usage

```
scale_color_aaas(palette = c("default"), alpha = 1, ...)
scale_colour_aaas(palette = c("default"), alpha = 1, ...)
scale_fill_aaas(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette inspired by <i>Science</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_aaas()
example_barplot() + scale_fill_aaas()
```

scale_color_atlassian *Atlassian Design System color scales*

Description

See `pal_atlassian()` for details.

Usage

```
scale_color_atlassian(palette = c("categorical8"), alpha = 1, ...)
scale_colour_atlassian(palette = c("categorical8"), alpha = 1, ...)
scale_fill_atlassian(palette = c("categorical8"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "categorical8" (8-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Atlassian (2025). "Atlassian Design System categorical chart colors." <https://atlassian.design/foundations/color-new/data-visualization-color>

Examples

```
example_scatterplot() + scale_color_atlassian()  
example_barplot() + scale_fill_atlassian()
```

scale_color_bmj	<i>BMJ color scales</i>
-----------------	-------------------------

Description

See [pal_bmj\(\)](#) for details.

Usage

```
scale_color_bmj(palette = c("default"), alpha = 1, ...)  
scale_colour_bmj(palette = c("default"), alpha = 1, ...)  
scale_fill_bmj(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (9-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Hui Chen | <huichen@zju.edu.cn>

References

<https://github.com/BMJ-Ltd/living-style-guide>

Examples

```
example_scatterplot() + scale_color_bmj()  
example_barplot() + scale_fill_bmj()
```

scale_color_bs5	<i>Bootstrap 5 color scales</i>
-----------------	---------------------------------

Description

See [pal_bs5\(\)](#) for details.

Usage

```
scale_color_bs5(  
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",  
             "teal", "cyan", "gray"),  
  alpha = 1,  
  reverse = FALSE,  
  ...  
)  
  
scale_colour_bs5(  
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",  
             "teal", "cyan", "gray"),  
  alpha = 1,  
  reverse = FALSE,  
  ...  
)  
  
scale_fill_bs5(  
  palette = c("blue", "indigo", "purple", "pink", "red", "orange", "yellow", "green",  
             "teal", "cyan", "gray"),  
  alpha = 1,  
  reverse = FALSE,  
  ...  
)
```

Arguments

palette	Palette type. There are 11 available options: • "blue" • "indigo" • "purple" • "pink" • "red" • "orange" • "yellow" • "green" • "teal"
---------	--

- "cyan"
- "gray"

alpha Transparency level, a real number in (0, 1]. See alpha in `grDevices::rgb()` for details.

reverse Logical. Should the order of the colors be reversed?

... Additional parameters for `ggplot2::discrete_scale()`.

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")

data("mtcars")
cor <- abs(cor(mtcars))
cor_melt <- data.frame(
  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_bs5("teal")
```

scale_color_cosmic *COSMIC color scales*

Description

See `pal_cosmic()` for details.

Usage

```
scale_color_cosmic(
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),
  alpha = 1,
  ...
)

scale_colour_cosmic(
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),
```

```

    alpha = 1,
    ...
  )

scale_fill_cosmic(
  palette = c("hallmarks_light", "hallmarks_dark", "signature_substitutions"),
  alpha = 1,
  ...
)

```

Arguments

palette	Palette type. Currently there are three available options: • "signature_substitutions" (6-color palette). • "hallmarks_light" (10-color palette). • "hallmarks_dark" (10-color palette). The "hallmarks_light" option is from Hanahan and Weinberg (2011) .
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Joshua H. Cook | <joshuacook0023@gmail.com> | [@jhrcook](#)

Examples

```

example_scatterplot() + scale_color_cosmic()
example_barplot() + scale_fill_cosmic()

```

scale_color_d3	<i>D3.js color scales</i>
----------------	---------------------------

Description

See [pal_d3\(\)](#) for details.

Usage

```

scale_color_d3(
  palette = c("category10", "category20", "category20b", "category20c"),
  alpha = 1,
  ...
)

scale_colour_d3(

```

```

    palette = c("category10", "category20", "category20b", "category20c"),
    alpha = 1,
    ...
)

scale_fill_d3(
  palette = c("category10", "category20", "category20b", "category20c"),
  alpha = 1,
  ...
)

```

Arguments

palette	Palette type. There are four available options: • "category10" (10-color palette). • "category20" (20-color palette). • "category20b" (20-color palette). • "category20c" (20-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

References

<https://github.com/d3/d3-3.x-api-reference/blob/master/Ordinal-Scales.md>

Examples

```

p1 <- example_scatterplot()
p2 <- example_barplot()

p1 + scale_color_d3()
p2 + scale_fill_d3()

p1 + scale_color_d3(palette = "category20")
p2 + scale_fill_d3(palette = "category20")

p1 + scale_color_d3(palette = "category20b")
p2 + scale_fill_d3(palette = "category20b")

p1 + scale_color_d3(palette = "category20c")
p2 + scale_fill_d3(palette = "category20c")

```

scale_color_flatui	<i>Flat UI color scales</i>
--------------------	-----------------------------

Description

See [pal_flatui\(\)](#) for details.

Usage

```
scale_color_flatui(  
  palette = c("default", "flattastic", "aussie"),  
  alpha = 1,  
  ...  
)  
  
scale_colour_flatui(  
  palette = c("default", "flattastic", "aussie"),  
  alpha = 1,  
  ...  
)  
  
scale_fill_flatui(  
  palette = c("default", "flattastic", "aussie"),  
  alpha = 1,  
  ...  
)
```

Arguments

palette	Palette type. Currently there are three available options: • "default" (10-color palette). • "flattastic" (12-color palette). • "aussie" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Clara Jégousse | [<cat3@hi.is>](mailto:cat3@hi.is)

Examples

```
p1 <- example_scatterplot()  
p2 <- example_barplot()
```

```

p1 + scale_color_flatui()
p2 + scale_fill_flatui()

p1 + scale_color_flatui(palette = "default")
p2 + scale_fill_flatui(palette = "default")

p1 + scale_color_flatui(palette = "flattastic")
p2 + scale_fill_flatui(palette = "flattastic")

p1 + scale_color_flatui(palette = "aussie")
p2 + scale_fill_flatui(palette = "aussie")

```

scale_color_frontiers *Frontiers journal color scales*

Description

See [pal_frontiers\(\)](#) for details.

Usage

```

scale_color_frontiers(palette = c("default"), alpha = 1, ...)

scale_colour_frontiers(palette = c("default"), alpha = 1, ...)

scale_fill_frontiers(palette = c("default"), alpha = 1, ...)

```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Clara Jégousse | [<cat3@hi.is>](mailto:cat3@hi.is)

Examples

```

example_scatterplot() +
  ggplot2::theme_dark() +
  ggplot2::theme(
    panel.background = ggplot2::element_rect(fill = "#2D2D2D"),
    legend.key = ggplot2::element_rect(fill = "#2D2D2D")
  ) +
  scale_color_frontiers()

```

```
example_barplot() +  
  ggplot2::theme_dark() +  
  ggplot2::theme(  
    panel.background = ggplot2::element_rect(fill = "#2D2D2D")  
  ) +  
  scale_fill_frontiers()
```

scale_color_futurama *Futurama color scales*

Description

See [pal_futurama\(\)](#) for details.

Usage

```
scale_color_futurama(palette = c("planetexpress"), alpha = 1, ...)
```

```
scale_colour_futurama(palette = c("planetexpress"), alpha = 1, ...)
```

```
scale_fill_futurama(palette = c("planetexpress"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "planetexpress" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_futurama()  
example_barplot() + scale_fill_futurama()
```

scale_color_gephi	<i>Gephi color scales</i>
-------------------	---------------------------

Description

See [pal_gephi\(\)](#) for details.

Usage

```
scale_color_gephi(palette = gephi_palettes(), alpha = 1, ...)
```

```
scale_colour_gephi(palette = gephi_palettes(), alpha = 1, ...)
```

```
scale_fill_gephi(palette = gephi_palettes(), alpha = 1, ...)
```

Arguments

palette	Palette type. See gephi_palettes() for available options.
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Examples

```
set.seed(42)
example_scatterplot() + scale_color_gephi()
example_barplot() + scale_fill_gephi("fancy_light")
```

scale_color_gsea	<i>The GSEA GenePattern color scales</i>
------------------	--

Description

See [pal_gsea\(\)](#) for details.

Usage

```
scale_color_gsea(palette = c("default"), alpha = 1, reverse = FALSE, ...)
```

```
scale_colour_gsea(palette = c("default"), alpha = 1, reverse = FALSE, ...)
```

```
scale_fill_gsea(palette = c("default"), alpha = 1, reverse = FALSE, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (continuous palette with 12 base colors).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
library("ggplot2")

data("mtcars")
cor <- cor(mtcars)
cor_melt <- data.frame(
  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_gsea()
```

scale_color_igv

Integrative Genomics Viewer (IGV) color scales

Description

See [pal_igv\(\)](#) for details.

Usage

```
scale_color_igv(palette = c("default", "alternating"), alpha = 1, ...)

scale_colour_igv(palette = c("default", "alternating"), alpha = 1, ...)

scale_fill_igv(palette = c("default", "alternating"), alpha = 1, ...)
```

Arguments

palette	Palette type. There are two available options: • "default" (51-color palette). • "alternating" (2-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
p1 <- example_scatterplot()
p2 <- example_barplot()

p1 + scale_color_igv()
p2 + scale_fill_igv()

p1 + ggplot2::scale_colour_manual(
  values = rep(pal_igv("alternating")(2), times = 3)
)
p2 + ggplot2::scale_fill_manual(
  values = rep(pal_igv("alternating")(2), times = 3)
)
```

scale_color_iterm *iTerm color scales*

Description

See `pal_iterm()` for details.

Usage

```
scale_color_iterm(
  palette = iterm_palettes(),
  variant = c("normal", "bright"),
  alpha = 1,
  ...
)

scale_colour_iterm(
  palette = iterm_palettes(),
  variant = c("normal", "bright"),
  alpha = 1,
```

```

    ...
  )

scale_fill_iterm(
  palette = iterm_palettes(),
  variant = c("normal", "bright"),
  alpha = 1,
  ...
)

```

Arguments

palette	Palette name. See <code>iterm_palettes()</code> for available options.
variant	Variant of the palette. One of "normal", "bright".
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Details

Preview all available iTerm color palettes in ggsci: <https://nanx.me/ggsci-iterm/>.

Examples

```

example_scatterplot() + scale_color_iterm("Rose Pine")
example_barplot() + scale_fill_iterm("Rose Pine")

```

scale_color_jama	<i>Journal of the American Medical Association color scales</i>
------------------	---

Description

See `pal_jama()` for details.

Usage

```

scale_color_jama(palette = c("default"), alpha = 1, ...)

scale_colour_jama(palette = c("default"), alpha = 1, ...)

scale_fill_jama(palette = c("default"), alpha = 1, ...)

```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_jama()
example_barplot() + scale_fill_jama()
```

scale_color_jco	<i>Journal of Clinical Oncology color scales</i>
-----------------	--

Description

See [pal_jco\(\)](#) for details.

Usage

```
scale_color_jco(palette = c("default"), alpha = 1, ...)
scale_colour_jco(palette = c("default"), alpha = 1, ...)
scale_fill_jco(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_jco()
example_barplot() + scale_fill_jco()
```

scale_color_lancet *Lancet journal color scales*

Description

See [pal_lancet\(\)](#) for details.

Usage

```
scale_color_lancet(palette = c("lanonc"), alpha = 1, ...)
```

```
scale_colour_lancet(palette = c("lanonc"), alpha = 1, ...)
```

```
scale_fill_lancet(palette = c("lanonc"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "lanonc" (9-color palette inspired by <i>Lancet Oncology</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_lancet()
example_barplot() + scale_fill_lancet()
```

scale_color_locuszoom *LocusZoom color scales*

Description

See [pal_locuszoom\(\)](#) for details.

Usage

```
scale_color_locuszoom(palette = c("default"), alpha = 1, ...)
```

```
scale_colour_locuszoom(palette = c("default"), alpha = 1, ...)
```

```
scale_fill_locuszoom(palette = c("default"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "default" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_locuszoom()
example_barplot() + scale_fill_locuszoom()
```

scale_color_material *Material Design color scales*

Description

See `pal_material()` for details.

Usage

```
scale_color_material(
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",
    "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",
    "deep-orange", "brown", "grey", "blue-grey"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_colour_material(
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",
    "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",
    "deep-orange", "brown", "grey", "blue-grey"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_fill_material(
  palette = c("red", "pink", "purple", "deep-purple", "indigo", "blue", "light-blue",
    "cyan", "teal", "green", "light-green", "lime", "yellow", "amber", "orange",
    "deep-orange", "brown", "grey", "blue-grey"),
```

```

    alpha = 1,
    reverse = FALSE,
    ...
  )

```

Arguments

palette	Palette type. There are 19 available options: • "red" • "pink" • "purple" • "deep-purple" • "indigo" • "blue" • "light-blue" • "cyan" • "teal" • "green" • "light-green" • "lime" • "yellow" • "amber" • "orange" • "deep-orange" • "brown" • "grey" • "blue-grey"
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```

library("ggplot2")

data("mtcars")
cor <- abs(cor(mtcars))
cor_melt <- data.frame(
  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

```



```

)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_material("blue-grey")

```

scale_color_nejm	<i>NEJM color scales</i>
------------------	--------------------------

Description

See [pal_nejm\(\)](#) for details.

Usage

```

scale_color_nejm(palette = c("default"), alpha = 1, ...)

scale_colour_nejm(palette = c("default"), alpha = 1, ...)

scale_fill_nejm(palette = c("default"), alpha = 1, ...)

```

Arguments

palette	Palette type. Currently there is one available option: "default" (8-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```

example_scatterplot() + scale_color_nejm()
example_barplot() + scale_fill_nejm()

```

scale_color_npg	<i>NPG journal color scales</i>
-----------------	---------------------------------

Description

See [pal_npg\(\)](#) for details.

Usage

```
scale_color_npg(palette = c("nrc"), alpha = 1, ...)
scale_colour_npg(palette = c("nrc"), alpha = 1, ...)
scale_fill_npg(palette = c("nrc"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "nrc" (10-color palette inspired by <i>Nature Reviews Cancer</i>).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_npg()
example_barplot() + scale_fill_npg()
```

scale_color_observable	<i>Observable 10 color scales</i>
------------------------	-----------------------------------

Description

See [pal_observable\(\)](#) for details.

Usage

```
scale_color_observable(palette = c("observable10"), alpha = 1, ...)
scale_colour_observable(palette = c("observable10"), alpha = 1, ...)
scale_fill_observable(palette = c("observable10"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "observable10" (10-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

Pettiross J (2023). "Crafting data colors and staying on brand." *Observable blog*. <https://observablehq.com/blog/crafting-data-colors>

Examples

```
example_scatterplot() + scale_color_observable()
example_barplot() + scale_fill_observable()
```

scale_color_primer	<i>Primer color scales</i>
--------------------	----------------------------

Description

See `pal_primer()` for details.

Usage

```
scale_color_primer(palette = c("mark17"), alpha = 1, ...)
scale_colour_primer(palette = c("mark17"), alpha = 1, ...)
scale_fill_primer(palette = c("mark17"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "mark17" (17-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

References

GitHub (2025). "Primer data visualization colors." <https://primer.style/product/ui-patterns/data-visualization/>

Examples

```
example_scatterplot() + scale_color_primer()
example_barplot() + scale_fill_primer()
```

scale_color_rickandmorty

Rick and Morty color scales

Description

See [pal_rickandmorty\(\)](#) for details.

Usage

```
scale_color_rickandmorty(palette = c("schwifty"), alpha = 1, ...)
scale_colour_rickandmorty(palette = c("schwifty"), alpha = 1, ...)
scale_fill_rickandmorty(palette = c("schwifty"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "schwifty" (12-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_rickandmorty()
example_barplot() + scale_fill_rickandmorty()
```

scale_color_simpsons *The Simpsons color scales*

Description

See [pal_simpsons\(\)](#) for details.

Usage

```
scale_color_simpsons(palette = c("springfield"), alpha = 1, ...)
```

```
scale_colour_simpsons(palette = c("springfield"), alpha = 1, ...)
```

```
scale_fill_simpsons(palette = c("springfield"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "springfield" (16-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_simpsons()
example_barplot() + scale_fill_simpsons()
```

scale_color_startrek *Star Trek color scales*

Description

See [pal_startrek\(\)](#) for details.

Usage

```
scale_color_startrek(palette = c("uniform"), alpha = 1, ...)
```

```
scale_colour_startrek(palette = c("uniform"), alpha = 1, ...)
```

```
scale_fill_startrek(palette = c("uniform"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "uniform" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
example_scatterplot() + scale_color_startrek()
example_barplot() + scale_fill_startrek()
```

scale_color_tron	<i>Tron Legacy color scales</i>
------------------	---------------------------------

Description

See `pal_tron()` for details.

Usage

```
scale_color_tron(palette = c("legacy"), alpha = 1, ...)
scale_colour_tron(palette = c("legacy"), alpha = 1, ...)
scale_fill_tron(palette = c("legacy"), alpha = 1, ...)
```

Arguments

palette	Palette type. Currently there is one available option: "legacy" (7-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in <code>grDevices::rgb()</code> for details.
...	Additional parameters for <code>ggplot2::discrete_scale()</code> .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
example_scatterplot() +
  ggplot2::theme_dark() +
  ggplot2::theme(
    panel.background = ggplot2::element_rect(fill = "#2D2D2D"),
    legend.key = ggplot2::element_rect(fill = "#2D2D2D")
  ) +
  scale_color_tron()

example_barplot() +
  ggplot2::theme_dark() +
  ggplot2::theme(
    panel.background = ggplot2::element_rect(fill = "#2D2D2D")
  ) +
  scale_fill_tron()
```

scale_color_tw3

Tailwind CSS color scales

Description

See [pal_tw3\(\)](#) for details.

Usage

```
scale_color_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_colour_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  alpha = 1,
  reverse = FALSE,
  ...
)

scale_fill_tw3(
  palette = c("slate", "gray", "zinc", "neutral", "stone", "red", "orange", "amber",
    "yellow", "lime", "green", "emerald", "teal", "cyan", "sky", "blue", "indigo",
    "violet", "purple", "fuchsia", "pink", "rose"),
  alpha = 1,
```

```
reverse = FALSE,
...
)
```

Arguments

palette	Palette type. There are 22 available options: • "slate" • "gray" • "zinc" • "neutral" • "stone" • "red" • "orange" • "amber" • "yellow" • "lime" • "green" • "emerald" • "teal" • "cyan" • "sky" • "blue" • "indigo" • "violet" • "purple" • "fuchsia" • "pink" • "rose"
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
reverse	Logical. Should the order of the colors be reversed?
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | <me@nanx.me> | <https://nanx.me>

Examples

```
library("ggplot2")

data("mtcars")
cor <- abs(cor(mtcars))
cor_melt <- data.frame(
```



```

  Var1 = rep(seq_len(nrow(cor)), times = ncol(cor)),
  Var2 = rep(seq_len(ncol(cor)), each = nrow(cor)),
  value = as.vector(cor)
)

ggplot(
  cor_melt,
  aes(x = Var1, y = Var2, fill = value)
) +
  geom_tile(colour = "black", size = 0.3) +
  theme_bw() +
  scale_fill_tw3("slate")

```

scale_color_uchicago *The University of Chicago color scales*

Description

See [pal_uchicago\(\)](#) for details.

Usage

```

scale_color_uchicago(palette = c("default", "light", "dark"), alpha = 1, ...)

scale_colour_uchicago(palette = c("default", "light", "dark"), alpha = 1, ...)

scale_fill_uchicago(palette = c("default", "light", "dark"), alpha = 1, ...)

```

Arguments

palette	Palette type. There are three available options: • "default" (9-color palette); • "light" (9-color light palette); • "dark" (9-color dark palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | me@nanx.me | <https://nanx.me>

References

https://news.uchicago.edu/sites/default/files/UCM_UniversityIdentityGuidelines_2-2020.pdf

Examples

```

p1 <- example_scatterplot()
p2 <- example_barplot()

p1 + scale_color_uchicago()
p2 + scale_fill_uchicago()

p1 + scale_color_uchicago(palette = "light")
p2 + scale_fill_uchicago(palette = "light")

p1 + scale_color_uchicago(palette = "dark")
p2 + scale_fill_uchicago(palette = "dark")

```

scale_color_ucscgb	<i>UCSC Genome Browser color scales</i>
--------------------	---

Description

See [pal_ucscgb\(\)](#) for details.

Usage

```

scale_color_ucscgb(palette = c("default"), alpha = 1, ...)

scale_colour_ucscgb(palette = c("default"), alpha = 1, ...)

scale_fill_ucscgb(palette = c("default"), alpha = 1, ...)

```

Arguments

palette	Palette type. Currently there is one available option: "default" (26-color palette).
alpha	Transparency level, a real number in (0, 1]. See alpha in grDevices::rgb() for details.
...	Additional parameters for ggplot2::discrete_scale() .

Author(s)

Nan Xiao | [<me@nanx.me>](mailto:me@nanx.me) | <https://nanx.me>

Examples

```

example_scatterplot() + scale_color_ucscgb()
example_barplot() + scale_fill_ucscgb()

```

Index

`base::set.seed()`, 12

`example_barplot` (`example_scatterplot`), 3

`example_scatterplot`, 3

`gephi_palettes`, 4

`gephi_palettes()`, 12, 41

`ggplot2::discrete_scale()`, 32, 33, 35–54, 56–58

`grDevices::rgb()`, 5–23, 25–29, 31–33, 35–54, 56–58

`iterm_palettes`, 4

`iterm_palettes()`, 14, 44

`pal_aaas`, 5

`pal_aaas()`, 31

`pal_atlassian`, 5

`pal_atlassian()`, 32

`pal_bmj`, 6

`pal_bmj()`, 33

`pal_bs5`, 7

`pal_bs5()`, 34

`pal_cosmic`, 8

`pal_cosmic()`, 35

`pal_d3`, 9

`pal_d3()`, 36

`pal_flatui`, 10

`pal_flatui()`, 38

`pal_frontiers`, 10

`pal_frontiers()`, 39

`pal_futurama`, 11

`pal_futurama()`, 40

`pal_gephi`, 12

`pal_gephi()`, 41

`pal_gsea`, 12

`pal_gsea()`, 41

`pal_igv`, 13

`pal_igv()`, 42

`pal_iterm`, 14

`pal_iterm()`, 43

`pal_jama`, 15

`pal_jama()`, 44

`pal_jco`, 15

`pal_jco()`, 45

`pal_lancet`, 16

`pal_lancet()`, 46

`pal_locuszoom`, 17

`pal_locuszoom()`, 46

`pal_material`, 17

`pal_material()`, 47

`pal_nejm`, 19

`pal_nejm()`, 49

`pal_npg`, 19

`pal_npg()`, 50

`pal_observable`, 20

`pal_observable()`, 50

`pal_primer`, 21

`pal_primer()`, 51

`pal_rickandmorty`, 21

`pal_rickandmorty()`, 52

`pal_simpsons`, 22

`pal_simpsons()`, 53

`pal_startrek`, 23

`pal_startrek()`, 53

`pal_tron`, 23

`pal_tron()`, 54

`pal_tw3`, 24

`pal_tw3()`, 55

`pal_uchicago`, 25

`pal_uchicago()`, 57

`pal_ucscgb`, 26

`pal_ucscgb()`, 58

`rgb_bs5`, 27

`rgb_gsea`, 28

`rgb_material`, 29

`rgb_tw3`, 30

`scale_color_aaas`, 31

- scale_color_atlassian, 32
- scale_color_bmj, 33
- scale_color_bs5, 34
- scale_color_cosmic, 35
- scale_color_d3, 36
- scale_color_flatui, 38
- scale_color_frontiers, 39
- scale_color_futurama, 40
- scale_color_gephi, 41
- scale_color_gsea, 41
- scale_color_igv, 42
- scale_color_iterm, 43
- scale_color_jama, 44
- scale_color_jco, 45
- scale_color_lancet, 46
- scale_color_locuszoom, 46
- scale_color_material, 47
- scale_color_nejm, 49
- scale_color_npg, 50
- scale_color_observable, 50
- scale_color_primer, 51
- scale_color_rickandmarty, 52
- scale_color_simpsons, 53
- scale_color_startrek, 53
- scale_color_tron, 54
- scale_color_tw3, 55
- scale_color_uchicago, 57
- scale_color_ucscgb, 58
- scale_colour_aaas (scale_color_aaas), 31
- scale_colour_atlassian
 - (scale_color_atlassian), 32
- scale_colour_bmj (scale_color_bmj), 33
- scale_colour_bs5 (scale_color_bs5), 34
- scale_colour_cosmic
 - (scale_color_cosmic), 35
- scale_colour_d3 (scale_color_d3), 36
- scale_colour_flatui
 - (scale_color_flatui), 38
- scale_colour_frontiers
 - (scale_color_frontiers), 39
- scale_colour_futurama
 - (scale_color_futurama), 40
- scale_colour_gephi (scale_color_gephi), 41
- scale_colour_gsea (scale_color_gsea), 41
- scale_colour_igv (scale_color_igv), 42
- scale_colour_iterm (scale_color_iterm), 43
- scale_colour_jama (scale_color_jama), 44
- scale_colour_jco (scale_color_jco), 45
- scale_colour_lancet (scale_color_lancet), 46
- scale_colour_jama (scale_color_jama), 44
- scale_colour_jco (scale_color_jco), 45
- scale_colour_lancet
 - (scale_color_lancet), 46
- scale_colour_locuszoom
 - (scale_color_locuszoom), 46
- scale_colour_material
 - (scale_color_material), 47
- scale_colour_nejm (scale_color_nejm), 49
- scale_colour_npg (scale_color_npg), 50
- scale_colour_observable
 - (scale_color_observable), 50
- scale_colour_primer
 - (scale_color_primer), 51
- scale_colour_rickandmarty
 - (scale_color_rickandmarty), 52
- scale_colour_simpsons
 - (scale_color_simpsons), 53
- scale_colour_startrek
 - (scale_color_startrek), 53
- scale_colour_tron (scale_color_tron), 54
- scale_colour_tw3 (scale_color_tw3), 55
- scale_colour_uchicago
 - (scale_color_uchicago), 57
- scale_colour_ucscgb
 - (scale_color_ucscgb), 58
- scale_fill_aaas (scale_color_aaas), 31
- scale_fill_atlassian
 - (scale_color_atlassian), 32
- scale_fill_bmj (scale_color_bmj), 33
- scale_fill_bs5 (scale_color_bs5), 34
- scale_fill_cosmic (scale_color_cosmic), 35
- scale_fill_d3 (scale_color_d3), 36
- scale_fill_flatui (scale_color_flatui), 38
- scale_fill_frontiers
 - (scale_color_frontiers), 39
- scale_fill_futurama
 - (scale_color_futurama), 40
- scale_fill_gephi (scale_color_gephi), 41
- scale_fill_gsea (scale_color_gsea), 41
- scale_fill_igv (scale_color_igv), 42
- scale_fill_iterm (scale_color_iterm), 43
- scale_fill_jama (scale_color_jama), 44
- scale_fill_jco (scale_color_jco), 45
- scale_fill_lancet (scale_color_lancet), 46

scale_fill_locuszoom
 (scale_color_locuszoom), 46
scale_fill_material
 (scale_color_material), 47
scale_fill_nejm(scale_color_nejm), 49
scale_fill_npg(scale_color_npg), 50
scale_fill_observable
 (scale_color_observable), 50
scale_fill_primer(scale_color_primer),
 51
scale_fill_rickandmorty
 (scale_color_rickandmorty), 52
scale_fill_simpsons
 (scale_color_simpsons), 53
scale_fill_startrek
 (scale_color_startrek), 53
scale_fill_tron(scale_color_tron), 54
scale_fill_tw3(scale_color_tw3), 55
scale_fill_uchicago
 (scale_color_uchicago), 57
scale_fill_ucscgb(scale_color_ucscgb),
 58