

Package ‘markovchain’

September 19, 2026

Type Package

Title Easy Handling Discrete Time Markov Chains

Version 1.1.1

Maintainer Giorgio Alfredo Spedicato <spedicato_giorgio@yahoo.it>

Description Functions and S4 methods to create and manage discrete time Markov chains more easily. In addition functions to perform statistical (fitting and drawing random variates) and probabilistic (analysis of their structural proprieties) analysis are provided. See Spedicato (2017) <[doi:10.32614/RJ-2017-036](https://doi.org/10.32614/RJ-2017-036)>. Some functions for continuous times Markov chains depend on the suggested ctmc package.

License MIT + file LICENSE

Depends R (>= 4.4.0), Matrix (>= 1.5-0), methods

Imports igraph (>= 1.0.0), expm, stats4, parallel, Rcpp (>= 1.0.2), RcppParallel, utils, stats, grDevices

Suggests knitr, testthat, diagram, DiagrammeR, ggplot2 (>= 3.4.0), msm, Rsolnp, rmarkdown, ctmc, bookdown, rticles, MCMCpack, microbenchmark, quarto

Enhances etm

VignetteBuilder rmarkdown, knitr, bookdown, rticles, quarto

LinkingTo Rcpp, RcppParallel, RcppArmadillo (>= 0.9.600.4.0)

SystemRequirements GNU make, Quarto

LazyLoad yes

ByteCompile yes

Encoding UTF-8

BugReports <https://github.com/spedygiorgio/markovchain/issues>

URL <https://github.com/spedygiorgio/markovchain/>

NeedsCompilation yes

Author Giorgio Alfredo Spedicato [aut, cre] (ORCID: <<https://orcid.org/0000-0002-0315-8888>>),
Tae Seung Kang [aut],

Sai Bhargav Yalamanchi [aut],
 Mildenberger Thoralf [ctb] (ORCID: <https://orcid.org/0000-0001-7242-1873>),
 Deepak Yadav [aut],
 Ignacio Córdón [aut] (ORCID: <https://orcid.org/0000-0002-3152-0231>),
 Vandit Jain [ctb],
 Toni Giorgino [ctb] (ORCID: <https://orcid.org/0000-0001-6449-0596>),
 Richèl J.C. Bilderbeek [ctb] (ORCID: <https://orcid.org/0000-0003-1107-7049>),
 Daniel Ebbert [ctb] (ORCID: <https://orcid.org/0000-0003-3666-7205>),
 Shreyash Maheshwari [ctb],
 Reinhold Koch [ctb]

Config/roxygen2/version 8.1.0

Repository CRAN

Date/Publication 2026-09-18 22:00:02 UTC

Contents

markovchain-package	4
absorptionProbabilities	5
autoLump	6
autoplot.markovchain	6
blanden	7
committorAB	8
conditionalDistribution	9
craigsendi	10
createSequenceMatrix	11
ctmc-class	13
ctmcFit	15
entropyRate	16
expectedRewards	17
expectedRewardsBeforeHittingA	18
ExpectedTime	19
firstPassage	20
firstPassageMultiple	21
fitHigherOrder	22
fitHighOrderMultivarMC	23
freq2Generator	24
fundamentalMatrix	25
generatorToTransitionMatrix	26
HigherOrderMarkovChain-class	27
hittingProbabilities	27
holson	28
hommc-class	29
ictmc-class	30
impreciseProbabilityatT	30
inferHyperparam	31

is.accessible	32
is.CTMCIrreducible	33
is.irreducible	34
is.lumpable	35
is.regular	36
is.stochasticallyMonotone	37
is.TimeReversible	37
kemenyConstant	38
kullback	40
lump	40
markovchain-class	41
markovchainList-class	43
markovchainListFit	45
markovchainSequence	46
meanAbsorptionTime	47
meanFirstPassageTime	48
meanNumVisits	49
meanRecurrenceTime	50
multinomialConfidenceIntervals	51
name	52
name<-	52
names,markovchain-method	53
noofVisitsDist	54
ones	55
period	55
predictHommc	57
predictiveDistribution	58
preproglucacon	59
priorDistribution	60
probabilityatT	61
rain	62
rctmc	63
rmarkovchain	64
sales	66
show,hommc-method	66
states	67
steadyStates	68
tm_abs	69
transition2Generator	69
transitionProbability	70
verifyMarkovProperty	71
zeros	73

markovchain-package *Easy Handling Discrete Time Markov Chains*

Description

The package contains classes and method to create and manage (plot, print, export for example) discrete time Markov chains (DTMC). In addition it provide functions to perform statistical (fitting and drawing random variates) and probabilistic (analysis of DTMC proprieties) analysis

Author(s)

Giorgio Alfredo Spedicato Maintainer: Giorgio Alfredo Spedicato <spedicato_giorgio@yahoo.it>

References

Discrete-Time Markov Models, Bremaud, Springer 1999

See Also

Useful links:

- <https://github.com/spedygiorgio/markovchain/>
- Report bugs at <https://github.com/spedygiorgio/markovchain/issues>

Examples

```
# create some markov chains
statesNames=c("a","b")
mcA<-new("markovchain", transitionMatrix=matrix(c(0.7,0.3,0.1,0.9),byrow=TRUE,
  nrow=2, dimnames=list(statesNames,statesNames)))

statesNames=c("a","b","c")
mcB<-new("markovchain", states=statesNames, transitionMatrix=
  matrix(c(0.2,0.5,0.3,0,1,0,0.1,0.8,0.1), nrow=3,
  byrow=TRUE, dimnames=list(statesNames, statesNames)))

statesNames=c("a","b","c","d")
matrice<-matrix(c(0.25,0.75,0,0,0.4,0.6,0,0,0,0.1,0.9,0,0,0.7,0.3), nrow=4, byrow=TRUE)
mcC<-new("markovchain", states=statesNames, transitionMatrix=matrice)
mcD<-new("markovchain", transitionMatrix=matrix(c(0,1,0,1), nrow=2,byrow=TRUE))

#operations with S4 methods
mcA^2
steadyStates(mcB)
absorbingStates(mcB)
markovchainSequence(n=20, markovchain=mcC, include=TRUE)
```

`absorptionProbabilities`*Absorption probabilities*

Description

Computes the absorption probability from each transient state to each recurrent one (i.e. the (i, j) entry or (j, i), in a stochastic matrix by columns, represents the probability that the first not transient state we can go from the transient state i is j (and therefore we are going to be absorbed in the communicating recurrent class of j)

Usage

```
absorptionProbabilities(object)
```

Arguments

`object` the markovchain object

Value

A named vector with the expected number of steps to go from a transient state to any of the recurrent ones

Author(s)

Ignacio Córdón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```
m <- matrix(c(1/2, 1/2, 0,
              1/2, 1/2, 0,
              0, 1/2, 1/2), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = letters[1:3], transitionMatrix = m)
absorptionProbabilities(mc)
```

autoLump

Automatically aggregate a Markov chain by spectral clustering

Description

Finds an approximate partition by clustering the leading right eigenvectors of the transition matrix, then returns the forced lumping over that partition. This is a heuristic for approximate lumping/metastable aggregation, not a proof of exact lumpability.

Usage

```
autoLump(object, k)
```

```
## S4 method for signature 'markovchain'
autoLump(object, k)
```

Arguments

object	A markovchain object.
k	Number of macro-states to discover.

Value

A list with partition and lumped_chain.

autoplot.markovchain *Plot a Markov chain with ggplot2*

Description

Creates a ggplot2 representation of a discrete-time Markov chain. Nodes are states and directed edges represent transitions with positive probability. Communicating classes are shown with different node fills.

Usage

```
autoplot.markovchain(
  object,
  threshold = 0,
  show_probabilities = TRUE,
  digits = 2,
  node_size = 6,
  edge_width = 1,
  ...
)
```

Arguments

<code>object</code>	An object of class ‘markovchain’.
<code>threshold</code>	Minimum transition probability to display. Defaults to 0.
<code>show_probabilities</code>	Logical; whether to label edges with transition probabilities. Defaults to ‘TRUE’.
<code>digits</code>	Number of digits used to format transition probabilities.
<code>node_size</code>	Size of state nodes in the ggplot2 plot.
<code>edge_width</code>	Minimum width multiplier for transition edges.
<code>...</code>	Currently unused, reserved for future extensions.

Value

A ggplot object.

Examples

```
if (requireNamespace("ggplot2", quietly = TRUE)) {
  weather <- matrix(c(0.7, 0.2, 0.1,
                     0.3, 0.4, 0.3,
                     0.2, 0.45, 0.35),
                   nrow = 3, byrow = TRUE,
                   dimnames = list(c("sunny", "cloudy", "rain"),
                                   c("sunny", "cloudy", "rain")))
  mc <- new("markovchain", states = rownames(weather),
           transitionMatrix = weather, name = "Weather")
  ggplot2::autoplot(mc)
}
```

blanden

Mobility between income quartiles

Description

This table show mobility between income quartiles for father and sons for the 1970 cohort born

Usage

```
data(blanden)
```

Format

An object of class table with 4 rows and 4 columns.

Details

The rows represent fathers’ income quartile when the son is aged 16, whilst the columns represent sons’ income quartiles when he is aged 30 (in 2000).

Source

Personal reworking

References

Jo Blanden, Paul Gregg and Stephen Machin, Intergenerational Mobility in Europe and North America, Center for Economic Performances (2005)

Examples

```
data(blanden)
mobilityMc<-as(blanden, "markovchain")
```

committorAB

Calculates committor of a markovchain object with respect to set A, B

Description

Returns the probability of hitting states rom set A before set B with different initial states

Usage

```
committorAB(object,A,B,p)
```

Arguments

object	a markovchain class object
A	a set of states
B	a set of states
p	initial state (default value : 1)

Details

The function solves a system of linear equations to calculate probaility that the process hits a state from set A before any state from set B

Value

Return a vector of probabilities in case initial state is not provided else returns a number

Examples

```
transMatr <- matrix(c(0,0,0,1,0.5,
                     0.5,0,0,0,0,
                     0.5,0,0,0,0,
                     0,0.2,0.4,0,0,
                     0,0.8,0.6,0,0.5),
                    nrow = 5)
object <- new("markovchain", states=c("a","b","c","d","e"),transitionMatrix=transMatr)
committorAB(object,c(5),c(3))
```

conditionalDistribution

conditionalDistribution of a Markov Chain

Description

It extracts the conditional distribution of the subsequent state, given current state.

Usage

```
conditionalDistribution(object, state)
```

Arguments

object	A markovchain object.
state	Subsequent state.

Value

A named probability vector

Author(s)

Giorgio Spedicato, Deepak Yadav

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchain](#)

Examples

```
# define a markov chain
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
    byrow = TRUE, dimnames = list(statesNames, statesNames)))

conditionalDistribution(markovB, "b")
```

craigsendi

CD4 cells counts on HIV Infects between zero and six month

Description

This is the table shown in Craig and Sendi paper showing zero and six month CD4 cells count in six brackets

Usage

```
data(craigsendi)
```

Format

The format is: table [1:3, 1:3] 682 154 19 33 64 19 25 47 43 - attr(*, "dimnames")=List of 2 ..\$: chr [1:3] "0-49" "50-74" "75-UP" ..\$: chr [1:3] "0-49" "50-74" "75-UP"

Details

Rows represent counts at the beginning, cols represent counts after six months.

Source

Estimation of the transition matrix of a discrete time Markov chain, Bruce A. Craig and Peter P. Sendi, Health Economics 11, 2002.

References

see source

Examples

```
data(craigsendi)
csMc<-as(craigsendi, "markovchain")
steadyStates(csMc)
```

createSequenceMatrix *Function to fit a discrete Markov chain*

Description

Given a sequence of states arising from a stationary state, it fits the underlying Markov chain distribution using either MLE (also using a Laplacian smoother), bootstrap or by MAP (Bayesian) inference.

Usage

```
createSequenceMatrix(
  stringchar,
  toRowProbs = FALSE,
  sanitize = FALSE,
  possibleStates = character()
)

.markovchainFitRcpp(
  data,
  method = "mle",
  byrow = TRUE,
  nboot = 10L,
  laplacian = 0,
  name = "",
  parallel = FALSE,
  confidencelevel = 0.95,
  confint = TRUE,
  hyperparam = matrix(),
  sanitize = FALSE,
  possibleStates = character()
)

markovchainFit(data, method = "mle", byrow = TRUE, nboot = 10L,
  laplacian = 0, name = "", parallel = FALSE, confidencelevel = 0.95,
  confint = TRUE, hyperparam = matrix(), sanitize = FALSE,
  possibleStates = character(), absorbingStates = character())
```

Arguments

stringchar	It can be a	$n \times n$
	matrix or a character vector or a list	
toRowProbs	converts a sequence matrix into a probability matrix	
sanitize	put 1 in all rows having rowSum equal to zero	
possibleStates	Possible states which are not present in the given sequence	

data	It can be a character vector or a $n \times n$ matrix or a $n \times n$ data frame or a list
method	Method used to estimate the Markov chain. Either "mle", "map", "bootstrap" or "laplace"
byrow	it tells whether the output Markov chain should show the transition probabilities by row.
nboot	Number of bootstrap replicates in case "bootstrap" is used.
laplacian	Laplacian smoothing parameter, default zero. It is only used when "laplace" method is chosen.
name	Optional character for name slot.
parallel	Use parallel processing when performing Bootstrap estimates.
confidencelevel	α
confint	level for confidence intervals width. Used only when method equal to "mle".
hyperparam	a boolean to decide whether to compute Confidence Interval or not.
	Hyperparameter matrix for the a priori distribution. If none is provided, default value of 1 is assigned to each parameter. This must be of size $k \times k$ where k is the number of states in the chain and the values should typically be non-negative integers.
absorbingStates	Character vector of states that are known a priori to be absorbing. The corresponding rows are set to the identity row after MLE fitting when byrow = TRUE; the corresponding columns are set to the identity column when byrow = FALSE. The argument is currently supported only for method = "mle".

Details

Disabling confint would lower the computation time on large datasets. If data or stringchar contain NAs, the related NA containing transitions will be ignored.

When absorbingStates is supplied, the declared states must have no observed outgoing transitions. This allows terminal states in censored customer journeys to be represented as absorbing states without adding artificial observations.

Value

A list containing an estimate, log-likelihood, and, when "bootstrap" method is used, a matrix of standards deviations and the bootstrap samples. When the "mle", "bootstrap" or "map" method is used, the lower and upper confidence bounds are returned along with the standard error. The "map" method also returns the expected value of the parameters with respect to the posterior distribution.

Note

This function has been rewritten in Rcpp. Bootstrap algorithm has been defined "heuristically". In addition, parallel facility is not complete, involving only a part of the bootstrap process. When data is either a `data.frame` or a `matrix` object, only MLE fit is currently available.

Author(s)

Giorgio Spedicato, Tae Seung Kang, Sai Bhargav Yalamanchi

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010
 Inferring Markov Chains: Bayesian Estimation, Model Comparison, Entropy Rate, and Out-of-Class Modeling, Christopher C. Strelloff, James P. Crutchfield, Alfred Hubler, Santa Fe Institute
 Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also

[markovchainSequence](#), [markovchainListFit](#)

Examples

```
sequence <- c("a", "b", "a", "a", "a", "a", "b", "a", "b", "a", "b", "a", "a",
             "b", "b", "b", "a")
sequenceMatr <- createSequenceMatrix(sequence, sanitize = FALSE)
mcFitMLE <- markovchainFit(data = sequence)
mcFitBSP <- markovchainFit(data = sequence, method = "bootstrap", nboot = 5, name = "Bootstrap Mc")

na.sequence <- c("a", NA, "a", "b")
# There will be only a (a,b) transition
na.sequenceMatr <- createSequenceMatrix(na.sequence, sanitize = FALSE)
mcFitMLE <- markovchainFit(data = na.sequence)

# data can be a list of character vectors
sequences <- list(x = c("a", "b", "a"), y = c("b", "a", "b", "a", "c"))
mcFitMap <- markovchainFit(sequences, method = "map")
mcFitMle <- markovchainFit(sequences, method = "mle")
```

Description

The S4 class that describes `ctmc` (continuous time Markov chain) objects.

Slots

states Name of the states. Must be the same of colnames and rownames of the generator matrix
byrow TRUE or FALSE. Indicates whether the given matrix is stochastic by rows or by columns
generator Square generator matrix
name Optional character name of the Markov chain

Methods

dim signature(x = "ctmc"): method to get the size
initialize signature(.Object = "ctmc"): initialize method
states signature(object = "ctmc"): states method.
steadyStates signature(object = "ctmc"): method to get the steady state vector.
plot signature(x = "ctmc", y = "missing"): plot method for ctmc objects

Note

1. ctmc classes are written using S4 classes
2. Validation method is used to assess whether either columns or rows totals to zero. Rounding is used up to 5th decimal. If state names are not properly defined for a generator matrix, coercing to ctmc object leads to overriding states name with artificial "s1", "s2", ... sequence

References

Introduction to Stochastic Processes with Applications in the Biosciences (2013), David F. Anderson, University of Wisconsin at Madison. Sai Bhargav Yalamanchi, Giorgio Spedicato

See Also

[generatorToTransitionMatrix,rctmc](#)

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3,
                      1, -1), nrow = 2,
              byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                    byrow = byRow, generator = gen,
                    name = "Molecular Transition Model")
                    steadyStates(molecularCTMC)
## Not run: plot(molecularCTMC)
```

`ctmcFit`*Function to fit a CTMC*

Description

This function fits the underlying CTMC give the state transition data and the transition times using the maximum likelihood method (MLE)

Usage

```
ctmcFit(data, byrow = TRUE, name = "", confidencelevel = 0.95)
```

Arguments

<code>data</code>	It is a list of two elements. The first element is a character vector denoting the states. The second is a numeric vector denoting the corresponding transition times.
<code>byrow</code>	Determines if the output transition probabilities of the underlying embedded DTMC are by row.
<code>name</code>	Optional name for the CTMC.
<code>confidencelevel</code>	Confidence level for the confidence interval construction.

Details

Note that in data, there must exist an element wise corresponding between the two elements of the list and that `data[[2]][1]` is always 0.

Value

It returns a list containing the CTMC object and the confidence intervals.

Author(s)

Sai Bhargav Yalamanchi

References

Continuous Time Markov Chains (vignette), Sai Bhargav Yalamanchi, Giorgio Alfredo Spedicato 2015

See Also

[rctmc](#)

Examples

```
data <- list(c("a", "b", "c", "a", "b", "a", "c", "b", "c"), c(0, 0.8, 2.1, 2.4, 4, 5, 5.9, 8.2, 9))
ctmcFit(data)
```

entropyRate

Entropy rate of a Markov chain

Description

Computes the entropy rate of a finite, irreducible discrete-time Markov chain from its stationary distribution and transition matrix.

Usage

```
entropyRate(object, base = 2)

## S4 method for signature 'markovchain'
entropyRate(object, base = 2)
```

Arguments

object	A markovchain object representing a finite, irreducible discrete-time Markov chain.
base	A finite numeric scalar strictly greater than one. The default, 2, returns entropy in bits per transition. Use exp(1) for nats per transition.

Details

For a row-stochastic transition matrix P and stationary distribution π , the entropy rate is

$$H = - \sum_i \pi_i \sum_j p_{ij} \log_b(p_{ij}),$$

with zero-probability transitions contributing zero by continuity.

For a stationary first-order Markov chain, the entropy rate equals the conditional entropy $H(X_{t+1} | X_t)$. Irreducibility guarantees a unique stationary distribution; aperiodicity is not required.

Reducible chains may admit multiple stationary distributions and therefore different entropy rates. This method rejects them rather than silently selecting one stationary distribution.

Transitions with probability zero are ignored, implementing the standard convention $0 \log(0) = 0$ without evaluating $\log(0)$.

The stationary-distribution computation dominates the running time. Once the stationary distribution is available, evaluating the entropy rate takes $O(n^2)$ time and $O(n^2)$ temporary memory for a dense n -state transition matrix.

Value

A non-negative numeric scalar containing the entropy rate in units determined by base.

References

Cover, T. M. and Thomas, J. A. (2006). *Elements of Information Theory*, 2nd edition. Wiley.

Strelhoff, C. C., Crutchfield, J. P. and Huebler, A. W. (2007). Inferring Markov chains: Bayesian estimation, model comparison, entropy rate, and out-of-class modeling. *Physical Review E*, 76, 011106.

See Also

[steadyStates](#), [is.irreducible](#)

Examples

```
statesNames <- c("a", "b")
mc <- new("markovchain",
  states = statesNames,
  transitionMatrix = matrix(c(0.7, 0.3, 0.1, 0.9),
    byrow = TRUE, nrow = 2,
    dimnames = list(statesNames, statesNames)))
entropyRate(mc)
entropyRate(mc, base = exp(1))
```

expectedRewards

Expected Rewards for a markovchain

Description

Given a markovchain object and reward values for every state, function calculates expected reward value after n steps.

Usage

```
expectedRewards(markovchain,n,rewards)
```

Arguments

markovchain	the markovchain-class object
n	no of steps of the process
rewards	vector depicting rewards coressponding to states

Details

the function uses a dynamic programming approach to solve a recursive equation described in reference.

Value

returns a vector of expected rewards for different initial states

Author(s)

Vandit Jain

References

Stochastic Processes: Theory for Applications, Robert G. Gallager, Cambridge University Press

Examples

```
transMatr<-matrix(c(0.99,0.01,0.01,0.99),nrow=2,byrow=TRUE)
simpleMc<-new("markovchain", states=c("a","b"),
             transitionMatrix=transMatr)
expectedRewards(simpleMc,1,c(0,1))
```

expectedRewardsBeforeHittingA

Expected first passage Rewards for a set of states in a markovchain

Description

Given a markovchain object and reward values for every state, function calculates expected reward value for a set A of states after n steps.

Usage

```
expectedRewardsBeforeHittingA(markovchain, A, state, rewards, n)
```

Arguments

markovchain	the markovchain-class object
A	set of states for first passage expected reward
state	initial state
rewards	vector depicting rewards coressponding to states
n	no of steps of the process

Details

The function returns the value of expected first passage rewards given rewards coressponding to every state, an initial state and number of steps.

Value

returns a expected reward (numerical value) as described above

Author(s)

Sai Bhargav Yalamanchi, Vandit Jain

ExpectedTime	<i>Returns expected hitting time from state i to state j</i>
--------------	--

Description

Returns expected hitting time from state i to state j

Usage

```
ExpectedTime(C,i,j,userCcpp)
```

Arguments

C	A CTMC S4 object
i	Initial state i
j	Final state j
userCcpp	logical whether to use Rcpp

Details

According to the theorem, holding times for all states except j should be greater than 0.

Value

A numerical value that returns expected hitting times from i to j

Author(s)

Vandit Jain

References

Markovchains, J. R. Norris, Cambridge University Press

Examples

```
states <- c("a","b","c","d")
byRow <- TRUE
gen <- matrix(data = c(-1, 1/2, 1/2, 0, 1/4, -1/2, 0, 1/4, 1/6, 0, -1/3, 1/6, 0, 0, 0, 0),
  nrow = 4,byrow = byRow, dimnames = list(states,states))
ctmc <- new("ctmc",states = states, byrow = byRow, generator = gen, name = "testctmc")
ExpectedTime(ctmc,1,4,TRUE)
```

firstPassage	<i>First passage across states</i>
--------------	------------------------------------

Description

This function compute the first passage probability in states

Usage

```
firstPassage(object, state, n)
```

Arguments

object	A markovchain object
state	Initial state
n	Number of rows on which compute the distribution

Details

Based on Feres' Matlab listings

Value

A matrix of size 1:n x number of states showing the probability of the first time of passage in states to be exactly the number in the row.

Author(s)

Giorgio Spedicato

References

Renaldo Feres, Notes for Math 450 Matlab listings for Markov chains

See Also

[conditionalDistribution](#)

Examples

```
simpleMc <- new("markovchain", states = c("a", "b"),  
               transitionMatrix = matrix(c(0.4, 0.6, .3, .7),  
                                         nrow = 2, byrow = TRUE))  
firstPassage(simpleMc, "b", 20)
```

firstPassageMultiple *function to calculate first passage probabilities*

Description

The function calculates first passage probability for a subset of states given an initial state.

Usage

```
firstPassageMultiple(object, state, set, n)
```

Arguments

object	a markovchain-class object
state	intital state of the process (charactervector)
set	set of states A, first passage of which is to be calculated
n	Number of rows on which compute the distribution

Value

A vector of size n showing the first time proabilities

Author(s)

Vandit Jain

References

Renaldo Feres, Notes for Math 450 Matlab listings for Markov chains; MIT OCW, course - 6.262, Discrete Stochastic Processes, course-notes, chap -05

See Also

[firstPassage](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
matrix(c(0.2, 0.5, 0.3,
        0, 1, 0,
        0.1, 0.8, 0.1), nrow = 3, byrow = TRUE,
        dimnames = list(statesNames, statesNames)
))
firstPassageMultiple(markovB,"a",c("b","c"),4)
```

fitHigherOrder

Functions to fit a higher order Markov chain

Description

Given a sequence of states arising from a stationary state, it fits the underlying Markov chain distribution with higher order.

Usage

```
fitHigherOrder(sequence, order = 2)
seq2freqProb(sequence)
seq2matHigh(sequence, order)
```

Arguments

sequence	A character list.
order	Markov chain order

Value

A list containing lambda, Q, and X.

Author(s)

Giorgio Spedicato, Tae Seung Kang

References

Ching, W. K., Huang, X., Ng, M. K., & Siu, T. K. (2013). Higher-order markov chains. In Markov Chains (pp. 141-176). Springer US.

Ching, W. K., Ng, M. K., & Fung, E. S. (2008). Higher-order multivariate Markov chains and their applications. Linear Algebra and its Applications, 428(2), 492-507.

Examples

```
sequence<-c("a", "a", "b", "b", "a", "c", "b", "a", "b", "c", "a", "b",
            "c", "a", "b", "c", "a", "b", "a", "b")
fitHigherOrder(sequence)
```

`fitHighOrderMultivarMC`*Function to fit Higher Order Multivariate Markov chain*

Description

Given a matrix of categorical sequences it fits Higher Order Multivariate Markov chain.

Usage

```
fitHighOrderMultivarMC(seqMat, order = 2, Norm = 2)
```

Arguments

<code>seqMat</code>	a matrix or a data frame where each column is a categorical sequence
<code>order</code>	Multivariate Markov chain order. Default is 2.
<code>Norm</code>	Norm to be used. Default is 2.

Value

an hommc object

Author(s)

Giorgio Spedicato, Deepak Yadav

References

W.-K. Ching et al. / Linear Algebra and its Applications

Examples

```
data <- matrix(c('2', '1', '3', '3', '4', '3', '2', '1', '3', '3', '2', '1',  
                 '2', '4', '4', '4', '4', '2', '3', '3', '1', '4', '3', '3'),  
              ncol = 2, byrow = FALSE)  
  
fitHighOrderMultivarMC(data, order = 2, Norm = 2)
```

freq2Generator

Returns a generator matrix corresponding to frequency matrix

Description

The function provides interface to calculate generator matrix corresponding to a frequency matrix and time taken

Usage

```
freq2Generator(P, t = 1, method = "QO", logmethod = "Eigen")
```

Arguments

P	relative frequency matrix
t	(default value = 1)
method	one among "QO"(Quasi optimaisation), "WA"(weighted adjustment), "DA"(diagonal adjustment)
logmethod	method for computation of matrix algorithm (by default : Eigen)

Value

returns a generator matrix with same dimnames

References

E. Kreinin and M. Sidelnikova: Regularization Algorithms for Transition Matrices. Algo Research Quarterly 4(1):23-40, 2001

Examples

```
sample <- matrix(c(150,2,1,1,1,200,2,1,2,1,175,1,1,1,1,150),nrow = 4,byrow = TRUE)
sample_rel = rbind((sample/rowSums(sample))[1:dim(sample)[1]-1,],c(rep(0,dim(sample)[1]-1),1))
freq2Generator(sample_rel,1)

data(tm_abs)
tm_rel=rbind((tm_abs/rowSums(tm_abs))[1:7,],c(rep(0,7),1))
## Derive quasi optimization generator matrix estimate
freq2Generator(tm_rel,1)
```

fundamentalMatrix	<i>Fundamental matrix of an absorbing Markov chain</i>
-------------------	--

Description

Computes the fundamental matrix of a finite absorbing discrete-time Markov chain. If Q is the transition submatrix restricted to transient states, the fundamental matrix is

$$N = I + Q + Q^2 + \cdots = (I - Q)^{-1}.$$

The (i, j) entry is the expected number of visits to transient state j , including the initial visit when $i = j$, before absorption, when the chain starts in transient state i .

Usage

```
fundamentalMatrix(object)
```

Arguments

object A markovchain object representing an absorbing Markov chain.

Details

For a finite absorbing chain, the state space can be reordered so that the transition matrix has canonical form with transient block Q and an absorbing block. The spectral radius of Q is less than one, so the Neumann series converges and $I - Q$ is nonsingular.

The fundamental matrix also gives the expected time to absorption through $t = N1$, where 1 is a vector of ones, and absorption probabilities through $B = NR$, where R contains transition probabilities from transient to absorbing states.

The function requires an absorbing Markov chain: at least one absorbing state must exist and every recurrent state must be absorbing. A chain with no transient states is a valid degenerate case and returns a 0-by-0 matrix.

Value

A numeric matrix containing the fundamental matrix, with transient state names as row and column names. If all states are absorbing, the result is a 0-by-0 matrix because there are no transient states.

References

Kemeny, J. G. and Snell, J. L. (1976). **Finite Markov Chains**. Springer.

Grinstead, C. M. and Snell, J. L. (1997). **Introduction to Probability**. American Mathematical Society.

See Also

[absorbingStates](#), [transientStates](#), [meanAbsorptionTime](#), [absorptionProbabilities](#)

Examples

```

states <- c("a", "b", "absorbed")
mc <- new("markovchain", states = states,
  transitionMatrix = matrix(c(
    0.5, 0.4, 0.1,
    0.2, 0.6, 0.2,
    0, 0, 1
  ), nrow = 3, byrow = TRUE,
  dimnames = list(states, states)))

fundamentalMatrix(mc)

```

generatorToTransitionMatrix

Function to obtain the transition matrix from the generator

Description

The transition matrix of the embedded DTMC is inferred from the CTMC's generator

Usage

```
generatorToTransitionMatrix(gen, byrow = TRUE)
```

Arguments

gen	The generator matrix
byrow	Flag to determine if rows (columns) sum to 0

Value

Returns the transition matrix.

Author(s)

Sai Bhargav Yalamanchi

References

Introduction to Stochastic Processes with Applications in the Biosciences (2013), David F. Anderson, University of Wisconsin at Madison

See Also

[rctmc,ctmc-class](#)

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3, 1, -1), nrow = 2,
              byrow = byRow, dimnames = list(energyStates, energyStates))
generatorToTransitionMatrix(gen)
```

HigherOrderMarkovChain-class

Higher order Markov Chains class

Description

The S4 class that describes HigherOrderMarkovChain objects.

hittingProbabilities *Hitting probabilities for markovchain*

Description

Given a markovchain object, this function calculates the probability of ever arriving from state i to j

Usage

```
hittingProbabilities(object)
```

Arguments

object the markovchain-class object

Value

a matrix of hitting probabilities

Author(s)

Ignacio Cordón

References

R. Vélez, T. Prieto, Procesos Estocásticos, Librería UNED, 2013

Examples

```

M <- markovchain::zeros(5)
M[1,1] <- M[5,5] <- 1
M[2,1] <- M[2,3] <- 1/2
M[3,2] <- M[3,4] <- 1/2
M[4,2] <- M[4,5] <- 1/2

mc <- new("markovchain", transitionMatrix = M)
hittingProbabilities(mc)

```

holson

Holson data set

Description

A data set containing 1000 life histories trajectories and a categorical status (1,2,3) observed on eleven evenly spaced steps.

Usage

```
data(holson)
```

Format

A data frame with 1000 observations on the following 12 variables.

```

id unique id
time1 observed status at i-th time
time2 observed status at i-th time
time3 observed status at i-th time
time4 observed status at i-th time
time5 observed status at i-th time
time6 observed status at i-th time
time7 observed status at i-th time
time8 observed status at i-th time
time9 observed status at i-th time
time10 observed status at i-th time
time11 observed status at i-th time

```

Details

The example can be used to fit a markovchain or a markovchainList object.

Source

Private communications

References

Private communications

Examples

```
data(holson)
head(holson)
```

hommc-class	<i>An S4 class for representing High Order Multivariate Markovchain (HOMMC)</i>
-------------	---

Description

An S4 class for representing High Order Multivariate Markovchain (HOMMC)

Usage

```
hommc
```

Slots

order an integer equal to order of Multivariate Markovchain
 states a vector of states present in the HOMMC model
 P array of transition matrices
 Lambda a vector which stores the weightage of each transition matrices in P
 byrow if FALSE each column sum of transition matrix is 1 else row sum = 1
 name a name given to hommc

Author(s)

Giorgio Spedicato, Deepak Yadav

Examples

```
statesName <- c("a", "b")

P <- array(0, dim = c(2, 2, 4), dimnames = list(statesName, statesName))
P[,1] <- matrix(c(0, 1, 1/3, 2/3), byrow = FALSE, nrow = 2)
P[,2] <- matrix(c(1/4, 3/4, 0, 1), byrow = FALSE, nrow = 2)
P[,3] <- matrix(c(1, 0, 1/3, 2/3), byrow = FALSE, nrow = 2)
P[,4] <- matrix(c(3/4, 1/4, 0, 1), byrow = FALSE, nrow = 2)
```

```
Lambda <- c(0.8, 0.2, 0.3, 0.7)

ob <- new("hommc", order = 1, states = statesName, P = P,
          Lambda = Lambda, byrow = FALSE, name = "FOMMC")
```

ictmc-class	<i>An S4 class for representing Imprecise Continuous Time Markovchains</i>
-------------	--

Description

An S4 class for representing Imprecise Continuous Time Markovchains

Slots

states a vector of states present in the ICTMC model
 Q matrix representing the generator demonstrated in the form of variables
 range a matrix that stores values of range of variables
 name name given to ICTMC

impreciseProbabilityatT	<i>Calculating full conditional probability using lower rate transition matrix</i>
-------------------------	--

Description

This function calculates full conditional probability at given time s using lower rate transition matrix

Usage

```
impreciseProbabilityatT(C,i,t,s,error,useRCpp)
```

Arguments

C	a ictmc class object
i	initial state at time t
t	initial time t. Default value = 0
s	final time
error	error rate. Default value = 0.001
useRCpp	logical whether to use RCpp implementation; by default TRUE

Author(s)

Vandit Jain

References

Imprecise Continuous-Time Markov Chains, Thomas Krak et al., 2016

Examples

```

states <- c("n", "y")
Q <- matrix(c(-1, 1, 1, -1), nrow = 2, byrow = TRUE, dimnames = list(states, states))
range <- matrix(c(1/52, 3/52, 1/2, 2), nrow = 2, byrow = 2)
name <- "testictmc"
ictmc <- new("ictmc", states = states, Q = Q, range = range, name = name)
impreciseProbabilityatT(ictmc, 2, 0, 1, 10^-3, TRUE)

```

inferHyperparam	<i>Function to infer the hyperparameters for Bayesian inference from an a priori matrix or a data set</i>
-----------------	---

Description

Since the Bayesian inference approach implemented in the package is based on conjugate priors, hyperparameters must be provided to model the prior probability distribution of the chain parameters. The hyperparameters are inferred from a given a priori matrix under the assumption that the matrix provided corresponds to the mean (expected) values of the chain parameters. A scaling factor vector must be provided too. Alternatively, the hyperparameters can be inferred from a data set.

Usage

```
inferHyperparam(transMatr = matrix(), scale = numeric(), data = character())
```

Arguments

transMatr	A valid transition matrix, with dimension names.
scale	A vector of scaling factors, each element corresponds to the row names of the provided transition matrix transMatr, in the same order.
data	A data set from which the hyperparameters are inferred.

Details

transMatr and scale need not be provided if data is provided.

Value

Returns the hyperparameter matrix in a list.

Note

The hyperparameter matrix returned is such that the row and column names are sorted alphanumerically, and the elements in the matrix are correspondingly permuted.

Author(s)

Sai Bhargav Yalamanchi, Giorgio Spedicato

References

Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also

[markovchainFit](#), [predictiveDistribution](#)

Examples

```
data(rain, package = "markovchain")
inferHyperparam(data = rain$rain)

weatherStates <- c("sunny", "cloudy", "rain")
weatherMatrix <- matrix(data = c(0.7, 0.2, 0.1,
                                0.3, 0.4, 0.3,
                                0.2, 0.4, 0.4),
                        byrow = TRUE, nrow = 3,
                        dimnames = list(weatherStates, weatherStates))
inferHyperparam(transMatr = weatherMatrix, scale = c(10, 10, 10))
```

is.accessible

Verify if a state j is reachable from state i.

Description

This function verifies if a state is reachable from another, i.e., if there exists a path that leads to state j leaving from state i with positive probability

Usage

```
is.accessible(object, from, to)
```

Arguments

object	A markovchain object.
from	The name of state "i" (beginning state).
to	The name of state "j" (ending state).

Details

It wraps an internal function named `reachabilityMatrix`.

Value

A boolean value.

Author(s)

Giorgio Spedicato, Ignacio Cordon

References

James Montgomery, University of Madison

See Also

`is.irreducible`

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames,
               transitionMatrix = matrix(c(0.2, 0.5, 0.3,
                                           0, 1, 0,
                                           0.1, 0.8, 0.1), nrow = 3, byrow = TRUE,
                                           dimnames = list(statesNames, statesNames)
               )
is.accessible(markovB, "a", "c")
```

is.CTMCirreducible	<i>Check if CTMC is irreducible</i>
--------------------	-------------------------------------

Description

This function verifies whether a CTMC object is irreducible

Usage

```
is.CTMCirreducible(ctmc)
```

Arguments

ctmc a ctmc-class object

Value

a boolean value as described above.

Author(s)

Vandit Jain

References

Continuous-Time Markov Chains, Karl Sigman, Columbia University

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3,
                      1, -1), nrow = 2,
              byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                    byrow = byRow, generator = gen,
                    name = "Molecular Transition Model")
is.CTMCirreducible(molecularCTMC)
```

is.irreducible

Function to check if a Markov chain is irreducible (i.e. ergodic)

Description

This function verifies whether a markovchain object transition matrix is composed by only one communicating class.

Usage

```
is.irreducible(object)
```

Arguments

object A markovchain object

Details

It is based on .communicatingClasses internal function.

Value

A boolean values.

Author(s)

Giorgio Spedicato

References

Feres, Matlab listings for Markov Chains.

See Also

[summary](#)

Examples

```
statesNames <- c("a", "b")
mcA <- new("markovchain", transitionMatrix = matrix(c(0.7,0.3,0.1,0.9),
                                                    byrow = TRUE, nrow = 2,
                                                    dimnames = list(statesNames, statesNames)
                                                    ))
is.irreducible(mcA)
```

is.lumpable

Check exact lumpability of a Markov chain

Description

Verifies the strong lumpability condition with respect to a partition of the state space. For every pair of macro-states, all micro-states in the same source macro-state must have the same total probability of moving to the destination macro-state.

Usage

```
is.lumpable(object, partition, tol = 1e-10)
```

```
## S4 method for signature 'markovchain'
is.lumpable(object, partition, tol = 1e-10)
```

Arguments

object	A markovchain object.
partition	A named list of character vectors defining macro-states.
tol	Non-negative numerical tolerance for equality checks.

Value

A logical value.

References

Kemeny, J. G. and Snell, J. L. (1960). *Finite Markov Chains*.

is.regular	<i>Check if a DTMC is regular</i>
------------	-----------------------------------

Description

Function to check whether a DTMC is regular

Usage

```
is.regular(object)
```

Arguments

object a markovchain object

Details

A Markov chain is regular if some of the powers of its matrix has all elements strictly positive

Value

A boolean value

Author(s)

Ignacio Córdón

References

Matrix Analysis. Roger A.Horn, Charles R.Johnson. 2nd edition. Corollary 8.5.8, Theorem 8.5.9

See Also

[is.irreducible](#)

Examples

```
P <- matrix(c(0.5, 0.25, 0.25,
              0.5, 0, 0.5,
              0.25, 0.25, 0.5), nrow = 3)
colnames(P) <- rownames(P) <- c("R", "N", "S")
ciao <- as(P, "markovchain")
is.regular(ciao)
```

is.stochasticallyMonotone

Check if a Markov chain is stochastically monotone

Description

Verifies if the transition matrix of the Markov chain is stochastically monotone.

Usage

```
is.stochasticallyMonotone(object)
```

```
## S4 method for signature 'markovchain'
is.stochasticallyMonotone(object)
```

```
## S4 method for signature 'matrix'
is.stochasticallyMonotone(object)
```

```
## S4 method for signature 'ANY'
is.stochasticallyMonotone(object)
```

Arguments

object A markovchain object or a transition matrix.

Value

A boolean value.

is.TimeReversible

checks if ctmc object is time reversible

Description

The function returns checks if provided function is time reversible

Usage

```
is.TimeReversible(ctmc)
```

Arguments

ctmc a ctmc-class object

Value

Returns a boolean value stating whether ctmc object is time reversible
 a boolean value as described above

Author(s)

Vandit Jain

References

INTRODUCTION TO STOCHASTIC PROCESSES WITH R, ROBERT P. DOBROW, Wiley

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3,
                      1, -1), nrow = 2,
              byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                    byrow = byRow, generator = gen,
                    name = "Molecular Transition Model")
is.TimeReversible(molecularCTMC)
```

kemenyConstant	<i>Kemeny's constant of a Markov chain</i>
----------------	--

Description

Computes Kemeny's constant for a finite, irreducible discrete-time Markov chain. It is the stationary-distribution-weighted mean hitting time of a randomly selected destination and is independent of the starting state.

Usage

```
kemenyConstant(object)

## S4 method for signature 'markovchain'
kemenyConstant(object)
```

Arguments

object	A markovchain object representing a finite, irreducible discrete-time Markov chain.
--------	---

Details

For a row-stochastic transition matrix P , let π be its unique stationary distribution and define

$$Z = (I - P + \mathbf{1}\pi^T)^{-1}.$$

With hitting times defined by $T_j = \inf\{n \geq 0 : X_n = j\}$, so that $m_{jj} = 0$, the function returns

$$K = \sum_j \pi_j m_{ij} = \text{tr}(Z) - 1.$$

The value does not depend on the starting state i .

Irreducibility is sufficient; aperiodicity is not required. Reducible chains can have multiple stationary distributions and are rejected.

Some references instead put the mean first-return time $m_{jj} = 1/\pi_j$ on the diagonal. Under that convention the corresponding stationary weighted sum is $K + 1$, not K . This function uses the zero-diagonal hitting-time convention, consistently with `meanFirstPassageTime()`.

The implementation uses a dense LAPACK solve for the fundamental matrix Z . Its time complexity is $O(n^3)$ and its memory use is $O(n^2)$, as expected for a dense exact computation. It supports both row- and column-stochastic storage.

Value

A numeric scalar containing Kemeny's constant.

References

Kemeny, J. G. and Snell, J. L. (1960). *Finite Markov Chains*. D. Van Nostrand, Princeton, NJ.

See Also

[meanFirstPassageTime](#), [steadyStates](#), [is.irreducible](#)

Examples

```
statesNames <- c("a", "b")
mc <- new("markovchain",
  states = statesNames,
  transitionMatrix = matrix(c(0.7, 0.3, 0.1, 0.9),
    byrow = TRUE, nrow = 2,
    dimnames = list(statesNames, statesNames)))
kemenyConstant(mc)
```

kullback

Example from Kullback and Kupperman Tests for Contingency Tables

Description

A list of two matrices representing raw transitions between two states

Usage

```
data(kullback)
```

Format

A list containing two 6x6 non - negative integer matrices

lump

Aggregate a Markov chain over a partition

Description

Coarsens a Markov chain to a reduced state space. By default the function requires exact lumpability. With `force = TRUE`, it performs an approximate aggregation using stationary weights when available and arithmetic averages for macro-states with zero stationary mass.

Usage

```
lump(object, partition, force = FALSE)
```

```
## S4 method for signature 'markovchain'
lump(object, partition, force = FALSE)
```

Arguments

object	A markovchain object.
partition	A named list of character vectors defining macro-states.
force	If FALSE, stop unless the chain is exactly lumpable. If TRUE, return a weighted approximate lumping.

Value

A markovchain object on the macro-state space.

markovchain-class	<i>Markov Chain class</i>
-------------------	---------------------------

Description

The S4 class that describes markovchain objects.

Slots

states Name of the states. Must be the same of colnames and rownames of the transition matrix
byrow TRUE or FALSE indicating whether the supplied matrix is either stochastic by rows or by columns

transitionMatrix Square transition matrix

name Optional character name of the Markov chain

Creation of objects

Objects can be created by calls of the form `new("markovchain", states, byrow, transitionMatrix, ...)`.

Methods

* `signature(e1 = "markovchain", e2 = "markovchain")`: multiply two markovchain objects

* `signature(e1 = "markovchain", e2 = "matrix")`: markovchain by matrix multiplication

* `signature(e1 = "markovchain", e2 = "numeric")`: markovchain by numeric vector multiplication

* `signature(e1 = "matrix", e2 = "markovchain")`: matrix by markov chain

* `signature(e1 = "numeric", e2 = "markovchain")`: numeric vector by markovchain multiplication

[`signature(x = "markovchain", i = "ANY", j = "ANY", drop = "ANY")`: ...

^ `signature(e1 = "markovchain", e2 = "numeric")`: power of a markovchain object

== `signature(e1 = "markovchain", e2 = "markovchain")`: equality of two markovchain object

!= `signature(e1 = "markovchain", e2 = "markovchain")`: non-equality of two markovchain object

absorbingStates `signature(object = "markovchain")`: method to get absorbing states

canonicForm `signature(object = "markovchain")`: return a markovchain object into canonic form

coerce `signature(from = "markovchain", to = "data.frame")`: coerce method from markovchain to data.frame

conditionalDistribution `signature(object = "markovchain")`: returns the conditional probability of subsequent states given a state

coerce signature(from = "data.frame", to = "markovchain"): coerce method from data.frame to markovchain

coerce signature(from = "table", to = "markovchain"): coerce method from table to markovchain

coerce signature(from = "msm", to = "markovchain"): coerce method from msm to markovchain

coerce signature(from = "msm.est", to = "markovchain"): coerce method from msm.est (but only from a Probability Matrix) to markovchain

coerce signature(from = "etm", to = "markovchain"): coerce method from etm to markovchain

coerce signature(from = "sparseMatrix", to = "markovchain"): coerce method from sparseMatrix to markovchain

coerce signature(from = "markovchain", to = "igraph"): coercing to igraph objects

coerce signature(from = "markovchain", to = "matrix"): coercing to matrix objects

coerce signature(from = "markovchain", to = "sparseMatrix"): coercing to sparseMatrix objects

coerce signature(from = "matrix", to = "markovchain"): coercing to markovchain objects from matrix one

dim signature(x = "markovchain"): method to get the size

names signature(x = "markovchain"): method to get the names of states

names<- signature(x = "markovchain", value = "character"): method to set the names of states

initialize signature(.Object = "markovchain"): initialize method

plot signature(x = "markovchain", y = "missing"): plot method for markovchain objects

predict signature(object = "markovchain"): predict method

print signature(x = "markovchain"): print method.

show signature(object = "markovchain"): show method.

sort signature(x = "markovchain", decreasing=FALSE): sorting the transition matrix.

states signature(object = "markovchain"): returns the names of states (as names).

steadyStates signature(object = "markovchain"): method to get the steady vector.

summary signature(object = "markovchain"): method to summarize structure of the markov chain

transientStates signature(object = "markovchain"): method to get the transient states.

t signature(x = "markovchain"): transpose matrix

transitionProbability signature(object = "markovchain"): transition probability

Note

1. markovchain object are backed by S4 Classes.
2. Validation method is used to assess whether either columns or rows totals to one. Rounding is used up to $.Machine$double.eps * 100$. If state names are not properly defined for a probability matrix, coercing to markovchain object leads to overriding states name with artificial "s1", "s2", ... sequence. In addition, operator overloading has been applied for +, *, '==', '!=' operators.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchainSequence](#), [markovchainFit](#)

Examples

```
#show markovchain definition
showClass("markovchain")
#create a simple Markov chain
transMatr<-matrix(c(0.4,0.6,.3,.7),nrow=2,byrow=TRUE)
simpleMc<-new("markovchain", states=c("a","b"),
             transitionMatrix=transMatr,
             name="simpleMc")

#power
simpleMc^4
#some methods
steadyStates(simpleMc)
absorbingStates(simpleMc)
simpleMc[2,1]
t(simpleMc)
is.irreducible(simpleMc)
#conditional distributions
conditionalDistribution(simpleMc, "b")
#example for predict method
sequence<-c("a", "b", "a", "a", "a", "a", "b", "a", "b", "a", "b", "a", "a", "b", "b", "b", "a")
mcFit<-markovchainFit(data=sequence)
predict(mcFit$estimate, newdata="b",n.ahead=3)
#direct conversion
myMc<-as(transMatr, "markovchain")

#example of summary
summary(simpleMc)
## Not run: plot(simpleMc)
```

markovchainList-class *Non homogeneous discrete time Markov Chains class*

Description

A class to handle non homogeneous discrete Markov chains

Slots

markovchains Object of class "list": a list of markovchains

name Object of class "character": optional name of the class

Objects from the Class

A markovchainlist is a list of markovchain objects. They can be used to model non homogeneous discrete time Markov Chains, when transition probabilities (and possible states) change by time.

Methods

[[signature(x = "markovchainList"): extract the i-th markovchain

dim signature(x = "markovchainList"): number of markovchain underlying the matrix

predict signature(object = "markovchainList"): predict from a markovchainList

print signature(x = "markovchainList"): prints the list of markovchains

show signature(object = "markovchainList"): same as print

Note

The class consists in a list of markovchain objects. It is aimed at working with non homogeneous Markov chains.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchain](#)

Examples

```
showClass("markovchainList")
#define a markovchainList
statesNames=c("a","b")

mcA<-new("markovchain",name="MCA",
        transitionMatrix=matrix(c(0.7,0.3,0.1,0.9),
                                byrow=TRUE, nrow=2,
                                dimnames=list(statesNames,statesNames))
        )

mcB<-new("markovchain", states=c("a","b","c"), name="MCB",
        transitionMatrix=matrix(c(0.2,0.5,0.3,0,1,0,0.1,0.8,0.1),
                                nrow=3, byrow=TRUE))
```

```

mcC<-new("markovchain", states=c("a","b","c","d"), name="MCC",
        transitionMatrix=matrix(c(0.25,0.75,0,0,0.4,0.6,
                                   0,0,0,0,0.1,0.9,0,0,0.7,0.3),
                                nrow=4, byrow=TRUE)
)
mcList<-new("markovchainList",markovchains=list(mcA, mcB, mcC),
           name="Non - homogeneous Markov Chain")

```

markovchainListFit	<i>markovchainListFit</i>
--------------------	---------------------------

Description

Given a data frame or a matrix (rows are observations, by cols the temporal sequence), it fits a non-homogeneous discrete time markov chain process (storing row). In particular a markovchainList of size = ncol - 1 is obtained estimating transitions from the n samples given by consecutive column pairs.

Usage

```
markovchainListFit(data, byrow = TRUE, laplacian = 0, name)
```

Arguments

data	Either a matrix or a data.frame or a list object.
byrow	Indicates whether distinct stochastic processes trajectories are shown in distinct rows.
laplacian	Laplacian correction (default 0).
name	Optional name.

Details

If data contains NAs then the transitions containing NA will be ignored.

Value

A list containing two slots: estimate (the estimate) name

Examples

```

# using holson dataset
data(holson)
# fitting a single markovchain
singleMc <- markovchainFit(data = holson[,2:12])
# fitting a markovchainList
mcListFit <- markovchainListFit(data = holson[, 2:12], name = "holsonMcList")

```

markovchainSequence	<i>Function to generate a sequence of states from homogeneous Markov chains.</i>
---------------------	--

Description

Provided any markovchain object, it returns a sequence of states coming from the underlying stationary distribution.

Usage

```
markovchainSequence(  
  n,  
  markovchain,  
  t0 = sample(markovchain@states, 1),  
  include.t0 = FALSE,  
  useRCpp = TRUE  
)
```

Arguments

n	Sample size
markovchain	markovchain object
t0	The initial state
include.t0	Specify if the initial state shall be used
useRCpp	Boolean. Should RCpp fast implementation being used? Default is yes.

Details

A sequence of size n is sampled.

Value

A Character Vector

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchainFit](#)

Examples

```
# define the markovchain object
statesNames <- c("a", "b", "c")
mcB <- new("markovchain", states = statesNames,
  transitionMatrix = matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1),
    nrow = 3, byrow = TRUE, dimnames = list(statesNames, statesNames)))

# show the sequence
outs <- markovchainSequence(n = 100, markovchain = mcB, t0 = "a")
```

meanAbsorptionTime	<i>Mean absorption time</i>
--------------------	-----------------------------

Description

Computes the expected number of steps to go from any of the transient states to any of the recurrent states. The Markov chain should have at least one transient state for this method to work

Usage

```
meanAbsorptionTime(object)
```

Arguments

object the markovchain object

Value

A named vector with the expected number of steps to go from a transient state to any of the recurrent ones

Author(s)

Ignacio Cordón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```
m <- matrix(c(1/2, 1/2, 0,
  1/2, 1/2, 0,
  0, 1/2, 1/2), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = letters[1:3], transitionMatrix = m)
times <- meanAbsorptionTime(mc)
```

meanFirstPassageTime *Mean First Passage Time for irreducible Markov chains*

Description

Given an irreducible (ergodic) markovchain object, this function calculates the expected number of steps to reach other states

Usage

```
meanFirstPassageTime(object, destination)
```

Arguments

object	the markovchain object
destination	a character vector representing the states respect to which we want to compute the mean first passage time. Empty by default

Details

For an ergodic Markov chain it computes:

- If destination is empty, the average first time (in steps) that takes the Markov chain to go from initial state i to j . (i, j) represents that value in case the Markov chain is given row-wise, (j, i) in case it is given col-wise.
- If destination is not empty, the average time it takes us from the remaining states to reach the states in destination

Value

a Matrix of the same size with the average first passage times if destination is empty, a vector if destination is not

Author(s)

Toni Giorgino, Ignacio Cordón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```

m <- matrix(1 / 10 * c(6,3,1,
                      2,3,5,
                      4,1,5), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = c("s","c","r"), transitionMatrix = m)
meanFirstPassageTime(mc, "r")

# Grinstead and Snell's "Oz weather" worked out example
mOz <- matrix(c(2,1,1,
                2,0,2,
                1,1,2)/4, ncol = 3, byrow = TRUE)

mcOz <- new("markovchain", states = c("s", "c", "r"), transitionMatrix = mOz)
meanFirstPassageTime(mcOz)

```

meanNumVisits	<i>Mean num of visits for markovchain, starting at each state</i>
---------------	---

Description

Given a markovchain object, this function calculates a matrix where the element (i, j) represents the expect number of visits to the state j if the chain starts at i (in a Markov chain by columns it would be the element (j, i) instead)

Usage

```
meanNumVisits(object)
```

Arguments

object	the markovchain-class object
--------	------------------------------

Value

a matrix with the expect number of visits to each state

Author(s)

Ignacio Córdón

References

R. Vélez, T. Prieto, Procesos Estocásticos, Librería UNED, 2013

Examples

```

M <- markovchain::zeros(5)
M[1,1] <- M[5,5] <- 1
M[2,1] <- M[2,3] <- 1/2
M[3,2] <- M[3,4] <- 1/2
M[4,2] <- M[4,5] <- 1/2

mc <- new("markovchain", transitionMatrix = M)
meanNumVisits(mc)

```

meanRecurrenceTime	<i>Mean recurrence time</i>
--------------------	-----------------------------

Description

Computes the expected time to return to a recurrent state in case the Markov chain starts there

Usage

```
meanRecurrenceTime(object)
```

Arguments

object the markovchain object

Value

For a Markov chain it outputs is a named vector with the expected time to first return to a state when the chain starts there. States present in the vector are only the recurrent ones. If the matrix is ergodic (i.e. irreducible), then all states are present in the output and order is the same as states order for the Markov chain

Author(s)

Ignacio Córdón

References

C. M. Grinstead and J. L. Snell. Introduction to Probability. American Mathematical Soc., 2012.

Examples

```

m <- matrix(1 / 10 * c(6,3,1,
                      2,3,5,
                      4,1,5), ncol = 3, byrow = TRUE)
mc <- new("markovchain", states = c("s","c","r"), transitionMatrix = m)
meanRecurrenceTime(mc)

```

`multinomialConfidenceIntervals`*A function to compute multinomial confidence intervals of DTMC*

Description

Return estimated transition matrix assuming a Multinomial Distribution

Usage

```
multinomialConfidenceIntervals(  
  transitionMatrix,  
  countsTransitionMatrix,  
  confidencelevel = 0.95  
)
```

Arguments

`transitionMatrix`
An estimated transition matrix.

`countsTransitionMatrix`
Empirical (counts) transition matrix, on which the `transitionMatrix` was performed.

`confidencelevel`
confidence interval level.

Value

Two matrices containing the confidence intervals.

References

Constructing two-sided simultaneous confidence intervals for multinomial proportions for small counts in a large number of cells. Journal of Statistical Software 5(6) (2000)

See Also

`markovchainFit`

Examples

```
seq<-c("a", "b", "a", "a", "a", "a", "b", "a", "b", "a", "b", "a", "a", "b", "b", "b", "a")  
mcf<-markovchainFit(data=seq,byrow=TRUE)  
seqmat<-createSequenceMatrix(seq)  
multinomialConfidenceIntervals(mcf$estimate@transitionMatrix, seqmat, 0.95)
```

name	<i>Method to retrieve name of markovchain object</i>
------	--

Description

This method returns the name of a markovchain object

Usage

```
name(object)

## S4 method for signature 'markovchain'
name(object)
```

Arguments

object A markovchain object

Author(s)

Giorgio Spedicato, Deepak Yadav

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
name(markovB)
```

name<-	<i>Method to set name of markovchain object</i>
--------	---

Description

This method modifies the existing name of markovchain object

Usage

```
name(object) <- value

## S4 replacement method for signature 'markovchain'
name(object) <- value
```

Arguments

object	A markovchain object
value	New name of markovchain object

Author(s)

Giorgio Spedicato, Deepak Yadav

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
    byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
name(markovB) <- "dangerous mc"
```

names,markovchain-method

Returns the states for a Markov chain object

Description

Returns the states for a Markov chain object

Usage

```
## S4 method for signature 'markovchain'
names(x)
```

Arguments

x	object we want to return states for
---	-------------------------------------

noofVisitsDist	<i>return a joint pdf of the number of visits to the various states of the DTMC</i>
----------------	---

Description

This function would return a joint pdf of the number of visits to the various states of the DTMC during the first N steps.

Usage

```
noofVisitsDist(markovchain,N,state)
```

Arguments

markovchain	a markovchain-class object
N	no of steps
state	the initial state

Details

This function would return a joint pdf of the number of visits to the various states of the DTMC during the first N steps.

Value

a numeric vector depicting the above described probability density function.

Author(s)

Vandit Jain

Examples

```
transMatr<-matrix(c(0.4,0.6,.3,.7),nrow=2,byrow=TRUE)
simpleMc<-new("markovchain", states=c("a","b"),
             transitionMatrix=transMatr,
             name="simpleMc")
noofVisitsDist(simpleMc,5,"a")
```

ones	Returns an Identity matrix
------	----------------------------

Description

Returns an Identity matrix

Usage

ones(n)

Arguments

n size of the matrix

Value

a identity matrix

period	Various function to perform structural analysis of DTMC
--------	---

Description

These functions return absorbing and transient states of the markovchain objects.

Usage

- period(object)
- communicatingClasses(object)
- recurrentClasses(object)
- transientClasses(object)
- transientStates(object)
- recurrentStates(object)
- absorbingStates(object)
- canonicForm(object)

Arguments

object A markovchain object.

Value

`period` returns a integer number corresponding to the periodicity of the Markov chain (if it is irreducible)

`absorbingStates` returns a character vector with the names of the absorbing states in the Markov chain

`communicatingClasses` returns a list in which each slot contains the names of the states that are in that communicating class

`recurrentClasses` analogously to `communicatingClasses`, but with recurrent classes

`transientClasses` analogously to `communicatingClasses`, but with transient classes

`transientStates` returns a character vector with all the transient states for the Markov chain

`recurrentStates` returns a character vector with all the recurrent states for the Markov chain

`canonicForm` returns the Markov chain reordered by a permutation of states so that we have blocks submatrices for each of the recurrent classes and a collection of rows in the end for the transient states

Author(s)

Giorgio Alfredo Spedicato, Ignacio Cordón

References

Feres, Matlab listing for markov chain.

See Also

[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
mc <- new("markovchain", states = statesNames, transitionMatrix =
      matrix(c(0.2, 0.5, 0.3,
               0, 1, 0,
               0.1, 0.8, 0.1), nrow = 3, byrow = TRUE,
            dimnames = list(statesNames, statesNames))
)

communicatingClasses(mc)
recurrentClasses(mc)
recurrentClasses(mc)
absorbingStates(mc)
transientStates(mc)
recurrentStates(mc)
canonicForm(mc)
```

```

# periodicity analysis
A <- matrix(c(0, 1, 0, 0, 0.5, 0, 0.5, 0, 0, 0.5, 0, 0.5, 0, 0, 1, 0),
            nrow = 4, ncol = 4, byrow = TRUE)
mcA <- new("markovchain", states = c("a", "b", "c", "d"),
           transitionMatrix = A,
           name = "A")

is.irreducible(mcA) #true
period(mcA) #2

# periodicity analysis
B <- matrix(c(0, 0, 1/2, 1/4, 1/4, 0, 0,
              0, 0, 1/3, 0, 2/3, 0, 0,
              0, 0, 0, 0, 0, 1/3, 2/3,
              0, 0, 0, 0, 0, 1/2, 1/2,
              0, 0, 0, 0, 0, 3/4, 1/4,
              1/2, 1/2, 0, 0, 0, 0, 0,
              1/4, 3/4, 0, 0, 0, 0, 0), byrow = TRUE, ncol = 7)
mcB <- new("markovchain", transitionMatrix = B)
period(mcB)

```

predictHommc

Simulate a higher order multivariate markovchain

Description

This function provides a prediction of states for a higher order multivariate markovchain object

Usage

```
predictHommc(hommc,t,init)
```

Arguments

hommc	a hommc-class object
t	no of iterations to predict
init	matrix of previous states size of which depends on hommc

Details

The user is required to provide a matrix of giving n previous coressponding every categorical sequence. Dimensions of the init are s X n, where s is number of categorical sequences and n is order of the homc.

Value

The function returns a matrix of size s X t displaying t predicted states in each row coressponding to every categorical sequence.

Author(s)

Vandit Jain

`predictiveDistribution`*predictiveDistribution*

Description

The function computes the probability of observing a new data set, given a data set

Usage

```
predictiveDistribution(stringchar, newData, hyperparam = matrix())
```

Arguments

<code>stringchar</code>	This is the data using which the Bayesian inference is performed.
<code>newData</code>	This is the data whose predictive probability is computed.
<code>hyperparam</code>	This determines the shape of the prior distribution of the parameters. If none is provided, default value of 1 is assigned to each parameter. This must be of size $k \times k$ where k is the number of states in the chain and the values should typically be non-negative integers.

Details

The underlying method is Bayesian inference. The probability is computed by averaging the likelihood of the new data with respect to the posterior. Since the method assumes conjugate priors, the result can be represented in a closed form (see the vignette for more details), which is what is returned.

Value

The log of the probability is returned.

Author(s)

Sai Bhargav Yalamanchi

References

Inferring Markov Chains: Bayesian Estimation, Model Comparison, Entropy Rate, and Out-of-Class Modeling, Christopher C. Strelhoff, James P. Crutchfield, Alfred Hubler, Santa Fe Institute
Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also[markovchainFit](#)**Examples**

```

sequence<- c("a", "b", "a", "a", "a", "a", "b", "a", "b", "a", "b", "a", "a",
             "b", "b", "b", "a")
hyperMatrix<-matrix(c(1, 2, 1, 4), nrow = 2,dimnames=list(c("a","b"),c("a","b")))
predProb <- predictiveDistribution(sequence[1:10], sequence[11:17], hyperparam =hyperMatrix )
hyperMatrix2<-hyperMatrix[c(2,1),c(2,1)]
predProb2 <- predictiveDistribution(sequence[1:10], sequence[11:17], hyperparam =hyperMatrix2 )
predProb2==predProb

```

preproglucacon

*Preprogluccacon DNA protein bases sequences***Description**

Sequence of bases for preproglucacon DNA protein

Usage

```
data(preproglucacon)
```

Format

A data frame with 1572 observations on the following 2 variables.

V1 a numeric vector, showing original coding

preproglucacon a character vector, showing initial of DNA bases (Adenine, Cytosine, Guanine, Thymine)

Source

Avery Henderson

References

Averuy Henderson, Fitting markov chain models on discrete time series such as DNA sequences

Examples

```

data(preproglucacon)
preproglucaconMc<-markovchainFit(data=preproglucacon$preproglucacon)

```

priorDistribution *priorDistribution*

Description

Function to evaluate the prior probability of a transition matrix. It is based on conjugate priors and therefore a Dirichlet distribution is used to model the transitions of each state.

Usage

```
priorDistribution(transMatr, hyperparam = matrix())
```

Arguments

transMatr	The transition matrix whose probability is the parameter of interest.
hyperparam	The hyperparam matrix (optional). If not provided, a default value of 1 is assumed for each and therefore the resulting probability distribution is uniform.

Details

The states (dimnames) of the transition matrix and the hyperparam may be in any order.

Value

The log of the probabilities for each state is returned in a numeric vector. Each number in the vector represents the probability (log) of having a probability transition vector as specified in corresponding the row of the transition matrix.

Note

This function can be used in conjunction with `inferHyperparam`. For example, if the user has a prior data set and a prior transition matrix, he can infer the hyperparameters using `inferHyperparam` and then compute the probability of their prior matrix using the inferred hyperparameters with `priorDistribution`.

Author(s)

Sai Bhargav Yalamanchi, Giorgio Spedicato

References

Yalamanchi SB, Spedicato GA (2015). Bayesian Inference of First Order Markov Chains. R package version 0.2.5

See Also

[predictiveDistribution](#), [inferHyperparam](#)

Examples

```
priorDistribution(matrix(c(0.5, 0.5, 0.5, 0.5),
  nrow = 2,
  dimnames = list(c("a", "b"), c("a", "b"))),
  matrix(c(2, 2, 2, 2),
  nrow = 2,
  dimnames = list(c("a", "b"), c("a", "b"))))
```

probabilityatT	<i>Calculating probability from a ctmc object</i>
----------------	---

Description

This function returns the probability of every state at time t under different conditions

Usage

```
probabilityatT(C, t, x0, useRCpp)
```

Arguments

C	A CTMC S4 object
t	final time t
x0	initial state
useRCpp	logical whether to use RCpp implementation

Details

The initial state is not mandatory, In case it is not provided, function returns a matrix of transition function at time t else it returns vector of probaabilities of transition to different states if initial state was x0

Value

returns a vector or a matrix in case x0 is provided or not respectively.

Author(s)

Vandit Jain

References

INTRODUCTION TO STOCHASTIC PROCESSES WITH R, ROBERT P. DOBROW, Wiley

Examples

```
states <- c("a", "b", "c", "d")
byRow <- TRUE
gen <- matrix(data = c(-1, 1/2, 1/2, 0, 1/4, -1/2, 0, 1/4, 1/6, 0, -1/3, 1/6, 0, 0, 0, 0),
  nrow = 4, byrow = byRow, dimnames = list(states, states))
ctmc <- new("ctmc", states = states, byrow = byRow, generator = gen, name = "testctmc")
probabilityatT(ctmc, 1, useRcpp = TRUE)
```

rain

Alofi island daily rainfall

Description

Rainfall measured in Alofi Island

Usage

```
data(rain)
```

Format

A data frame with 1096 observations on the following 2 variables.

V1 a numeric vector, showing original coding

rain a character vector, showing daily rainfall millilitres brackets

Source

Avery Henderson

References

Avery Henderson, Fitting markov chain models on discrete time series such as DNA sequences

Examples

```
data(rain)
rainMc<-markovchainFit(data=rain$rain)
```

rctmc

rctmc

Description

The function generates random CTMC transitions as per the provided generator matrix.

Usage

```
rctmc(n, ctmc, initDist = numeric(), T = 0, include.T0 = TRUE,  
      out.type = "list")
```

Arguments

n	The number of samples to generate.
ctmc	The CTMC S4 object.
initDist	The initial distribution of states.
T	The time up to which the simulation runs (all transitions after time T are not returned).
include.T0	Flag to determine if start state is to be included.
out.type	"list" or "df"

Details

In order to use the T0 argument, set n to Inf.

Value

Based on out.type, a list or a data frame is returned. The returned list has two elements - a character vector (states) and a numeric vector (indicating time of transitions). The data frame is similarly structured.

Author(s)

Sai Bhargav Yalamanchi

References

Introduction to Stochastic Processes with Applications in the Biosciences (2013), David F. Anderson, University of Wisconsin at Madison

See Also

[generatorToTransitionMatrix](#), [ctmc-class](#)

Examples

```
energyStates <- c("sigma", "sigma_star")
byRow <- TRUE
gen <- matrix(data = c(-3, 3, 1, -1), nrow = 2,
              byrow = byRow, dimnames = list(energyStates, energyStates))
molecularCTMC <- new("ctmc", states = energyStates,
                    byrow = byRow, generator = gen,
                    name = "Molecular Transition Model")

statesDist <- c(0.8, 0.2)
rctmc(n = Inf, ctmc = molecularCTMC, T = 1)
rctmc(n = 5, ctmc = molecularCTMC, initDist = statesDist, include.T0 = FALSE)
```

rmarkovchain	<i>Function to generate a sequence of states from homogeneous or non-homogeneous Markov chains.</i>
--------------	---

Description

Provided any markovchain or markovchainList objects, it returns a sequence of states coming from the underlying stationary distribution.

Usage

```
rmarkovchain(
  n,
  object,
  what = "data.frame",
  useRCpp = TRUE,
  parallel = FALSE,
  num.cores = NULL,
  ...
)
```

Arguments

n	Sample size
object	Either a markovchain or a markovchainList object
what	It specifies whether either a data.frame or a matrix (each rows represent a simulation) or a list is returned.
useRCpp	Boolean. Should RCpp fast implementation being used? Default is yes.
parallel	Boolean. Should parallel implementation being used? Default is yes.
num.cores	Number of Cores to be used
...	additional parameters passed to the internal sampler

Details

When a homogeneous process is assumed (markovchain object) a sequence is sampled of size n.
 When a non - homogeneous process is assumed, n samples are taken but the process is assumed to last from the begin to the end of the non-homogeneous markov process.

Value

Character Vector, data.frame, list or matrix

Note

Check the type of input

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchainFit](#), [markovchainSequence](#)

Examples

```
# define the markovchain object
statesNames <- c("a", "b", "c")
mcB <- new("markovchain", states = statesNames,
  transitionMatrix = matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1),
    nrow = 3, byrow = TRUE, dimnames = list(statesNames, statesNames)))

# show the sequence
outs <- rmarkovchain(n = 100, object = mcB, what = "list")

#define markovchainList object
statesNames <- c("a", "b", "c")
mcA <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1), nrow = 3,
    byrow = TRUE, dimnames = list(statesNames, statesNames)))
mcB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1), nrow = 3,
    byrow = TRUE, dimnames = list(statesNames, statesNames)))
mcC <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 0.2, 0.8, 0.1, 0.8, 0.1), nrow = 3,
    byrow = TRUE, dimnames = list(statesNames, statesNames)))
mcList <- new("markovchainList", markovchains = list(mcA, mcB, mcC))

# show the list of sequence
```

```
rmarkovchain(100, mclist, "list")
```

sales	<i>Sales Demand Sequences</i>
-------	-------------------------------

Description

Sales demand sequences of five products (A, B, C, D, E). Each row corresponds to a sequence. First row corresponds to Sequence A, Second row to Sequence B and so on.

Usage

```
data("sales")
```

Format

An object of class `matrix` (inherits from `array`) with 269 rows and 5 columns.

Details

The example can be used to fit High order multivariate markov chain.

Examples

```
data("sales")
# fitHighOrderMultivarMC(seqMat = sales, order = 2, Norm = 2)
```

show,hommc-method	<i>Function to display the details of hommc object</i>
-------------------	--

Description

This is a convenience function to display the slots of `hommc` object in proper format

Usage

```
## S4 method for signature 'hommc'
show(object)
```

Arguments

object	An object of class <code>hommc</code>
--------	---------------------------------------

states	<i>Defined states of a transition matrix</i>
--------	--

Description

This method returns the states of a transition matrix.

Usage

```
states(object)

## S4 method for signature 'markovchain'
states(object)
```

Arguments

object A discrete markovchain object

Value

The character vector corresponding to states slot.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
  byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
states(markovB)
names(markovB)
```

steadyStates	<i>Stationary states of a markovchain object</i>
--------------	--

Description

This method returns the stationary vector in matricial form of a markovchain object.

Usage

```
steadyStates(object)
```

Arguments

object A discrete markovchain object

Value

A matrix corresponding to the stationary states

Note

The steady states are identified starting from which eigenvectors correspond to identity eigenvalues and then normalizing them to sum up to unity. When negative values are found in the matrix, the eigenvalues extraction is performed on the recurrent classes submatrix.

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also

[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
    byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
steadyStates(markovB)
```

tm_abs	Single Year Corporate Credit Rating Transitions
--------	---

Description

Matrix of Standard and Poor’s Global Corporate Rating Transition Frequencies 2000 (NR Removed)

Usage

data(tm_abs)

Format

The format is: num [1:8, 1:8] 17 2 0 0 0 0 0 1 455 ... - attr(*, "dimnames")=List of 2 ..\$: chr [1:8] "AAA" "AA" "A" "BBB"\$: chr [1:8] "AAA" "AA" "A" "BBB" ...

References

European Securities and Markets Authority, 2016 <https://cerep.esma.europa.eu/cerep-web/statistics/transitionMatrice.xhtml>

Examples

data(tm_abs)

transition2Generator	Return the generator matrix for a corresponding transition matrix
----------------------	---

Description

Calculate the generator matrix for a corresponding transition matrix

Usage

transition2Generator(P, t = 1, method = "logarithm")

Arguments

- P transition matrix between time 0 and t
- t time of observation
- method "logarithm" returns the Matrix logarithm of the transition matrix

Value

A matrix that represent the generator of P

See Also[rctmc](#)**Examples**

```
mymatr <- matrix(c(.4, .6, .1, .9), nrow = 2, byrow = TRUE)
Q <- transition2Generator(P = mymatr)
expm::expm(Q)
```

`transitionProbability` *Function to get the transition probabilities from initial to subsequent states.*

Description

This is a convenience function to get transition probabilities.

Usage

```
transitionProbability(object, t0, t1)

## S4 method for signature 'markovchain'
transitionProbability(object, t0, t1)
```

Arguments

<code>object</code>	A markovchain object.
<code>t0</code>	Initial state.
<code>t1</code>	Subsequent state.

Value

Numeric Vector

Author(s)

Giorgio Spedicato

References

A First Course in Probability (8th Edition), Sheldon Ross, Prentice Hall 2010

See Also[markovchain](#)

Examples

```
statesNames <- c("a", "b", "c")
markovB <- new("markovchain", states = statesNames, transitionMatrix =
  matrix(c(0.2, 0.5, 0.3, 0, 1, 0, 0.1, 0.8, 0.1), nrow = 3,
    byrow = TRUE, dimnames=list(statesNames,statesNames)),
  name = "A markovchain Object"
)
transitionProbability(markovB,"b", "c")
```

verifyMarkovProperty *Test the first-order Markov property of an empirical sequence*

Description

Tests the null hypothesis that the conditional distribution of the next state depends only on the current state, against a second-order alternative.

Tests whether the sequence is compatible with a first-order Markov chain against a second-order alternative, by testing independence of past and future states conditional on the present state. Degrees of freedom are summed, present-state by present-state, over only the past and future states actually observed with that present state, mirroring the other functions documented on this page.

Tests whether transition probabilities are constant across consecutive blocks. Structural zeros can be supplied explicitly through a logical transition matrix.

Usage

```
verifyMarkovProperty(
  sequence,
  method = c("G", "Pearson", "simulation"),
  B = 9999,
  seed = NULL,
  verbose = TRUE
)
```

```
assessOrder(sequence, verbose = TRUE)
```

```
verifyEmpiricalToTheoretical(
  data,
  object,
  method = c("G", "Pearson", "simulation"),
  B = 9999,
  seed = NULL,
  verbose = TRUE
)
```

```
verifyHomogeneity(
  inputList,
```

```

method = c("G", "Pearson", "simulation"),
B = 9999,
seed = NULL,
verbose = TRUE
)

assessStationarity(sequence, nblocks, structural.zeros = NULL, verbose = TRUE)

```

Arguments

sequence	An empirical sequence.
method	Test statistic: "G", "Pearson", or "simulation".
B	Number of Monte Carlo replicates for simulation.
seed	Optional random seed.
verbose	Should test results be printed?
data	An empirical sequence or a matrix of transition counts.
object	A 'markovchain' object specifying theoretical probabilities.
inputList	A list whose elements are empirical sequences or matrices.
nblocks	Number of blocks, at least two.
structural.zeros	Optional logical matrix marking impossible transitions.

Value

An 'htest' object with additional package-specific components.

An 'htest' object.

An 'htest' object with observed and expected counts.

An 'htest' object with pooled and individual transition counts.

An 'htest' object.

References

Anderson, T. W. and Goodman, L. A. (1957). Statistical inference about Markov chains. **The Annals of Mathematical Statistics**, 28(1), 89–110.

Kullback, S., Kupperman, M. and Ku, H. H. (1962). Tests for Contingency Tables and Markov Chains. **Technometrics**, 4(4), 573–608.

Anderson, T. W. and Goodman, L. A. (1957). Statistical inference about Markov chains. **The Annals of Mathematical Statistics**, 28(1), 89–110.

zeros	<i>Matrix to create zeros</i>
-------	-------------------------------

Description

Matrix to create zeros

Usage

zeros(n)

Arguments

n size of the matrix

Value

a square matrix of zeros

Index

!=, markovchain, markovchain-method
(markovchain-class), 41

* **classes**

- ctmc-class, 13
- markovchain-class, 41
- markovchainList-class, 43

* **datasets**

- blanden, 7
- craigsendi, 10
- holson, 28
- kullback, 40
- preproglucacon, 59
- rain, 62
- sales, 66
- tm_abs, 69

* **package**

- markovchain-package, 4

* **statisticalTests**

- verifyMarkovProperty, 71

*, markovchain, markovchain-method
(markovchain-class), 41

*, markovchain, matrix-method
(markovchain-class), 41

*, markovchain, numeric-method
(markovchain-class), 41

*, matrix, markovchain-method
(markovchain-class), 41

*, numeric, markovchain-method
(markovchain-class), 41

.markovchainFitRcpp
(createSequenceMatrix), 11

==, markovchain, markovchain-method
(markovchain-class), 41

[, markovchain, ANY, ANY, ANY-method
(markovchain-class), 41

[[, markovchainList-method
(markovchainList-class), 43

^, markovchain, numeric-method
(markovchain-class), 41

absorbingStates, 25

absorbingStates (period), 55

absorbingStates, markovchain-method
(markovchain-class), 41

absorptionProbabilities, 5, 25

absorptionProbabilities, markovchain-method
(markovchain-class), 41

assessOrder (verifyMarkovProperty), 71

assessStationarity
(verifyMarkovProperty), 71

autoLump, 6

autoLump, markovchain-method (autoLump),
6

autoplot.markovchain, 6

blanden, 7

canonicForm (period), 55

canonicForm, markovchain-method
(markovchain-class), 41

coerce, data.frame, markovchain-method
(markovchain-class), 41

coerce, etm, markovchain-method
(markovchain-class), 41

coerce, markovchain, data.frame-method
(markovchain-class), 41

coerce, markovchain, igraph-method
(markovchain-class), 41

coerce, markovchain, matrix-method
(markovchain-class), 41

coerce, markovchain, sparseMatrix-method
(markovchain-class), 41

coerce, Matrix, markovchain-method
(markovchain-class), 41

coerce, matrix, markovchain-method
(markovchain-class), 41

coerce, msm, markovchain-method
(markovchain-class), 41

coerce, msm.est, markovchain-method
(markovchain-class), 41

- coerce, sparseMatrix, markovchain-method
(markovchain-class), 41
- coerce, table, markovchain-method
(markovchain-class), 41
- committorAB, 8
- communicatingClasses (period), 55
- communicatingClasses, markovchain-method
(markovchain-class), 41
- conditionalDistribution, 9, 20
- conditionalDistribution, markovchain-method
(markovchain-class), 41
- craigsendi, 10
- createSequenceMatrix, 11
- ctmc-class, 13
- ctmcFit, 15
- dim, ctmc-method (ctmc-class), 13
- dim, markovchain-method
(markovchain-class), 41
- dim, markovchainList-method
(markovchainList-class), 43
- entropyRate, 16
- entropyRate, markovchain-method
(entropyRate), 16
- expectedRewards, 17
- expectedRewardsBeforeHittingA, 18
- ExpectedTime, 19
- firstPassage, 20, 21
- firstPassageMultiple, 21
- fitHigherOrder, 22
- fitHighOrderMultivarMC, 23
- freq2Generator, 24
- fundamentalMatrix, 25
- generatorToTransitionMatrix, 14, 26, 63
- HigherOrderMarkovChain-class, 27
- hittingProbabilities, 27
- hittingProbabilities, markovchain-method
(markovchain-class), 41
- holson, 28
- hommc (hommc-class), 29
- hommc-class, 29
- ictmc (ictmc-class), 30
- ictmc-class, 30
- impreciseProbabilityatT, 30
- inferHyperparam, 31, 60
- initialize, ctmc_method (ctmc-class), 13
- initialize, markovchain-method
(markovchain-class), 41
- is.accessible, 32
- is.accessible, markovchain, character, character-method
(markovchain-class), 41
- is.accessible, markovchain, missing, missing-method
(markovchain-class), 41
- is.CTMCirreducible, 33
- is.irreducible, 17, 34, 36, 39
- is.irreducible, markovchain-method
(markovchain-class), 41
- is.lumpable, 35
- is.lumpable, markovchain-method
(is.lumpable), 35
- is.regular, 36
- is.regular, markovchain-method
(markovchain-class), 41
- is.stochasticallyMonotone, 37
- is.stochasticallyMonotone, ANY-method
(is.stochasticallyMonotone), 37
- is.stochasticallyMonotone, markovchain-method
(is.stochasticallyMonotone), 37
- is.stochasticallyMonotone, matrix-method
(is.stochasticallyMonotone), 37
- is.TimeReversible, 37
- kemenyConstant, 38
- kemenyConstant, markovchain-method
(kemenyConstant), 38
- kullback, 40
- lump, 40
- lump, markovchain-method (lump), 40
- markovchain, 9, 44, 56, 67, 68, 70
- markovchain (markovchain-package), 4
- markovchain-class, 41
- markovchain-package, 4
- markovchainFit, 32, 43, 46, 59, 65
- markovchainFit (createSequenceMatrix),
11
- markovchainList-class, 43
- markovchainListFit, 13, 45
- markovchainSequence, 13, 43, 46, 65
- meanAbsorptionTime, 25, 47
- meanAbsorptionTime, markovchain-method
(markovchain-class), 41
- meanFirstPassageTime, 39, 48

meanFirstPassageTime,markovchain,character-method
 (markovchain-class), 41
 meanFirstPassageTime,markovchain,missing-method
 (markovchain-class), 41
 meanNumVisits, 49
 meanNumVisits,markovchain-method
 (markovchain-class), 41
 meanRecurrenceTime, 50
 meanRecurrenceTime,markovchain-method
 (markovchain-class), 41
 multinomialConfidenceIntervals, 51

 name, 52
 name,markovchain-method (name), 52
 name<-, 52
 name<-,markovchain-method (name<-), 52
 names,markovchain-method, 53
 names<-,markovchain-method
 (markovchain-class), 41
 noofVisitsDist, 54

 ones, 55

 period, 55
 plot,ctmc,missing-method (ctmc-class),
 13
 plot,markovchain,missing-method
 (markovchain-class), 41
 predict,markovchain-method
 (markovchain-class), 41
 predict,markovchainList-method
 (markovchainList-class), 43
 predictHommc, 57
 predictiveDistribution, 32, 58, 60
 preproglucacon, 59
 print,markovchain-method
 (markovchain-class), 41
 print,markovchainList-method
 (markovchainList-class), 43
 priorDistribution, 60
 probabilityatT, 61

 rain, 62
 rctmc, 14, 15, 26, 63, 70
 recurrentClasses (period), 55
 recurrentClasses,markovchain-method
 (markovchain-class), 41
 recurrentStates (period), 55
 recurrentStates,markovchain-method
 (markovchain-class), 41

 check,markovchain, 64
 sales, 66
 seq2freqProb (fitHigherOrder), 22
 seq2matHigh (fitHigherOrder), 22
 show,hommc-method, 66
 show,markovchain-method
 (markovchain-class), 41
 show,markovchainList-method
 (markovchainList-class), 43
 sort,markovchain-method
 (markovchain-class), 41
 states, 67
 states,ctmc-method (ctmc-class), 13
 states,markovchain-method (states), 67
 steadyStates, 17, 39, 68
 steadyStates,ctmc-method (ctmc-class),
 13
 steadyStates,markovchain-method
 (markovchain-class), 41
 summary, 35
 summary,markovchain-method
 (markovchain-class), 41

 t,markovchain-method
 (markovchain-class), 41
 tm_abs, 69
 transientClasses (period), 55
 transientClasses,markovchain-method
 (markovchain-class), 41
 transientStates, 25
 transientStates (period), 55
 transientStates,markovchain-method
 (markovchain-class), 41
 transition2Generator, 69
 transitionProbability, 70
 transitionProbability,markovchain-method
 (transitionProbability), 70

 verifyEmpiricalToTheoretical
 (verifyMarkovProperty), 71
 verifyHomogeneity
 (verifyMarkovProperty), 71
 verifyMarkovProperty, 71

 zeros, 73