

Package ‘ridgetorus’

July 24, 2026

Type Package

Title PCA on the Torus via Density Ridges

Version 1.1.0

Date 2026-07-24

Description Implementation of a Principal Component Analysis (PCA) in the torus via density ridge estimation. The main function, `ridge_pca()`, obtains the relevant density ridge for bivariate sine von Mises and bivariate wrapped Cauchy distribution models and provides the associated scores and variance decomposition. Auxiliary functions for evaluating, fitting, and sampling these models are also provided. The package provides replicability to García-Portugués and Prieto-Tirado (2023) [doi:10.1007/s11222-023-10273-9](https://doi.org/10.1007/s11222-023-10273-9).

License GPL-3

LazyData true

Depends R (>= 3.5.0), Rcpp

Imports rootSolve, sdetorus, sphunif, circular

Suggests BAMBI, covr, DirStats, GGally, ggplot2, knitr, markdown, mvtnorm, numDeriv, rmarkdown, testthat, viridisLite

LinkingTo Rcpp, RcppArmadillo

URL <https://github.com/egarpor/ridgetorus>

BugReports <https://github.com/egarpor/ridgetorus/issues>

Encoding UTF-8

RoxygenNote 7.3.3

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation yes

Author Eduardo García-Portugués [aut, cre] (ORCID: <https://orcid.org/0000-0002-9224-4111>),
Arturo Prieto-Tirado [aut] (ORCID: <https://orcid.org/0000-0003-0193-2988>)

Maintainer Eduardo García-Portugués <edgarcia@est-econ.uc3m.es>
Repository CRAN
Date/Publication 2026-07-24 14:40:02 UTC

Contents

ridgetorus-package	2
biv_lrt	3
bvm	5
bwc	7
bwn	9
earthquakes	11
frechet	12
ridge_curve	13
ridge_distr	17
ridge_fourier_fit	19
ridge_pca	21
ridge_scores	23
santabarbara	25
show_ridge_pca	26
torus_dist	28
torus_pairs	29
wind	31
Index	32

ridgetorus-package	ridgetorus: <i>PCA on the Torus via Density Ridges</i>
--------------------	--

Description

Implementation of a Principal Component Analysis (PCA) in the torus via density ridge estimation. The main function, `ridge_pca()`, obtains the relevant density ridge for bivariate sine von Mises and bivariate wrapped Cauchy distribution models and provides the associated scores and variance decomposition. Auxiliary functions for evaluating, fitting, and sampling these models are also provided. The package provides replicability to García-Portugués and Prieto-Tirado (2023) <doi:10.1007/s11222-023-10273-9>.

Author(s)

Eduardo García-Portugués and Arturo Prieto-Tirado.

References

García-Portugués, E. and Prieto-Tirado, A. (2023). Toroidal PCA via density ridges. *Statistics and Computing*, 33(5):107. doi:10.1007/s11222023102739

See Also

Useful links:

- <https://github.com/egarpor/ridgetorus>
- Report bugs at <https://github.com/egarpor/ridgetorus/issues>

biv_lrt	<i>Tests of homogeneity and independence in bivariate sine von Mises and wrapped Cauchy distributions</i>
---------	---

Description

Performs the following likelihood ratio tests for the concentrations in bivariate sine von Mises and wrapped Cauchy distributions: (1) *homogeneity*: $H_0 : \kappa_1 = \kappa_2$ vs. $H_1 : \kappa_1 \neq \kappa_2$, and $H_0 : \xi_1 = \xi_2$ vs. $H_1 : \xi_1 \neq \xi_2$, respectively; (2) *independence*: $H_0 : \lambda = 0$ vs. $H_1 : \lambda \neq 0$, and $H_0 : \rho = 0$ vs. $H_1 : \rho \neq 0$. The tests (1) and (2) can be performed simultaneously.

Usage

```
biv_lrt(x, hom = FALSE, indep = FALSE, fit_mle = NULL, type, ...)
```

Arguments

x	matrix of dimension $c(n, 2)$ containing the n observations of the pair of angles.
hom	test the homogeneity hypothesis? Defaults to FALSE.
indep	test the independence hypothesis? Defaults to FALSE.
fit_mle	output of <code>fit_bvm_mle</code> or <code>fit_bwc_mle</code> with <code>hom = FALSE</code> . Computed internally if not provided.
type	either "bvm" (bivariate sine von Mises) or "bwc" (bivariate wrapped Cauchy).
...	optional parameters passed to <code>fit_bvm_mle</code> and <code>fit_bwc_mle</code> , such as <code>start</code> , <code>lower</code> , or <code>upper</code> .

Value

A list with class `htest`:

statistic	the value of the likelihood ratio test statistic.
p.value	the p -value of the test (computed using the asymptotic distribution).
alternative	a character string describing the alternative hypothesis.
method	description of the type of test performed.
df	degrees of freedom.
data.name	a character string giving the name of <code>x</code> .
fit_mle	maximum likelihood fit.
fit_null	maximum likelihood fit under the null hypothesis.

References

- Kato, S. and Pewsey, A. (2015). A Möbius transformation-induced distribution on the torus. *Biometrika*, 102(2):359–370. doi:[10.1093/biomet/asv003](https://doi.org/10.1093/biomet/asv003)
- Singh, H., Hnizdo, V., and Demchuk, E. (2002). Probabilistic model for two dependent circular variables. *Biometrika*, 89(3):719–723. doi:[10.1093/biomet/89.3.719](https://doi.org/10.1093/biomet/89.3.719)

See Also

[fit_bvm_mle](#) and [fit_bwc_mle](#) for the fits compared by the tests, and [ridge_pca](#), which uses these tests to enforce the sticky horizontal/vertical/diagonal ridges.

Examples

```
## Bivariate sine von Mises

# Homogeneity
n <- 200
mu <- c(0, 0)
kappa_0 <- c(1, 1, 0.5)
kappa_1 <- c(0.7, 0.1, 0.25)
samp_0 <- r_bvm(n = n, mu = mu, kappa = kappa_0)
samp_1 <- r_bvm(n = n, mu = mu, kappa = kappa_1)
biv_lrt(x = samp_0, hom = TRUE, type = "bvm")
biv_lrt(x = samp_1, hom = TRUE, type = "bvm")

# Independence
kappa_0 <- c(0, 1, 0)
kappa_1 <- c(1, 0, 1)
samp_0 <- r_bvm(n = n, mu = mu, kappa = kappa_0)
samp_1 <- r_bvm(n = n, mu = mu, kappa = kappa_1)
biv_lrt(x = samp_0, indep = TRUE, type = "bvm")
biv_lrt(x = samp_1, indep = TRUE, type = "bvm")

# Independence and homogeneity
kappa_0 <- c(3, 3, 0)
kappa_1 <- c(3, 1, 0)
samp_0 <- r_bvm(n = n, mu = mu, kappa = kappa_0)
samp_1 <- r_bvm(n = n, mu = mu, kappa = kappa_1)
biv_lrt(x = samp_0, indep = TRUE, hom = TRUE, type = "bvm")
biv_lrt(x = samp_1, indep = TRUE, hom = TRUE, type = "bvm")

## Bivariate wrapped Cauchy

# Homogeneity
xi_0 <- c(0.5, 0.5, 0.25)
xi_1 <- c(0.7, 0.1, 0.5)
samp_0 <- r_bwc(n = n, mu = mu, xi = xi_0)
samp_1 <- r_bwc(n = n, mu = mu, xi = xi_1)
biv_lrt(x = samp_0, hom = TRUE, type = "bwc")
biv_lrt(x = samp_1, hom = TRUE, type = "bwc")
```

```

# Independence
xi_0 <- c(0.1, 0.5, 0)
xi_1 <- c(0.3, 0.5, 0.2)
samp_0 <- r_bwc(n = n, mu = mu, xi = xi_0)
samp_1 <- r_bwc(n = n, mu = mu, xi = xi_1)
biv_lrt(x = samp_0, indep = TRUE, type = "bwc")
biv_lrt(x = samp_1, indep = TRUE, type = "bwc")

# Independence and homogeneity
xi_0 <- c(0.2, 0.2, 0)
xi_1 <- c(0.1, 0.2, 0.1)
samp_0 <- r_bwc(n = n, mu = mu, xi = xi_0)
samp_1 <- r_bwc(n = n, mu = mu, xi = xi_1)
biv_lrt(x = samp_0, indep = TRUE, hom = TRUE, type = "bwc")
biv_lrt(x = samp_1, indep = TRUE, hom = TRUE, type = "bwc")

```

bvm

Density evaluation, sampling, and parameter estimation of the bivariate sine von Mises distribution

Description

Computation of the density and normalizing constant $T(\kappa_1, \kappa_2, \lambda)$ of the bivariate sine von Mises

$$f(\theta_1, \theta_2) = T(\kappa_1, \kappa_2, \lambda) \exp\{\kappa_1 \cos(\theta_1 - \mu_1) + \kappa_2 \cos(\theta_2 - \mu_2) + \lambda \sin(\theta_1 - \mu_1) \sin(\theta_2 - \mu_2)\}.$$

Simulation of samples from a bivariate sine von Mises.

Maximum likelihood and method of moments estimation of the parameters $(\mu_1, \mu_2, \kappa_1, \kappa_2, \lambda)$.

Usage

```

d_bvm(x, mu, kappa, log_const = NULL)

const_bvm(kappa, M = 25, MC = 10000)

r_bvm(n, mu, kappa)

fit_bvm_mm(
  x,
  lower = c(0, 0, -30),
  upper = c(30, 30, 30),
  start = NULL,
  M = 25,
  hom = FALSE,
  indep = FALSE,
  ...
)
```

```

fit_bvm_mle(
  x,
  start = NULL,
  M = 25,
  lower = c(-pi, -pi, 0, 0, -30),
  upper = c(pi, pi, 30, 30, 30),
  hom = FALSE,
  indep = FALSE,
  ...
)

```

Arguments

x	matrix of size $c(n_x, 2)$ with the angles on which the density is evaluated.
mu	circular means of the density, a vector of length 2.
kappa	vector of length 3 with the concentrations (κ_1, κ_2) and the dependence parameter λ of the density.
log_const	logarithm of the normalizing constant. Computed internally if NULL (default).
M	truncation of the series expansion for computing the normalizing constant. Defaults to 25.
MC	Monte Carlo replicates for computing the normalizing constant when there is no series expansion. Defaults to 1e4.
n	sample size.
lower, upper	bounds for the optimizer. For <code>fit_bvm_mle</code> , vectors of length 5 defaulting to $c(-\pi, -\pi, 0, 0, -30)$ and $c(\pi, \pi, 30, 30, 30)$. For <code>fit_bvm_mm</code> (concentrations only), vectors of length 3 defaulting to $c(0, 0, -30)$ and $c(30, 30, 30)$.
start	a vector of length 5 with the initial values for the maximum likelihood optimizer. The first two entries are disregarded in <code>fit_bvm_mm</code> . If NULL (default), the starting values are taken from the estimation of marginal von Mises in <code>fit_bvm_mm</code> . In <code>fit_bvm_mle</code> , the method of moments estimates are employed.
hom	assume a homogeneous distribution with equal marginal concentrations? Defaults to FALSE.
indep	set the dependence parameter to zero? Defaults to FALSE.
...	further parameters passed to mleOptimWrapper .

Value

- `d_bvm`: a vector of length n_x with the density evaluated at `x`.
- `const_bvm`: the value of the normalizing constant $T(\kappa_1, \kappa_2, \lambda)$.
- `r_bvm`: a matrix of size $c(n, 2)$ with the random sample.
- `fit_bvm_mm`, `fit_bvm_mle`: a list with the estimated parameters $(\mu_1, \mu_2, \kappa_1, \kappa_2, \lambda)$. `fit_bvm_mle` also returns the object `opt` with the optimization summary.

References

- Mardia, K. V., Hughes, G., Taylor, C. C., and Singh, H. (2008). A multivariate von Mises with applications to bioinformatics. *Canadian Journal of Statistics*, 36(1):99–109. doi:10.1002/cjs.5550360110
- Singh, H., Hnizdo, V., and Demchuk, E. (2002). Probabilistic model for two dependent circular variables. *Biometrika*, 89(3):719–723. doi:10.1093/biomet/89.3.719

See Also

[bwc](#) and [bwn](#) for the other toroidal distributions, [ridge_bvm](#) for its density ridge, and [ridge_pca](#) for the toroidal PCA built on this model.

Examples

```
## Density evaluation

mu <- c(0, 0)
kappa <- 3:1
nth <- 50
th <- seq(-pi, pi, l = nth)
x <- as.matrix(expand.grid(th, th))
const <- const_bvm(kappa = kappa)
d <- d_bvm(x = x, mu = mu, kappa = kappa, log_const = log(const))
filled.contour(th, th, matrix(d, nth, nth), col = viridisLite::viridis(31),
               levels = seq(0, max(d), l = 30))

## Sampling and estimation

n <- 100
samp <- r_bvm(n = n, mu = mu, kappa = kappa)
(param_mm <- fit_bvm_mm(samp))
(param_mle <- fit_bvm_mle(samp)$opt$par)
```

bwc

Density evaluation, sampling, and parameter estimation of the bivariate wrapped Cauchy distribution

Description

Computation of the density of a bivariate wrapped Cauchy:

$$f(\theta_1, \theta_2) = c(\xi_1, \xi_2, \rho) \{c_0(\xi_1, \xi_2, \rho) - c_1(\xi_1, \xi_2, \rho) \cos(\theta_1 - \mu_1) - c_2(\xi_1, \xi_2, \rho) \cos(\theta_2 - \mu_2) - c_3(\xi_1, \xi_2, \rho) \cos(\theta_1 - \mu_1) \cos(\theta_2 - \mu_2)\}$$

Simulation of samples from a bivariate wrapped Cauchy.

Maximum likelihood and method of moments estimation of the parameters $(\mu_1, \mu_2, \xi_1, \xi_2, \rho)$.

Usage

```

d_bwc(x, mu, xi)

r_bwc(n, mu, xi)

fit_bwc_mm(x, hom = FALSE, indep = FALSE)

fit_bwc_mle(
  x,
  start = NULL,
  lower = c(-pi, -pi, 0, 0, -1 + 0.001),
  upper = c(pi, pi, 1 - 0.001, 1 - 0.001, 1 - 0.001),
  hom = FALSE,
  indep = FALSE,
  ...
)

```

Arguments

<code>x</code>	matrix of size $c(n \times 2)$ with the angles on which the density is evaluated.
<code>mu</code>	circular means of the density, a vector of length 2.
<code>xi</code>	a vector of length 3 with the marginal concentrations (ξ_1, ξ_2) , and the dependence parameter ρ .
<code>n</code>	sample size.
<code>hom</code>	assume a homogeneous distribution with equal marginal concentrations? Defaults to FALSE.
<code>indep</code>	set the dependence parameter to zero? Defaults to FALSE.
<code>start</code>	a vector of length 5 with the initial values for the maximum likelihood optimizer. If NULL (default), the method of moments estimates are employed.
<code>lower, upper</code>	vectors of length 5 with the bounds for the likelihood optimizer. Default to $c(-\pi, -\pi, 0, 0, -1 + 1e-3)$ and $c(\pi, \pi, 1 - 1e-3, 1 - 1e-3, 1 - 1e-3)$.
<code>...</code>	further parameters passed to mleOptimWrapper .

Value

- `d_bwc`: a vector of length $n \times$ with the density evaluated at `x`.
- `r_bwc`: a matrix of size $c(n, 2)$ with the random sample.
- `fit_bwc_mm`, `fit_bwc_mle`: a list with the parameters $(\mu_1, \mu_2, \xi_1, \xi_2, \rho)$. `fit_bwc_mle` also returns the object `opt` with the optimization summary.

Author(s)

The original code for `r_bwc` was supplied by Arthur Pewsey.

References

Kato, S. and Pewsey, A. (2015). A Möbius transformation-induced distribution on the torus. *Biometrika*, 102(2):359–370. doi:[10.1093/biomet/asv003](https://doi.org/10.1093/biomet/asv003)

See Also

[bvm](#) and [bwn](#) for the other toroidal distributions, [ridge_bwc](#) for its density ridge, and [ridge_pca](#) for the toroidal PCA built on this model.

Examples

```
## Density evaluation

mu <- c(0, 0)
xi <- c(0.3, 0.5, 0.4)
nth <- 50
th <- seq(-pi, pi, l = nth)
x <- as.matrix(expand.grid(th, th))
d <- d_bwc(x = x, mu = mu, xi = xi)
filled.contour(th, th, matrix(d, nth, nth), col = viridisLite::viridis(20),
               levels = seq(0, max(d), l = 20))

## Sampling and estimation

n <- 100
samp <- r_bwc(n = n, mu = mu, xi = xi)
(param_mm <- fit_bwc_mm(samp))
(param_mle <- fit_bwc_mle(samp)$opt$par)
```

bwn

Density evaluation, sampling, and parameter estimation of the bivariate wrapped normal distribution

Description

Computation of the density of the bivariate wrapped normal.

Simulation of pairs of samples from a bivariate wrapped normal.

Maximum likelihood estimation of the parameters $(\boldsymbol{\mu}, \boldsymbol{\Sigma})$.

Usage

```
d_bwn(x, mu, Sigma, kmax = 2)
```

```
r_bwn(n, mu, Sigma)
```

```
fit_bwn_mle(
  x,
  kmax = 2,
```

```

lower = c(-pi, -pi, 0.001, 0.001, -1),
upper = c(pi, pi, 20, 20, 1),
...
)

```

Arguments

<code>x</code>	matrix of size $c(n_x, 2)$ with the angles on which the density is evaluated.
<code>mu</code>	circular means of the density, a vector of length 2.
<code>Sigma</code>	covariance matrix of size $c(2, 2)$.
<code>kmax</code>	integer number up to truncate the wrapped normal series in $-kmax:kmax$. Defaults to 2.
<code>n</code>	sample size.
<code>lower, upper</code>	vector of length 5 with the bounds of the parameters for the maximum likelihood optimizer.
<code>...</code>	further parameters passed to mleOptimWrapper .

Value

- `d_bwn`: a vector of length n_x with the density evaluated at `x`.
- `r_bwn`: a matrix of size $c(n, 2)$ with the random sample.
- `fit_bwn_mle`: a list with the parameters (μ, Σ) and the object `opt` containing the optimization summary.

See Also

[bvm](#) and [bwc](#) for the toroidal distributions used by [ridge_pca](#), and [ridge_bwn](#) for the density ridge of this model.

Examples

```

## Density evaluation

mu <- c(0, 0)
Sigma <- 3 * matrix(c(1.5, 0.75, 0.75, 1), nrow = 2, ncol = 2)
nth <- 50
th <- seq(-pi, pi, l = nth)
x <- as.matrix(expand.grid(th, th))
d <- d_bwn(x = x, mu = mu, Sigma = Sigma)
filled.contour(th, th, matrix(d, nth, nth), col = viridisLite::viridis(31),
               levels = seq(0, max(d), l = 30))

## Sampling and estimation

n <- 100
samp <- r_bwn(n = 100, mu = mu, Sigma = Sigma)
(param_mle <- fit_bwn_mle(samp)$opt$par)

```

earthquakes	<i>Japanese earthquakes dataset</i>
-------------	-------------------------------------

Description

Pre-earthquake direction of steepest descent and the direction of lateral ground movement before and after, respectively, an earthquake in Noshiro (Japan) in 1983.

Usage

earthquakes

Format

A data frame with 678 rows and 2 variables:

theta1 Direction of steepest descent.

theta2 Direction of lateral ground movement.

Details

The direction is measured in radians in $[0, 2\pi)$ with $0 / \frac{\pi}{2} / \pi / \frac{3\pi}{2} / 2\pi$ representing the East / North / West / South / East directions.

References

Hamada, M. and O'Rourke, T. (1992). Case Studies of Liquefaction & Lifeline Performance During Past Earthquake. Volume 1: Japanese Case Studies. Technical Report NCEER-92-0001. National Center for Earthquake Engineering Research, University at Buffalo. doi:[10.1016/0886-7798\(93\)90146m](https://doi.org/10.1016/0886-7798(93)90146m)

Jones, M. C., Pewsey, A., and Kato, S. (2015). On a class of circulars: copulas for circular distributions. *Annals of the Institute of Statistical Mathematics*, 67(5):843–862. doi:[10.1007/s10463014-04936](https://doi.org/10.1007/s10463014-04936)

Rivest, L.-P. (1997). A decentred predictor for circular-circular regression. *Biometrika*, 84(3):717–726. doi:[10.1093/biomet/84.3.717](https://doi.org/10.1093/biomet/84.3.717)

See Also

[ridge_pca](#) for the toroidal PCA of this dataset.

Examples

```
# Load data
data("earthquakes")

# Transform the data into [-pi, pi)
earthquakes <- sdetorus::toPiInt(earthquakes)
plot(earthquakes, xlab = expression(theta[1]), ylab = expression(theta[2]),
```

```

      xlim = c(-pi, pi), ylim = c(-pi, pi), axes = FALSE)
sdetorus::torusAxis()

# Perform TR-PCA
fit <- ridge_pca(x = earthquakes)
show_ridge_pca(fit)

```

frechet

Fréchet statistics on the torus

Description

Computes the Fréchet mean, variance, and standard deviation of a sample on the d -torus $[-l, l]^d$, $d \geq 1$, with $-l \equiv l$ identified.

Usage

```

frechet_mean(x, l = pi, N = 500, draw_plot = FALSE)

frechet_ss(x, l = pi, N = 500, draw_plot = FALSE)

```

Arguments

<code>x</code>	sample of angles on $[-l, l)$, a vector or a matrix.
<code>l</code>	half-period of the circular data. Can be a vector of length <code>ncol(x)</code> if <code>x</code> is a matrix. Defaults to <code>pi</code> .
<code>N</code>	size of the grid in $[-l, l)$ for the exhaustive search of the mean. Defaults to <code>5e2</code> .
<code>draw_plot</code>	draw a diagnostic plot showing the Fréchet loss function? Defaults to <code>FALSE</code> .

Value

- `frechet_mean`: a list with the marginal Fréchet means (`mu`), variances (`var`), and standard deviations (`sd`).
- `frechet_ss`: a list with the Fréchet variances (`var`) and the cumulative proportion of total variance explained (`var_exp`).

See Also

[torus_dist](#) for the underlying toroidal distance, and [ridge_scores](#), whose explained variance is computed with `frechet_ss`.

Examples

```
## Circular data

# Sample from a wrapped normal
x <- sdetorus::toPiInt(rnorm(n = 5e2, mean = 2, sd = 1))
frechet_mean(x = x)

# Sample from a bimodal distribution
x <- sdetorus::toPiInt(rnorm(n = 5e2, mean = c(1, -2), sd = c(0.5, 0.75)))
frechet_mean(x = x)

# Periodic data in [-2, 2)
x <- sdetorus::toInt(rnorm(n = 5e2, mean = c(-2, 1), sd = 2:1),
                    a = -2, b = 2)
frechet_mean(x = x, l = 2)

## Toroidal data

# Sample from a multivariate wrapped normal
n <- 50
S <- rbind(c(2.5, -0.2, 0.5),
           c(-0.2, 1.5, -0.5),
           c(0.5, -0.5, 0.75))
x <- sdetorus::toPiInt(mvtnorm::rmvnorm(n, mean = c(0, 1.5, -2), sigma = S))
(f <- frechet_mean(x = x))

# Total Fréchet variance is sum of marginal variances
sum(torus_dist(x, y = f$mu, squared = TRUE)) / n
sum(f$var)

# Cumulative proportion of variances
frechet_ss(x)
```

ridge_curve

Fourier-fitted ridge curve and related utilities

Description

Given the angles theta in $[-\pi, \pi)$, `ridge_curve` computes the Fourier-fitted ridge curve $(\theta, r_1(\theta))$ or $(r_2(\theta), \theta)$, where

$$r_j(\theta) := \text{atan2}(S_m(\theta), C_m(\theta))$$

with $C_m(x) := a_0/2 + \sum_{k=1}^m a_k \cos(kx)$ and $S_m(x) := \sum_{k=1}^m b_k \sin(kx)$ for $j = 1, 2$. `der_ridge_curve` and `dist_ridge_curve` compute the derivatives of and the distances along these curves, respectively. `arclength_ridge_curve` provides a uniform grid of the ridge curve using the arc-length parametrization. `proj_ridge_curve` gives the ridge's θ for which the curve is closer to any point on $[-\pi, \pi)^2$.

Usage

```
ridge_curve(  
  theta,  
  mu = c(0, 0),  
  coefs = list(cos_a = c(0, 0), sin_b = 0),  
  ind_var = 1,  
  at2 = TRUE  
)  
  
der_ridge_curve(  
  theta,  
  mu = c(0, 0),  
  coefs = list(cos_a = c(0, 0), sin_b = 0),  
  ind_var = 1,  
  norm = NULL,  
  at2 = TRUE  
)  
  
dist_ridge_curve(  
  alpha,  
  mu = c(0, 0),  
  coefs = list(cos_a = c(0, 0), sin_b = 0),  
  ind_var = 1,  
  N = 500,  
  der = TRUE,  
  shortest = TRUE,  
  at2 = TRUE  
)  
  
arclength_ridge_curve(  
  mu = c(0, 0),  
  coefs = list(cos_a = c(0, 0), sin_b = 0),  
  ind_var = 1,  
  N = 500,  
  L = 500,  
  at2 = TRUE  
)  
  
proj_ridge_curve(  
  x,  
  mu = c(0, 0),  
  coefs = list(cos_a = c(0, 0), sin_b = 0),  
  ind_var = 1,  
  N = 500,  
  ridge_curve_grid = NULL,  
  arclength = FALSE,  
  at2 = TRUE  
)
```

Arguments

theta	vector θ of size nth.
mu	a vector of size 2 giving (μ_1, μ_2) . Defaults to <code>c(0, 0)</code> .
coefs	list of coefficients <code>cos_a</code> (a_k) and <code>sin_b</code> (b_k) giving the Fourier fit of the ridge curve. Defaults to <code>list(cos_a = c(0, 0), sin_b = 0)</code> . See examples.
ind_var	index j of the variable that parametrizes the ridge. Defaults to 1.
at2	do the <code>atan2</code> fit instead of the sine fit (only using S_m)? Defaults to TRUE. <code>at2 = FALSE</code> is not recommended to use.
norm	normalize tangent vectors? If different from NULL (the default), the vectors are normalized to have the given norm.
alpha	a vector of size 2.
N	number of discretization points for approximating curve lengths. Defaults to 5e2.
der	use derivatives to approximate curve lengths? Defaults to TRUE.
shortest	return the shortest possible distance? Defaults to TRUE.
L	number of discretization points for computing the arc-length parametrization curve lengths. Defaults to 5e2.
x	a matrix of size <code>c(nx, 2)</code> with angular coordinates.
ridge_curve_grid	if provided, the <code>ridge_curve</code> evaluated at a grid of size N. If not provided, it is computed internally. Useful for saving computations.
arclength	use the arc-length parametrization to compute the projections? This yields a more uniform grid for searching the projections. Defaults to TRUE.

Value

- `ridge_curve`: a matrix of size `c(nth, 2)` with the ridge curve evaluated at theta.
- `der_ridge_curve`: a matrix of size `c(nth, 2)` with the derivatives of the ridge curve evaluated at theta.
- `dist_ridge_curve`: the distance between two points along the ridge curve, a non-negative scalar.
- `proj_ridge_curve`: a list with (1) the theta's that give the points in the ridge curve that are the closest (in the flat torus distance) to `x` (a matrix of size `c(nx, 2)`); (2) the indexes of `ridge_curve_grid` in which those theta's were obtained.
- `arclength_ridge_curve`: a vector of size N giving the theta angles that yield a uniform-length grid of the ridge curve.

See Also

[ridge_fourier_fit](#) to obtain `coefs` from a ridge, [ridge_scores](#) for the associated PCA scores, and [ridge_pca](#) for the full toroidal PCA.

Examples

```

mu <- c(-0.5, 1.65)
th <- seq(-pi, pi, l = 200)
K <- 5
coefs <- list(cos_a = 1 / (1:(K + 1))^3, sin_b = 1 / (1:K)^3)
rid1 <- ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = 1)
rid2 <- ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = 2)
plot(mu[1], mu[2], xlim = c(-pi, pi), ylim = c(-pi, pi), axes = FALSE,
     xlab = expression(theta[1]), ylab = expression(theta[2]),
     pch = "*", col = 5, cex = 3)
sdetorus::linesTorus(rid1[, 1], rid1[, 2], col = 1)
sdetorus::linesTorus(rid2[, 1], rid2[, 2], col = 2)
abline(v = mu[1], lty = 3, col = 5)
abline(h = mu[2], lty = 3, col = 5)
points(ridge_curve(theta = mu[1], mu = mu, coefs = coefs, ind_var = 1),
       col = 1)
points(ridge_curve(theta = mu[2], mu = mu, coefs = coefs, ind_var = 2),
       col = 2)
sdetorus::torusAxis()

## der_ridge_curve

th <- seq(-pi, pi, l = 10)
mu <- c(0.5, 1.5)
K <- 5
coefs <- list(cos_a = 1 / (1:(K + 1))^3, sin_b = 1 / (1:K)^3)
rid1 <- ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = 1)
rid2 <- ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = 2)
v1 <- der_ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = 1,
                      norm = 0.5)
v2 <- der_ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = 2,
                      norm = 0.5)
points(rid1, pch = 16, col = 1)
points(rid2, pch = 16, col = 2)
arrows(x0 = rid1[, 1], y0 = rid1[, 2],
       x1 = (rid1 + v1)[, 1], y1 = (rid1 + v1)[, 2],
       col = 3, angle = 5, length = 0.1)
arrows(x0 = rid2[, 1], y0 = rid2[, 2],
       x1 = (rid2 + v2)[, 1], y1 = (rid2 + v2)[, 2],
       col = 4, angle = 5, length = 0.1)

## dist_ridge_curve

# Distances accuracy
a <- c(-pi / 2, pi)
mu <- c(-pi / 2, pi / 2)
dist_ridge_curve(alpha = a, mu = mu, coefs = coefs, der = TRUE, N = 1e6)
dist_ridge_curve(alpha = a, mu = mu, coefs = coefs, der = FALSE, N = 1e6)
dist_ridge_curve(alpha = a, mu = mu, coefs = coefs, der = TRUE, N = 1e2)
dist_ridge_curve(alpha = a, mu = mu, coefs = coefs, der = FALSE, N = 1e2)

## arclength_ridge_curve

```



```

mu <- c(-pi / 2, pi / 2)
alpha <- arclength_ridge_curve(mu = mu, coefs = coefs, ind_var = 1, N = 25)
alpha <- sdetorus::toPiInt(c(alpha, alpha[1]))
rid <- ridge_curve(theta = alpha, mu = mu, coefs = coefs, ind_var = 1)
plot(mu[1], mu[2], pch = "*", col = 5, cex = 3, xlim = c(-pi, pi),
      ylim = c(-pi, pi), axes = FALSE, xlab = expression(theta[1]),
      ylab = expression(theta[2]))
sdetorus::linesTorus(rid[, 1], rid[, 2], col = 1, pch = 16)
points(rid[, 1], rid[, 2], pch = 16, col = 1)
abline(v = mu[1], lty = 3, col = 5)
abline(h = mu[2], lty = 3, col = 5)
sdetorus::torusAxis()

## proj_ridge_curve

mu <- c(0, 0)
n <- 25
x <- matrix(runif(2 * n, -pi, pi), nrow = n, ncol = 2)
col <- rainbow(n)
th <- seq(-pi, pi, l = 100)
old_par <- par(no.readonly = TRUE)
par(mfrow = c(1, 2))
for (j in 1:2) {

  plot(x, xlim = c(-pi, pi), ylim = c(-pi, pi), axes = FALSE,
        xlab = expression(theta[1]), ylab = expression(theta[2]), col = col)
  rid <- ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = j)
  sdetorus::linesTorus(x = rid[, 1], y = rid[, 2], lwd = 2)
  abline(v = mu[1], lty = 3)
  abline(h = mu[2], lty = 3)
  points(mu[1], mu[2], pch = "*", cex = 3)
  sdetorus::torusAxis()
  theta_projs <- proj_ridge_curve(x = x, mu = mu, coefs = coefs, ind_var = j,
                                ridge_curve_grid = rid)$theta_proj
  projs <- ridge_curve(theta = theta_projs, mu = mu, coefs = coefs,
                       ind_var = j)
  points(projs, col = col, pch = 3)
  for (i in 1:n) {

    sdetorus::linesTorus(x = c(x[i, 1], projs[i, 1]),
                          y = c(x[i, 2], projs[i, 2]), col = col[i], lty = 3)

  }

}
par(old_par)

```

Description

Computation of the connected component of the density ridge of in a given set of points or, if not specified, in a regular grid on $[-\pi, \pi)$.

Usage

```
ridge_bvm(mu, kappa, eval_points, subint_1, subint_2)

ridge_bwc(mu, xi, eval_points, subint_1, subint_2)

ridge_bwn(mu, Sigma, kmax = 2, eval_points, subint_1, subint_2)
```

Arguments

mu	circular means of the density, a vector of length 2.
kappa	vector of length 3 with the concentrations (κ_1, κ_2) and the dependence parameter λ of the density.
eval_points	evaluation points for the ridge.
subint_1	number of points for θ_1 .
subint_2	number of points for θ_2 at each θ_1 .
xi	a vector of length 3 with the marginal concentrations (ξ_1, ξ_2) , and the dependence parameter ρ .
Sigma	covariance matrix of size c(2, 2).
kmax	integer number up to truncate the wrapped normal series in $-kmax:kmax$. Defaults to 2.

Value

A matrix of size c(subint_1, 2) containing the points of the connected component of the ridge.

References

Ozertem, U. and Erdogmus, D. (2011). Locally defined principal curves and surfaces. *Journal of Machine Learning Research*, 12(34):1249–1286. doi:[10.6083/M4ZG6Q60](https://doi.org/10.6083/M4ZG6Q60)

See Also

[ridge_fourier_fit](#) and [ridge_curve](#) to turn the ridge into a Fourier curve, and [ridge_pca](#) for the full toroidal PCA.

Examples

```
# Bivariate von Mises
mu <- c(0, 0)
kappa <- c(0.3, 0.5, 0.4)
nth <- 100
th <- seq(-pi, pi, l = nth)
x <- as.matrix(expand.grid(th, th))
```

```

d <- d_bvm(x = x, mu = mu, kappa = kappa)
image(th, th, matrix(d, nth, nth), col = viridisLite::viridis(20))
ridge <- ridge_bvm(mu = mu, kappa = kappa, subint_1 = 5e2,
                  subint_2 = 5e2)
points(ridge)

# Bivariate wrapped Cauchy
mu <- c(0, 0)
xi <- c(0.3, 0.6, 0.25)
nth <- 100
th <- seq(-pi, pi, l = nth)
x <- as.matrix(expand.grid(th, th))
d <- d_bwc(x = x, mu = mu, xi = xi)
image(th, th, matrix(d, nth, nth), col = viridisLite::viridis(20))
ridge <- ridge_bwc(mu = mu, xi = xi, subint_1 = 5e2, subint_2 = 5e2)
points(ridge)

# Bivariate wrapped normal
mu <- c(0, 0)
Sigma <- matrix(c(10, 3, 3, 5), nrow = 2)
nth <- 100
th <- seq(-pi, pi, l = nth)
x <- as.matrix(expand.grid(th, th))
d <- d_bwn(x = x, mu = mu, Sigma = Sigma)
image(th, th, matrix(d, nth, nth), col = viridisLite::viridis(20))
ridge <- ridge_bwn(mu = mu, Sigma = Sigma, subint_1 = 5e2,
                  subint_2 = 5e2)
points(ridge)

```

ridge_fourier_fit *Fourier expansion of a given curve*

Description

Computation of the Fourier expansion coefficients of a given curve.

Usage

```
ridge_fourier_fit(curve, K = 15, norm_prop = 1, N = 1280, at2 = TRUE)
```

Arguments

curve	points of the curve.
K	number of terms in the Fourier expansion. Defaults to 15.
norm_prop	percentage of explained norm. Defaults to 1.
N	number of Gaussian quadrature points, passed to Gauss_Legen_nodes . Defaults to 1280.
at2	do the atan2 fit instead of the sine fit (only using S_m)? Defaults to TRUE. at2 = FALSE is not recommended to use.

Value

The coefficients of the fit (see [ridge_curve](#)). A list with entries:

<code>cos_a</code>	contains $a_0, a_1, \dots, a_m$.
<code>sin_b</code>	contains $b_1, \dots, b_m$.

See Also

[ridge_curve](#) to evaluate the fitted curve, [ridge_bvm](#) for the ridge to fit, and [ridge_pca](#) for the full toroidal PCA.

Examples

```
# Zero mean
ridge0 <- ridge_bvm(mu = c(0, 0), kappa = c(1, 2, -5), subint_1 = 5e2,
                    subint_2 = 5e2)
coefs <- ridge_fourier_fit(ridge0)
th <- seq(-pi, pi, l = 500)
plot(ridge0, xlim = c(-pi, pi), ylim = c(-pi, pi))
points(ridge_curve(th, mu = c(0, 0), coefs = coefs, at2 = TRUE), col = 3,
       cex = 0.5)

# Non-zero mean from a zero-mean ridge
mu <- c(1.4, 2)
ridge1 <- ridge_bvm(mu = mu, kappa = c(1, 2, -5), subint_1 = 5e2,
                    subint_2 = 5e2) # Just for plot
plot(ridge1, xlim = c(-pi, pi), ylim = c(-pi, pi))
points(mu[1], mu[2], col = 4, pch = "*", cex = 5)
points(ridge_curve(th, mu = mu, coefs = coefs), col = 3, cex = 0.5)

# Other zero-mean example
mu <- c(0, 0)
ridge <- ridge_bwc(mu = mu, xi = c(0.3, 0.5, 0.7), subint_1 = 5e2,
                  subint_2 = 5e2)
plot(ridge, xlim = c(-pi, pi), ylim = c(-pi, pi))
coefs <- ridge_fourier_fit(ridge)
points(ridge_curve(th, mu = mu, coefs = coefs), col = 4, cex = 0.5)

# Another zero-mean example
mu <- c(0, 0)
ridge <- ridge_bwc(mu = mu, xi = c(0.8, 0.1, 0.75), subint_1 = 5e2,
                  subint_2 = 5e2)
plot(ridge, xlim = c(-pi, pi), ylim = c(-pi, pi))
coefs <- ridge_fourier_fit(ridge)
points(ridge_curve(th, mu = mu, coefs = coefs), col = 4, cex = 0.5)
```

Description

This function computes the whole process of toroidal PCA via density ridges on a given sample: parameter estimation of the underlying distribution, estimation of the connected component of the ridge, and determination of its Fourier expansion from which to obtain the first and second scores.

Usage

```
ridge_pca(
  x,
  type = c("auto", "bvm", "bwc")[1],
  N = 500,
  K = 15,
  scale = TRUE,
  lrts = TRUE,
  alpha = 0.05,
  at2 = TRUE,
  ...
)
```

Arguments

<code>x</code>	matrix of dimension $c(n, 2)$ containing the n observations of the pair of angles.
<code>type</code>	either "bvm" (bivariate sine von Mises), "bwc" (bivariate wrapped Cauchy), or "auto" (default). "auto" performs both fits and uses the one with lowest BIC.
<code>N</code>	number of discretization points for approximating curve lengths. Defaults to 5e2.
<code>K</code>	number of terms in the Fourier expansion. Defaults to 15.
<code>scale</code>	scale the resulting scores to $[-\pi, \pi)^2$? Defaults to TRUE.
<code>lrts</code>	run <code>biv_lrt</code> to check the null hypothesis of homogeneous concentration parameters using likelihood ratio tests? If TRUE (default), enforces the special horizontal/vertical/diagonal cases to become "sticky" fits.
<code>alpha</code>	significance level for the homogeneity test.
<code>at2</code>	do the <code>atan2</code> fit instead of the sine fit (only using S_m)? Defaults to TRUE. <code>at2 = FALSE</code> is not recommended to use.
<code>...</code>	optional parameters passed to <code>fit_bvm_mle</code> and <code>fit_bwc_mle</code> , such as <code>start</code> , <code>lower</code> , or <code>upper</code> .

Value

A list with:

<code>mu_hat</code>	estimated circular means of the sample.
<code>coefs_hat</code>	estimated Fourier coefficients.
<code>ind_var</code>	indexing variable.
<code>scores</code>	scores for each of the sample points.
<code>var_exp</code>	percentage of explained variance.
<code>fit_mle</code>	maximum likelihood fit.
<code>bic_fit</code>	BIC of the fit.
<code>data</code>	original sample.
<code>scales</code>	vector of length 2 with the scale limits for the axes.
<code>type</code>	type of fit performed.
<code>p_hom</code>	p -value of the homogeneity test.
<code>p_indep</code>	p -value of the independence test.

See Also

[ridge_curve](#), [ridge_scores](#), and [ridge_fourier_fit](#) for the ridge-fitting building blocks; [ridge_bvm](#) for the density ridge; [biv_lrt](#) for the sticky-fit tests; and [show_ridge_pca](#) to visualize the result.

Examples

```
## Bivariate von Mises

n <- 100
x <- r_bvm(n = n, mu = c(1, 2), kappa = c(0.4, 0.4, 0.5))
fit <- ridge_pca(x = x, type = "bvm")
show_ridge_pca(fit = fit, col_data = "red")

x <- r_bvm(n = n, mu = c(2, 1), kappa = c(1, 2, 0))
fit <- ridge_pca(x = x, type = "bvm")
show_ridge_pca(fit = fit, col_data = "red")

x <- r_bvm(n = n, mu = c(2, 1), kappa = c(3, 2, 0))
fit <- ridge_pca(x = x, type = "bvm")
show_ridge_pca(fit = fit, col_data = "red")

## Bivariate wrapped Cauchy

x <- r_bwc(n = n, mu = c(1, 2), xi = c(0.2, 0.2, 0.5))
fit <- ridge_pca(x = x, type = "bwc")
show_ridge_pca(fit = fit, col_data = "red")

x <- r_bwc(n = n, mu = c(1, 2), xi = c(0.2, 0.8, 0))
fit <- ridge_pca(x = x, type = "bwc")
show_ridge_pca(fit = fit, col_data = "red")
```

```
x <- r_bwc(n = n, mu = c(1, 2), xi = c(0.5, 0.2, 0))
fit <- ridge_pca(x = x, type = "bwc")
show_ridge_pca(fit = fit, col_data = "red")
```

ridge_scores

Scores and scales for Fourier-fitted ridge curves

Description

Computation of PCA scores for [Fourier-fitted ridge curves](#). The scores are defined as follows:

- First scores: signed distances along the ridge curve of the data projections to μ .
- Second scores: signed toroidal distances from the data points to their ridge projections.

The scores can be scaled to $(-\pi, \pi)$ or remain as $(l/2, m_2)$, where l is the length of the curve and m_2 is the maximal absolute second score.

Usage

```
ridge_scores(
  x,
  mu = c(0, 0),
  coefs = list(cos_a = c(0, 0), sin_b = 0),
  ind_var = 1,
  N = 500,
  scale = TRUE,
  at2 = TRUE
)

max_score_2(
  mu = c(0, 0),
  coefs = list(cos_a = c(0, 0), sin_b = 0),
  ind_var = 1,
  L = 25,
  f = 2,
  at2 = TRUE
)
```

Arguments

x	a matrix of size $c(n \times 2)$ with angular coordinates.
mu	a vector of size 2 giving (μ_1, μ_2) . Defaults to $c(0, 0)$.
coefs	list of coefficients $\cos_a(a_k)$ and $\sin_b(b_k)$ giving the Fourier fit of the ridge curve. Defaults to $\text{list}(\cos_a = c(0, 0), \sin_b = 0)$. See examples.
ind_var	index j of the variable that parametrizes the ridge. Defaults to 1.

N	number of discretization points for approximating curve lengths. Defaults to 5e2.
scale	scale the resulting scores to $[-\pi, \pi)^2$? Defaults to TRUE.
at2	do the atan2 fit instead of the sine fit (only using S_m)? Defaults to TRUE. at2 = FALSE is not recommended to use.
L	grid along the variable ind_var used for searching the maximum allowed second score. Defaults to 25.
f	factor for shrinking the grid on the variable that is different to ind_var. Defaults to 2.

Details

The mean μ corresponds to the first score being null.

Value

ridge_scores returns a list with:

scores a matrix of size $c(n_x, 2)$ with the ridge scores.
scales a vector of length 2 with the scale limits for the axes.

max_score_2 computes the maximum allowed second score to rescale if scale = TRUE.

See Also

[ridge_curve](#) for the fitted ridge, [frechet](#) for the variance decomposition of the scores, and [ridge_pca](#) for the full toroidal PCA.

Examples

```
mu <- c(-0.5, 1.65)
th <- seq(-pi, pi, l = 200)
K <- 5
coefs <- list(cos_a = 1 / (1:(K + 1))^3, sin_b = 1 / (1:K)^3)
n <- 10
col <- rainbow(n)

set.seed(13213)
old_par <- par(no.readonly = TRUE)
par(mfrow = c(2, 2))
for (j in 1:2) {

  # Simulate synthetic data close to the ridge curve
  rid <- ridge_curve(theta = th, mu = mu, coefs = coefs, ind_var = j)
  ind <- sort(sample(length(th), size = n))
  eps <- 0.25 * matrix(runif(2 * n, -1, 1), nrow = n, ncol = 2)
  x <- sdetorus::toPiInt(rid[ind, ] + eps)

  # Plot ridge and synthetic data, with signs from the second scores
  s <- ridge_scores(x, mu = mu, coefs = coefs, ind_var = j)$scores
```



```

plot(x, xlim = c(-pi, pi), ylim = c(-pi, pi), axes = FALSE,
     xlab = expression(theta[1]), ylab = expression(theta[2]), col = col,
     pch = ifelse(sign(s[, 2]) == 1, "+", "-"), cex = 1.25)
sdetorus::linesTorus(rid[, 1], rid[, 2], lwd = 2)
abline(v = mu[1], lty = 3)
abline(h = mu[2], lty = 3)
points(mu[1], mu[2], pch = "*", cex = 3)
sdetorus::torusAxis()

# Projections
theta_projs <- proj_ridge_curve(x = x, mu = mu, coefs = coefs,
                               ind_var = j, ridge_curve_grid = rid,
                               )$theta_proj
projs <- ridge_curve(theta = theta_projs, mu = mu, coefs = coefs,
                    ind_var = j)
for (i in 1:n) {

  sdetorus::linesTorus(x = c(x[i, 1], projs[i, 1]),
                      y = c(x[i, 2], projs[i, 2]),
                      col = col[i], lty = 3)

}

# Scores plot
plot(s, xlim = c(-pi, pi), ylim = c(-pi, pi), axes = FALSE,
     xlab = "Score 1", ylab = "Score 2", col = col,
     pch = ifelse(sign(s[, 2]) == 1, "+", "-"))
sdetorus::torusAxis()
abline(v = 0, lty = 3)
abline(h = 0, lty = 3)
points(0, 0, pch = "*", cex = 3)

}
par(old_par)

```

santabarbara

Santa Barbara currents

Description

The Santa Barbara Channel is a coastal area in California. This dataset contains the sea currents in the four areas present in the data application in García-Portugués and Prieto-Tirado (2023). Precisely, it contains the 24-hour speed-weighted mean of the currents' direction in each of the four areas downloaded from the [NOAA High Frequency Radar National Server](#).

Usage

```
santabarbara
```

Format

A data frame with 1092 rows and 4 variables:

- A** Sea current direction at zone A.
- B** Sea current direction at zone B.
- C** Sea current direction at zone C.
- D** Sea current direction at zone D.

Details

The selection of these four areas is motivated by previous studies on the Santa Barbara currents, like Auad et al. (1998). The direction is measured in radians in $[-\pi, \pi)$ with $-\pi / -\frac{\pi}{2} / 0 / \frac{\pi}{2} / \pi$ representing the East / South / West / North / East directions. The script performing the data preprocessing is available at [data-acquisition.R](#). The data was retrieved on 2022-10-21.

References

- Auad, G., Hendershott, M. C., and Winant, C. D. (1998). Wind-induced currents and bottom-trapped waves in the Santa Barbara Channel. *Journal of Physical Oceanography*, 28(1):85–102. [doi:10.1175/15200485\(1998\)028<0085:WICABT>2.0.CO;2](#)
- García-Portugués, E. and Prieto-Tirado, A. (2023). Toroidal PCA via density ridges. *Statistics and Computing*, 33(5):107. [doi:10.1007/s11222023102739](#)

See Also

[ridge_pca](#) for the toroidal PCA of this dataset.

Examples

```
# Load data
data("santabarbara")
AB_zone <- santabarbara[c("A", "B")]

# Perform TR-PCA
fit <- ridge_pca(x = AB_zone)
show_ridge_pca(fit)
```

show_ridge_pca

Illustration of toroidal PCA via density ridges

Description

Shows the scores computation for PCA via density ridges on $[-\pi, \pi)^2$.

Usage

```
show_ridge_pca(
  fit,
  n_max = 500,
  projs = TRUE,
  projs_lines = TRUE,
  signs = TRUE,
  col_data = 1,
  col_projs = c(3, 4),
  main = "",
  N = 500,
  at2 = TRUE
)
```

Arguments

<code>fit</code>	the output of <code>ridge_pca</code> .
<code>n_max</code>	maximum number of data points to draw. These are sampled from the data provided. Defaults to 500.
<code>projs</code>	draw projections? Defaults to TRUE.
<code>projs_lines</code>	draw projection lines? Defaults to TRUE.
<code>signs</code>	plot the original data points with + and - facets depending on the signs of the second scores? Defaults to TRUE.
<code>col_data</code>	color(s) for the data points. Defaults to 1.
<code>col_projs</code>	a vector of size 2 giving the colors for the curve-projected data and the ridge curve, respectively. Defaults to <code>c(3, 4)</code> .
<code>main</code>	caption of the plot. Empty by default.
<code>N</code>	number of discretization points for approximating curve lengths. Defaults to 5e2.
<code>at2</code>	do the <code>atan2</code> fit instead of the sine fit (only using S_m)? Defaults to TRUE. <code>at2 = FALSE</code> is not recommended to use.

Value

Nothing, the functions are called to produce plots.

See Also

`ridge_pca` to compute `fit` and `torus_pairs` for a pairs plot of the scores.

Examples

```
# Generate data
set.seed(987654321)
n <- 50
S1 <- rbind(c(1, -0.7), c(-0.7, 1))
```

```

S2 <- rbind(c(1, 0.5), c(0.5, 1))
x <- rbind(mvtnorm::rmvnorm(n, mean = c(0, pi / 2), sigma = S1),
           mvtnorm::rmvnorm(n, mean = c(pi, -pi / 2), sigma = S2))
x <- sdetorus::toPiInt(x)
col <- rainbow(2)[rep(1:2, each = n)]

# ridge_pca and its visualization
fit <- ridge_pca(x = x, at2 = FALSE)
show_ridge_pca(fit = fit, col_data = col, at2 = FALSE)
fit2 <- ridge_pca(x = x, at2 = TRUE)
show_ridge_pca(fit = fit2, col_data = col, at2 = TRUE)

```

torus_dist

Toroidal distances

Description

Computation of distances on $[-\pi, \pi)^d$, $d \geq 1$, between two sets of observations.

Usage

```
torus_dist(x, y, squared = FALSE)
```

Arguments

x a matrix of size $c(n \times d)$ with angles on $[-\pi, \pi)$.

y either a matrix with the same size as **x** or a vector of length `ncol(x)`.

squared return the squared distance? Defaults to FALSE.

Details

The maximal distance on $[-\pi, \pi)^d$ is $\sqrt{d}\pi$.

Value

A vector of size $n \times$ with the distances between the observations of **x** and **y**.

See Also

[frechet](#) for Fréchet means and variances built on this distance.

Examples

```
# Illustration of torus distances
n <- 10
x <- matrix(runif(2 * n, -pi, pi), nrow = n, ncol = 2)
y <- c(pi / 2, pi / 3)
col <- rainbow(n)
plot(x, xlim = c(-pi, pi), ylim = c(-pi, pi), axes = FALSE, col = col,
      xlab = expression(theta[1]), ylab = expression(theta[2]), pch = 16)
sdetorus::torusAxis()
points(y[1], y[2], col = 1, pch = 17)
for (i in 1:n) {

  sdetorus::linesTorus(x = c(x[i, 1], y[1]),
                       y = c(x[i, 2], y[2]), lty = 2, col = col[i])

}
text(x = x, labels = sprintf("%.2f", torus_dist(x, y)), col = col, pos = 1)
```

torus_pairs

Toroidal pairs plot

Description

Pairs plots for data on $[-\pi, \pi)^d$, $d \geq 2$. The diagonal panels contain kernel density estimates tailored to circular data.

Usage

```
torus_pairs(
  x,
  max_dim = 10,
  columns = NULL,
  col_data = 1,
  ylim_dens = c(0, 1.5),
  bwd = "ROT",
  scales = rep(pi, ncol(x))
)
```

Arguments

<code>x</code>	a matrix of size $c(n \times d)$ with angles on $[-\pi, \pi)$.
<code>max_dim</code>	the maximum number of scores to produce the scores plot. Defaults to 10.
<code>columns</code>	if specified, the variables to be plotted. If <code>NULL</code> (the default), the first <code>max_dim</code> variables are plotted.
<code>col_data</code>	color(s) for the data points. Defaults to 1.
<code>ylim_dens</code>	common ylim for the diagonal plots. Defaults to <code>c(0, 1.5)</code> .

bwd	type of bandwidth selector used in the kernel density plots. Either "ROT", "EMI", "AMI", "LSCV", or "LCV". See bw_dir_pi and bw_dir_cv . Defaults to "ROT".
scales	scales of the torus. Defaults to <code>rep(pi, ncol(x))</code> .

Details

The default bandwidth selector is the Rule-Of-Thumb (ROT) selector in García-Portugués (2013). It is fast, yet it may oversmooth non-unimodal densities. The EMI selector gives more flexible fits.

Value

A [ggplot](#). The density plots show the [Fréchet means](#) (red bars) and the Fréchet standard deviations (gray text).

References

García-Portugués, E. (2013). Exact risk improvement of bandwidth selectors for kernel density estimation with directional data. *Electronic Journal of Statistics*, 7:1655–1685. doi:[10.1214/13-ejs821](#)

See Also

[ridge_pca](#) to obtain the scores and [show_ridge_pca](#) to visualize a fitted ridge.

Examples

```
# Generate data
n <- 50
set.seed(123456)
x <- sdetorus::toPiInt(rbind(
  mvtnorm::rmvnorm(n = n, mean = c(-pi, -pi) / 2,
    sigma = diag(0.1, nrow = 2)),
  mvtnorm::rmvnorm(n = n, mean = c(-3 * pi / 2, 0) / 2,
    sigma = diag(0.1, nrow = 2)),
  mvtnorm::rmvnorm(n = n, mean = c(0, pi / 2),
    sigma = diag(0.1, nrow = 2))
))
col <- rainbow(3)[rep(1:3, each = n)]

# Torus pairs
torus_pairs(x, col_data = col)

fit <- ridge_pca(x = x)
torus_pairs(fit$scores, col_data = col)
```

wind	<i>Texas wind dataset</i>
------	---------------------------

Description

Wind direction at 6:00 and 7:00 from June 1, 2003 to June 30, 2003, in radians, measured at a weather station in Texas coded as C28-1.

Usage

```
wind
```

Format

A data frame with 30 rows and 2 variables:

theta1 Direction at 6:00 am.

theta2 Direction at 7:00 am.

Details

The direction is measured in radians in $[-\pi, \pi)$ with $-\pi/-\frac{\pi}{2}/0/\frac{\pi}{2}/\pi$ representing the East/South/West/North/East directions.

References

Johnson, R. A. and Wehrly, T. (1977). Measures and models for angular correlation and angular-linear correlation. *Journal of the Royal Statistical Society. Series B (Methodological)*, 39(2):222–229. <https://www.jstor.org/stable/2984799>

See Also

[ridge_pca](#) for the toroidal PCA of this dataset.

Examples

```
# Load data
data("wind")
plot(wind, xlab = expression(theta[1]), ylab = expression(theta[2]),
      xlim = c(-pi, pi), ylim = c(-pi, pi), axes = FALSE)
sdetorus::torusAxis()

# Perform TR-PCA
fit <- ridge_pca(x = wind)
show_ridge_pca(fit)
```

Index

* datasets

- earthquakes, 11
- santabarbara, 25
- wind, 31

Fourier-fitted ridge curves, 23

arclength_ridge_curve (ridge_curve), 13

biv_lrt, 3, 21, 22

bvm, 5, 9, 10

bw_dir_cv, 30

bw_dir_pi, 30

bwc, 7, 7, 10

bwn, 7, 9, 9

const_bvm (bvm), 5

d_bvm (bvm), 5

d_bwc (bwc), 7

d_bwn (bwn), 9

der_ridge_curve (ridge_curve), 13

dist_ridge_curve (ridge_curve), 13

earthquakes, 11

fit_bvm_mle, 3, 4, 21

fit_bvm_mle (bvm), 5

fit_bvm_mm (bvm), 5

fit_bwc_mle, 3, 4, 21

fit_bwc_mle (bwc), 7

fit_bwc_mm (bwc), 7

fit_bwn_mle (bwn), 9

frechet, 12, 24, 28

frechet_mean (frechet), 12

frechet_ss (frechet), 12

Fréchet means, 30

Gauss_Legen_nodes, 19

ggplot, 30

max_score_2 (ridge_scores), 23

mleOptimWrapper, 6, 8, 10

proj_ridge_curve (ridge_curve), 13

r_bvm (bvm), 5

r_bwc (bwc), 7

r_bwn (bwn), 9

ridge_bvm, 7, 20, 22

ridge_bvm (ridge_distr), 17

ridge_bwc, 9

ridge_bwc (ridge_distr), 17

ridge_bwn, 10

ridge_bwn (ridge_distr), 17

ridge_curve, 13, 18, 20, 22, 24

ridge_distr, 17

ridge_fourier_fit, 15, 18, 19, 22

ridge_pca, 4, 7, 9–11, 15, 18, 20, 21, 24, 26, 27, 30, 31

ridge_scores, 12, 15, 22, 23

ridgetorus (ridgetorus-package), 2

ridgetorus-package, 2

santabarbara, 25

show_ridge_pca, 22, 26, 30

torus_dist, 12, 28

torus_pairs, 27, 29

wind, 31