

Package ‘stickyr’

July 13, 2026

Type Package
Title Data Frames with Persistent Columns and Attributes
Version 0.1.3
Description Provides data frames that hold certain columns and attributes persistently for data processing in 'dplyr'.
License MIT + file LICENSE
Encoding UTF-8
Imports dplyr, generics, pillar, purrr, rlang (>= 1.0.0), tibble, tidyselect, vctrs
Suggests testthat (>= 3.0.0)
Config/testthat/edition 3
URL <https://github.com/UchidaMizuki/stickyr>
BugReports <https://github.com/UchidaMizuki/stickyr/issues>
Config/roxygen2/version 8.0.0
NeedsCompilation no
Author Mizuki Uchida [aut, cre]
Maintainer Mizuki Uchida <uchidamizuki@vivaldi.net>
Repository CRAN
Date/Publication 2026-07-12 23:10:02 UTC

Contents

as_sticky_tibble	2
is_sticky_tibble	2
new_sticky_tibble	3
Index	4

as_sticky_tibble	<i>Coerce objects to sticky tibble</i>
------------------	--

Description

'as_sticky_tibble' turns an object to a sticky tibble ('sticky_tbl_df').

Usage

as_sticky_tibble(x, ...)

Arguments

- x An object.
- ... Unused, for extensibility.

Value

A sticky tibble ('sticky_tbl_df') object.

is_sticky_tibble	<i>Test if the object is a sticky tibble</i>
------------------	--

Description

Test if the object is a sticky tibble

Usage

is_sticky_tibble(x)

Arguments

- x An object

Value

TRUE if an object inherits from sticky_tbl_df, sticky_grouped_df or sticky_rowwise_df class.

new_sticky_tibble	<i>Constructs a tibble with persistent columns and attributes</i>
-------------------	---

Description

`new_sticky_tibble` constructs a tibble with persistent columns and attributes. These persistent columns can be hidden.

Usage

```
new_sticky_tibble(  
  x = list(),  
  cols = NULL,  
  col_show = tidyselect::everything(),  
  col_summary = list(),  
  attrs = character(),  
  ...,  
  class = character(),  
  class_grouped_df = class,  
  class_rowwise_df = class  
)
```

Arguments

<code>x</code>	A tibble-like object.
<code>cols</code>	Columns to be kept persistently.
<code>col_show</code>	Which persistent columns to show? By default, all are displayed.
<code>col_summary</code>	A named list of functions to summarise persistent columns.
<code>attrs</code>	Names of attributes to be kept persistently.
<code>...</code>	Additional attributes.
<code>class</code>	Subclasses.
<code>class_grouped_df</code>	Subclasses of <code>grouped_df</code> . By default, it is the same as <code>class</code> .
<code>class_rowwise_df</code>	Subclasses of <code>rowwise_df</code> . By default, it is the same as <code>class</code> .

Value

A sticky tibble (`sticky_tbl_df`) object.

Index

`as_sticky_tibble`, [2](#)

`is_sticky_tibble`, [2](#)

`new_sticky_tibble`, [3](#)